

REGIONE SICILIA
PROVINCIA DI TRAPANI
COMUNE DI ALCAMO
LOCALITÀ MONTELEONE

Oggetto:

**PROGETTO DEFINITIVO PER LA COSTRUZIONE E L'ESERCIZIO DI UN IMPIANTO
AGRO-FOTOVOLTAICO AVENTE POTENZA DI PICCO PARI A 25.01 MW E POTENZA DI IMMISSIONE
22.37 MW E RELATIVE OPERE DI CONNESSIONE**

Sezione:

SEZIONE A - RELAZIONI GENERALI

Elaborato:

STIMA DI PRODUCIBILITA'

Nome file stampa:

FV.ALC01.PD.A.13.pdf

Codifica Regionale:

RS06REL0010A0

Scala:

Formato di stampa:

A4

Nome elaborato:

FV.ALC01.PD.A.13

Tipologia:

R

Proponente:

E-WAY 8 S.r.l.

Piazza di San Lorenzo in Lucina, 4
00186 ROMA (RM)
P.IVA. 16771051006



E-WAY 8 S.R.L.
P.zza di San Lorenzo in Lucina, 4
00186 - Roma
G.E./P.Iva 16771051006
PEC: e-way8srl@legalmail.it

Progettazione:

E-WAY 8 S.r.l.

Piazza di San Lorenzo in Lucina, 4
00186 ROMA (RM)
P.IVA. 16771051006



CODICE

REV. n.

DATA REV.

REDAZIONE

VERIFICA

VALIDAZIONE

FV.ALC01.PD.A.13

00

11/2023

C.Amorevole

A.Bottone

A.Bottone

E-WAY 8 S.r.l.

Sede legale
Piazza di San Lorenzo in Lucina, 4
00186 ROMA (RM)
PEC: e-way8srl@legalmail.it tel. +39 0694414500



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	2 di 13

INDICE

1	<i>PREMESSA</i>	5
2	<i>INTRODUZIONE</i>	6
3	<i>DATI CLIMATICI</i>	8
4	<i>RISULTATI</i>	10
5	<i>RICADUTE AMBIENTALI DEL PROGETTO</i>	11
6	<i>ALLEGATI</i>	13



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	3 di 13

INDICE DELLE FIGURE

<i>Figura 1: Schema funzionamento Back-Tracking.....</i>	<i>7</i>
<i>Figura 2: Meteo per Case Frasca - Typical Metereological Year.....</i>	<i>9</i>



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	4 di 13

INDICE DELLE TABELLE

<i>Tabella 1: Dati metereologici di irraggiamento per il sito di progetto</i>	<i>9</i>
<i>Tabella 2: Principali caratteristiche di potenza installata ed energia prodotta</i>	<i>10</i>
<i>Tabella 3: Bilancio di emissione di CO₂</i>	<i>11</i>



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	5 di 13

1 PREMESSA

IL PRESENTE ELABORATO È RIFERITO AL PROGETTO PER LA COSTRUZIONE E L'ESERCIZIO DI UN IMPIANTO AGRO-FOTOVOLTAICO, SITO IN ALCAMO (TP), LOCALITÀ MONTELEONE.

In particolare, l'impianto in progetto ha una potenza installata pari a 25,01 MW e una potenza nominale di 22,37 MW e presenta la seguente configurazione:

1. Un generatore fotovoltaico suddiviso in 11 sottocampi, costituiti da moduli fotovoltaici bifacciali aventi potenza unitaria pari a 710 Wp cadauno ed installati su strutture ad inseguimento solare mono-assiali (tracker);
2. Una stazione integrata per la conversione e trasformazione dell'energia elettrica detta "Power Station" per ogni sottocampo dell'impianto;
3. Una Cabina di Raccolta e Misura;
4. Elettrodotto interno in cavo interrato per l'interconnessione delle Power Station di cui al punto 2, con la Cabina di Raccolta e Misura;
5. Elettrodotto esterno in cavo interrato per l'interconnessione della Cabina di Raccolta e Misura in antenna a 36 kV con una nuova stazione elettrica di trasformazione (SE) della RTN a 220/36 kV, da inserire in entra - esce sulla linea RTN a 220 kV "Partinico - Partanna";

Titolare dell'iniziativa proposta è la società E-Way 8 S.R.L., avente sede legale in Piazza di San Lorenzo in Lucina, 4 – 00186 Roma (RM), P.IVA 16771051006



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	6 di 13

2 INTRODUZIONE

Il presente documento costituisce la relazione di stima di producibilità energetica dell'impianto agrofotovoltaico proposto.

Tale stima è stata ottenuta caratterizzando l'impianto all'interno del **software per sistemi fotovoltaici PVSystem**.

Il progetto prevede l'installazione di **35224 moduli fotovoltaici** di marca Mysolar, modello GOLD N-Type e potenza pari a **710 W** (marca e modello del pannello sono stati scelti in via del tutto preliminare e possono essere adeguati o ridefiniti in una fase avanzata del progetto). I moduli sono installati su strutture atte a garantire la massima captazione di irraggiamento seguendo il percorso solare e consentendo, di conseguenza, ai moduli di essere sempre nella posizione ottimale di lavoro. Tali strutture sono dette "tracker" o "inseguitori solari", proprio per questa loro caratteristica funzionale.

I moduli vengono alloggiati in numero di 28 per ogni tracker in modo tale da far coincidere la singola struttura con la stringa elettrica, l'unità minima elettrica di impianto. I tracker/stringhe vengono quindi a loro volta raccolti in quadri di stringhe o "combiner box", i quali semplificano il collegamento con le Power Station, sede dei principali componenti elettrici quali inverter, trasformatore, quadri di misura e controllo, protezioni principali.

La struttura elettrica dell'impianto è chiaramente esposta ed approfondita nell'apposita documentazione dello schema unifilare.

Si vuole evidenziare il ricorso ad un ulteriore sistema di efficientamento produttivo del campo fotovoltaico: il sistema di Back Tracking, il quale consente di ridurre le perdite per auto-ombreggiamento, cioè le perdite da ombreggiamento indotto dai tracker stessi alle file retrostanti. Ciò avviene per mezzo di un sistema logico-adattivo che gestisce contemporaneamente piccoli gruppi di tracker, al fine di ottimizzare dunque le prestazioni del campo FV.




Figura 1: Schema funzionamento Back-Tracking



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	8 di 13

3 DATI CLIMATICI

Il **PVGIS – PhotoVoltaic Geographical Information System** è un sistema sviluppato dal JRC (Joint Research Centre) della Commissione Europea a partire dal 2001. Gli obiettivi principali del progetto sono:

- La ricerca scientifica ai fini della valutazione della risorsa energetica solare;
- Effettuare studi sui miglioramenti di performance dei sistemi fotovoltaici;
- La diffusione di conoscenze e dati riguardanti l'irraggiamento solare e le performance fotovoltaiche ad esso collegate.

Ad oggi la copertura territoriale dei database PVGIS riguarda la totalità dell'Europa e dell'Africa e gran parte dell'Asia e dell'America.

Il PVGIS consente un accesso libero e gratuito ad una grande serie di dati:

- Potenziale fotovoltaico per diverse tecnologie e configurazioni di impianto, sia questo un impianto stand-alone che connesso alla rete;
- Dati di temperatura e radiazione solare, sia in forma di medie mensili che di profili giornalieri;
- Serie storiche dei valori orari di radiazione solare e performance FV;
- Dati TMY – Typical Meteorological Year per 9 differenti parametri climatici;
- Mappe stampabili dell'irraggiamento solare e della potenzialità fotovoltaica.

L'attendibilità dei dati PVGIS è internazionalmente riconosciuta, questi possono essere dunque utilizzati per l'elaborazione statistica della stima di radiazione solare del sito in progetto.

Si riportano di seguito i dati meteorologici assunti:

	GlobHor kWh/m ²	DiffHor kWh/m ²	T_Amb °C	GlobInc kWh/m ²	GlobEff kWh/m ²	EArray MWh	E_Grid MWh	PR ratio
January	71.0	34.55	11.08	102.2	95.1	133.0	127.6	0.897
February	79.6	40.26	9.10	110.2	103.7	145.8	139.9	0.912
March	145.0	53.88	11.04	201.8	192.3	262.1	238.9	0.851
April	180.1	63.93	14.77	243.3	234.0	304.9	292.6	0.864
May	224.5	68.21	18.60	296.2	285.3	359.8	345.4	0.838
June	223.1	69.71	23.77	289.5	278.9	351.2	315.7	0.784
July	246.3	62.50	28.25	329.4	318.2	392.2	376.6	0.822
August	204.4	63.43	26.93	276.0	265.6	339.9	326.4	0.850
September	150.2	56.50	22.33	207.0	198.3	266.0	255.4	0.887
October	114.7	45.40	17.11	163.3	155.1	212.8	189.2	0.832
November	79.3	33.14	14.90	116.8	109.0	150.5	144.5	0.889
December	72.4	31.63	11.01	110.0	101.4	141.7	136.1	0.889
Year	1790.7	623.17	17.46	2445.6	2336.9	3060.1	2888.2	0.849

Tabella 1: Dati meteorologici di irraggiamento per il sito di progetto




Figura 2: Meteo per Casa Valdibella - Typical Meteorological Year



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	10 di 13

4 RISULTATI

I risultati completi dell'analisi di producibilità svolta sono mostrati nei report allegati alla presente relazione.

Si riportano qui, brevemente, i risultati complessivi di produzione dell'impianto:

POTENZA DI PICCO (MW _p)	25,01
POTENZA AC (MW _{AC})	22,37
ENERGIA PRODOTTA P50 (MWh/anno)	52578
PRODUZIONE SPECIFICA P50 (kWh/kWp/anno)	2103
ENERGIA PRODOTTA P90 (MWh/anno)	50502
PRODUZIONE SPECIFICA P90 (kWh/kWp/anno)	2020

Tabella 2: Principali caratteristiche di potenza installata ed energia prodotta

I valori tabellati rappresentano:

- Potenza di picco: essa è la potenza installata d'impianto intesa come somma complessiva della potenza dei pannelli che lo costituiscono;
- Potenza AC: intesa come potenza nominale d'impianto, che nel progetto in esame coincide con la potenza complessiva degli inverter costituenti il campo fotovoltaico;
- Energia prodotta P50: rappresenta il valore di energia prodotta in un anno che ha la probabilità del 50% di essere superata;
- Produzione specifica P50: rappresenta il valore di produzione specifica in un anno che ha la probabilità del 50% di essere superato;
- Energia prodotta P90: rappresenta il valore di energia prodotta in un anno che ha la probabilità del 90% di essere superata;
- Produzione specifica P90: rappresenta il valore di produzione specifica in un anno che ha la probabilità del 90% di essere superato.

I valori P90 e P50 sono risultati da un'analisi probabilistico/statistica. Questo approccio presuppone che, nell'arco di diversi anni di funzionamento, la distribuzione delle rese annuali segua una legge che si assume essere la distribuzione gaussiana (o "normale"). Essa è funzione di due parametri, ossia il valore medio e la deviazione standard (denominata sigma o RMS) principalmente funzione dell'incertezza e della variabilità dei dati meteo.

Altri risultati legati all'analisi di producibilità dell'impianto sono consultabili nei documenti in allegato.



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	11 di 13

5 RICADUTE AMBIENTALI DEL PROGETTO

Un utile indicatore per definire il risparmio di combustibile derivante dall'utilizzo di fonti energetiche rinnovabili è il **Life Cycle Emissions (LCE)**. Esso rappresenta le potenziali emissioni di CO₂ associate a un dato componente installativo o ammontare energetico nell'arco di tutto il ciclo di vita dell'impianto, e può comprendere le fasi di produzione, messa in opera, gestione, dismissione, ecc. Nel calcolare tale parametro si può ricorrere alle **T.E.P.** ossia le **Tonnellate Equivalenti di Petrolio** necessarie per la realizzazione di 1 MWh di energia da fonte rinnovabile fotovoltaica, ovvero alla **Grey Energy** intesa come l'energia impiegata per la produzione di un componente seguito da un fattore di conversione per trasformare l'energia in un valore LCE.

Il LCE è un parametro fondamentale per il calcolo del **bilancio di emissione del carbonio totale** per un impianto PV. Quest'ultimo rappresenta la differenza tra le emissioni di CO₂ risparmiate e prodotte, e dipende da 4 fattori chiave:

- Energia immessa in rete (E Grid): la produzione energetica, o rendimento energetico, dell'impianto PV per il primo anno (può essere stimato anche per gli anni successivi al 1°);
- Ciclo di vita del sistema (Project lifetime): è la durata di vita dell'impianto PV data in anni;
- LCE della rete (LCE Grid): è dato in gCO₂/kWh e rappresenta l'ammontare medio di emissioni di CO₂ per unità di Energia elettrica prodotta dalla rete;
- LCE dell'impianto PV (LCE System): è dato in gCO₂/kWh e rappresenta l'ammontare medio di emissioni di CO₂ causate dalla costruzione e messa in opera dell'impianto fotovoltaico.

Emissioni generate	584093 tCO ₂
Emissioni risparmiate	667222,8 tCO ₂
Produzione annuale	52578 MWh/yr
LCE di rete	423 gCO ₂ /kWh
Ciclo di vita d'impianto	30 anni
Degradazione annuale stimata	1,0 %

Tabella 3: Bilancio di emissione di CO₂

Di seguito si riporta un'equazione utile al calcolo del bilancio di carbonio totale dell'impianto:

$$E \text{ Grid} \cdot \text{Project lifetime} \cdot LCE \text{ Grid} - LCE \text{ System} = \text{Carbon balance}$$



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	12 di 13

I valori dei termini dell'equazione sono di seguito specificati:

$$52578 \text{ MWh} \cdot 30 \text{ years} \cdot 423 \frac{\text{gCO}_2}{\text{kWh}} - 584093 \text{ tCO}_2 = 667222 \text{ tCO}_2$$

Il calcolo dei valori di LCE inoltre, dipende dalle categorie per le quali viene calcolato e da scelte progettuali. Nel calcolo appena descritto le categorie sono suddivisibili in 3 macro: **produzione dei moduli PV, bilancio del sistema impianto (BoS: Balance of System) ed eventuali apporti aggiuntivi (manutenzione, dismissione, ecc.)**. Naturalmente è preferibile utilizzare valori di LCE messi direttamente a disposizione dal produttore o dal fornitore o ricorrendo a banche dati riconosciute (ECOINVENT, Carbon Trust, ecc). Tali valori del LCE sono ottenuti a partire da:

- Caratteristiche e quantità di moduli impiegati;
- modalità di spostamento dei moduli che generalmente sono il trasporto via mare e via terra. Per il progetto in esame è stato previsto che il paese di produzione sia la Cina, regione contraddistinta per essere tra i principali produttori di pannelli;
- caratteristiche e quantità degli elementi di supporto dei pannelli, dei fabbricati quali cabine di raccolta e misura, delle strutture per ospitare inverter, trasformatori, combiner box, ed altri elementi elettromeccanici dell'impianto;
- Caratteristiche e quantità degli inverter, dei cavi e di tutti quegli elementi essenziali per il funzionamento del sistema impianto (Balance of System);
- apporti aggiuntivi dati dalle operazioni di manutenzione (generalmente considerata nulla perché di piccola entità) e dismissione (riciclaggio, smaltimento, rinaturalizzazione dell'area d'impianto, ecc). Per il progetto in esame non sono stati considerati apporti aggiuntivi in quanto considerati non significativi o in seguito alla consultazione dei vari database scientifici riconosciuti a livello internazionale, non sono stati ritrovati valori utili alla definizione esatta della loro entità.

Altri risultati legati al bilancio sulle emissioni di Carbonio dell'impianto sono consultabili nei documenti in allegato.



STIMA DI PRODUCIBILITA'

CODICE	FV.ALC01.PD.A.13
REVISIONE n.	00
DATA REVISIONE	11/2023
PAGINA	13 di 13

6 ALLEGATI

PVsyst - Simulation report

Grid-Connected System

Project: Alcamo_Monteleone_Project

Variant: 08_Alcamo_Monteleone_CTR_VIG_7.5m_SottocampoA

Tracking system with backtracking

System power: 1392 kWp

Casa Valdibella - Italy

Author

E-Way Finance S.p.A. (Italy)



Project: Alcamo_Monte Leone_Project

Variant: 08_Alcamo_Monte Leone_CTR_VIG_7.5m_SottocampoA

PVsyst V7.4.2

VC2, Simulation date:
17/10/23 17:48
with v7.4.2

E-Way Finance S.p.A. (Italy)

Project summary

Geographical Site Casa Valdibella Italy	Situation Latitude 37.93 °N Longitude 13.00 °E Altitude 250 m Time zone UTC+1	Project settings Albedo 0.20
Meteo data Casa Valdibella PVGIS api TMY		

System summary

Grid-Connected System	Tracking system with backtracking	
PV Field Orientation	Tracking algorithm	Near Shadings
Orientation Tracking plane, tilted axis Avg axis tilt 5.1 ° Avg axis azim. 0 °	Irradiance optimization Backtracking activated Wind stow Wind Speed threshold 12 m/s Wind stow position 0 °	According to strings : Fast (table) Electrical effect 80 % Diffuse shading Automatic
System information	PV Array	Inverters
PV Array Nb. of modules 1960 units Pnom total 1392 kWp	Inverters Nb. of units 1 unit Pnom total 1169 kWac Pnom ratio 1.190	
User's needs Unlimited load (grid)		

Results summary

Produced Energy 2888.20 MWh/year	Specific production 2075 kWh/kWp/year	Perf. Ratio PR 84.86 %
----------------------------------	---------------------------------------	------------------------

Table of contents

Project and results summary	2
General parameters, PV Array Characteristics, System losses	3
Horizon definition	6
Near shading definition - Iso-shadings diagram	7
Main results	8
Loss diagram	9
P50 - P90 evaluation	10
CO ₂ Emission Balance	11



PVsyst V7.4.2

VC2, Simulation date:
17/10/23 17:48
with v7.4.2

E-Way Finance S.p.A. (Italy)

General parameters

Grid-Connected System

PV Field Orientation

Orientation

Tracking plane, tilted axis
Avg axis tilt 5.1 °
Avg axis azim. 0 °

Models used

Transposition Perez
Diffuse Imported
Circumsolar separate

Horizon

Average Height 4.1 °

Bifacial system

Model 2D Calculation
unlimited trackers

Bifacial model geometry

Tracker Spacing 7.50 m
Tracker width 2.38 m
GCR 31.8 %
Axis height above ground 3.05 m

Tracking system with backtracking

Tracking algorithm

Irradiance optimization
Backtracking activated
Wind stow
Wind Speed threshold 12 m/s
Wind stow position 0 °

Near Shadings

According to strings : Fast (table)
Electrical effect 80 %
Diffuse shading Automatic

Backtracking array

Nb. of trackers 79 units

Sizes

Tracker Spacing 7.50 m
Collector width 2.38 m
Ground Cov. Ratio (GCR) 31.8 %
Phi min / max. -/+ 45.0 °

Backtracking strategy

Phi limits for BT -/+ 79.9 °
Backtracking pitch 7.50 m
Backtracking width 2.38 m

User's needs

Unlimited load (grid)

Bifacial model definitions

Ground albedo 0.20
Bifaciality factor 80 %
Rear shading factor 5.0 %
Rear mismatch loss 10.0 %
Shed transparent fraction 0.0 %

PV Array Characteristics

PV module

Manufacturer Mysolar
Model Mysolar GOLD N-Type HJT BIFACIAL MS710N-HJTGB
(Custom parameters definition)

Unit Nom. Power 710 Wp
Number of PV modules 1960 units
Nominal (STC) 1392 kWp
Modules 70 Strings x 28 In series

At operating cond. (50°C)

Pmpp 1301 kWp
U mpp 1104 V
I mpp 1179 A

Total PV power

Nominal (STC) 1392 kWp
Total 1960 modules
Module area 6088 m²

Inverter

Manufacturer Ingeteam
Model INGECON SUN 1170TL B450 IP54 H1000
(Custom parameters definition)

Unit Nom. Power 1169 kWac
Number of inverters 1 unit
Total power 1169 kWac
Operating voltage 645-1300 V
Pnom ratio (DC:AC) 1.19

Total inverter power

Total power 1169 kWac
Number of inverters 1 unit
Pnom ratio 1.19



PVsyst V7.4.2

VC2, Simulation date:
17/10/23 17:48
with v7.4.2

E-Way Finance S.p.A. (Italy)

Array losses

Array Soiling Losses

Loss Fraction 1.0 %

Thermal Loss factor

Module temperature according to irradiance

Uc (const) 29.0 W/m²K

Uv (wind) 0.0 W/m²K/m/s

DC wiring losses

Global array res. 0.69 mΩ

Loss Fraction 0.1 % at STC

LID - Light Induced Degradation

Loss Fraction 1.0 %

Module Quality Loss

Loss Fraction -0.2 %

Module mismatch losses

Loss Fraction 1.0 % at MPP

Strings Mismatch loss

Loss Fraction 0.2 %

IAM loss factor

Incidence effect (IAM): Fresnel smooth glass, n = 1.526

0°	30°	50°	60°	70°	75°	80°	85°	90°
1.000	0.998	0.981	0.948	0.862	0.776	0.636	0.403	0.000

Spectral correction

FirstSolar model

Precipitable water estimated from relative humidity

Coefficient Set	C0	C1	C2	C3	C4	C5
Monocrystalline Si	0,85914	-0,02088	-0,0058853	0,12029	0,026814	-0,001781

System losses

Unavailability of the system

Time fraction 1.5 %
5.5 days,
3 periods

Auxiliaries loss

constant (fans) 2.00 kW
292.0 kW from Power thresh.

AC wiring losses

Inv. output line up to MV transfo

Inverter voltage 450 Vac tri
Loss Fraction 0.02 % at STC

Inverter: INGECON SUN 1170TL B450 IP54 H1000

Wire section (1 Inv.) Copper 1 x 3 x 1200 mm²
Wires length 2 m

MV line up to Injection

MV Voltage 36 kV
Wires Copper 3 x 6 mm²
Length 1700 m
Loss Fraction 0.56 % at STC

AC losses in transformers



PVsyst V7.4.2

VC2, Simulation date:
17/10/23 17:48
with v7.4.2

E-Way Finance S.p.A. (Italy)

AC losses in transformers

MV transfo

Medium voltage 36 kV

Transformer parameters

Nominal power at STC 1.36 MVA

Iron Loss (24/24 Connexion) 1.36 kVA

Iron loss fraction 0.10 % at STC

Copper loss 13.59 kVA

Copper loss fraction 1.00 % at STC

Coils equivalent resistance 3 x 1.49 mΩ



Horizon definition


Horizon from PVGIS website API, Lat=37°55'53", Long=13°0'14", Alt=221m

Average Height	4.1 °	Albedo Factor	0.77
Diffuse Factor	0.96	Albedo Fraction	100 %

Horizon profile

Azimuth [°]	-180	-173	-165	-158	-150	-143	-135	-128	-120	-113	-105	-90	-83
Height [°]	8.0	6.1	5.3	5.3	5.7	5.7	3.4	3.8	3.8	3.1	2.7	2.7	1.9
Azimuth [°]	-75	-68	-60	-53	-45	-38	-15	-8	15	23	38	45	68
Height [°]	1.5	2.7	2.7	2.3	1.9	1.5	1.5	1.1	1.1	2.3	2.3	3.8	3.8
Azimuth [°]	75	105	113	120	128	135	143	150	158	165	173	180	
Height [°]	4.2	4.2	5.7	6.5	7.6	8.4	8.8	8.8	7.6	8.4	8.8	8.0	


Sun Paths (Height / Azimuth diagram)






Near shadings parameter

Perspective of the PV-field and surrounding shading scene



Iso-shadings diagram

Orientation #1






Main results


System Production

Produced Energy (P50) 2888.20 MWh/year Specific production (P50) 2075 kWh/kWp/year Perf. Ratio PR 84.86 %
 Produced Energy (P90) 2774.05 MWh/year Specific production (P90) 1993 kWh/kWp/year
 Produced Energy (P95) 2741.93 MWh/year Specific production (P95) 1970 kWh/kWp/year

Normalized productions (per installed kWp)



Performance Ratio PR



Balances and main results


	GlobHor kWh/m ²	DiffHor kWh/m ²	T_Amb °C	GlobInc kWh/m ²	GlobEff kWh/m ²	EArray MWh	E_Grid MWh	PR ratio
January	71.0	34.55	11.08	102.2	95.1	133.0	127.6	0.897
February	79.6	40.26	9.10	110.2	103.7	145.8	139.9	0.912
March	145.0	53.88	11.04	201.8	192.3	262.1	238.9	0.851
April	180.1	63.93	14.77	243.3	234.0	304.9	292.6	0.864
May	224.5	68.21	18.60	296.2	285.3	359.8	345.4	0.838
June	223.1	69.71	23.77	289.5	278.9	351.2	315.7	0.784
July	246.3	62.50	28.25	329.4	318.2	392.2	376.6	0.822
August	204.4	63.43	26.93	276.0	265.6	339.9	326.4	0.850
September	150.2	56.50	22.33	207.0	198.3	266.0	255.4	0.887
October	114.7	45.40	17.11	163.3	155.1	212.8	189.2	0.832
November	79.3	33.14	14.90	116.8	109.0	150.5	144.5	0.889
December	72.4	31.63	11.01	110.0	101.4	141.7	136.1	0.889
Year	1790.7	623.17	17.46	2445.6	2336.9	3060.1	2888.2	0.849

Legends

GlobHor	Global horizontal irradiation	EArray	Effective energy at the output of the array
DiffHor	Horizontal diffuse irradiation	E_Grid	Energy injected into grid
T_Amb	Ambient Temperature	PR	Performance Ratio
GlobInc	Global incident in coll. plane		
GlobEff	Effective Global, corr. for IAM and shadings		



Loss diagram





P50 - P90 evaluation

Meteo data

Source	PVGIS api TMY
Kind	TMY, multi-year
Year-to-year variability(Variance)	2.5 %

Specified Deviation

Climate change	0.0 %
----------------	-------

Global variability (meteo + system)

Variability (Quadratic sum)	3.1 %
-----------------------------	-------


Simulation and parameters uncertainties

PV module modelling/parameters	1.0 %
Inverter efficiency uncertainty	0.5 %
Soiling and mismatch uncertainties	1.0 %
Degradation uncertainty	1.0 %

Annual production probability

Variability	89 MWh
P50	2888 MWh
P90	2774 MWh
P95	2742 MWh

Probability distribution





CO₂ Emission Balance

Total: 29221.9 tCO₂

Generated emissions

Total: 2579.13 tCO₂

Source: Detailed calculation from table below

Replaced Emissions

Total: 36651.2 tCO₂

System production: 2888.20 MWh/yr

Grid Lifecycle Emissions: 423 gCO₂/kWh


Source: IEA List

Country: Italy

Lifetime: 30 years

Annual degradation: 1.0 %

Saved CO₂ Emission vs. Time



System Lifecycle Emissions Details

Item	LCE	Quantity	Subtotal
			[kgCO ₂]
Modules	1713 kgCO ₂ /kWp	1392 kWp	2383421
Transport1	35.0 gCO ₂ /km	15100 km	40191
Transport2	59.7 gCO ₂ /km	1350 km	6129
Supports	2.82 kgCO ₂ /kg	40600 kg	114549
Concrete	177 kgCO ₂ /m ³	45.0 m ³	7965
Inverters	280 kgCO ₂ /units	1.00 units	280
Wiring	14.8 kgCO ₂ /m	1800 m	26591

PVsyst - Simulation report

Grid-Connected System

Project: Alcamo_Monteleone_Project

Variant: 08_Alcamo_Monteleone_CTR_VIG_7.5m_SottocampoB-J

Tracking system with backtracking

System power: 21.89 MWp

Casa Valdibella - Italy

Author

E-Way Finance S.p.A. (Italy)



Project: Alcamo_Monte Leone_Project

Variant: 08_Alcamo_Monte Leone_CTR_VIG_7.5m_SottocampoB-J

PVsyst V7.4.2

VC7, Simulation date:
18/10/23 12:47
with v7.4.2

E-Way Finance S.p.A. (Italy)

Project summary

Geographical Site Casa Valdibella Italy	Situation Latitude 37.92 °N Longitude 12.99 °E Altitude 196 m Time zone UTC+1	Project settings Albedo 0.20
Meteo data Casa Valdibella PVGIS api TMY		

System summary

Grid-Connected System	Tracking system with backtracking	
PV Field Orientation Orientation Tracking plane, horizontal N-S axis Avg axis azim. 0 °	Tracking algorithm Irradiance optimization Backtracking activated Wind stow Wind Speed threshold 12 m/s Wind stow position 0 °	Near Shadings According to strings : Fast (table) Electrical effect 80 % Diffuse shading Automatic
System information PV Array Nb. of modules 30828 units Pnom total 21.89 MWp	Inverters Nb. of units 13 units Pnom total 19.64 MWac Pnom ratio 1.114	
User's needs Unlimited load (grid)		

Results summary

Produced Energy 46027.86 MWh/year	Specific production 2103 kWh/kWp/year	Perf. Ratio PR 87.10 %
-----------------------------------	---------------------------------------	------------------------

Table of contents

Project and results summary	2
General parameters, PV Array Characteristics, System losses	3
Horizon definition	8
Near shading definition - Iso-shadings diagram	9
Main results	10
Loss diagram	11
P50 - P90 evaluation	12
CO ₂ Emission Balance	13

**PVsyst V7.4.2**

VC7, Simulation date:
18/10/23 12:47
with v7.4.2

E-Way Finance S.p.A. (Italy)

General parameters**Grid-Connected System****PV Field Orientation****Orientation**

Tracking plane, horizontal N-S axis
Avg axis azim. 0 °

Models used

Transposition Perez
Diffuse Imported
Circumsolar separate

Horizon

Average Height 4.1 °

Bifacial system

Model 2D Calculation
unlimited trackers

Bifacial model geometry

Tracker Spacing 7.50 m
Tracker width 2.38 m
GCR 31.8 %
Axis height above ground 3.05 m

Tracking system with backtracking**Tracking algorithm**

Irradiance optimization
Backtracking activated
Wind stow
Wind Speed threshold 12 m/s
Wind stow position 0 °

Near Shadings

According to strings : Fast (table)
Electrical effect 80 %
Diffuse shading Automatic

Backtracking array

Nb. of trackers 1212 units

Sizes

Tracker Spacing 7.50 m
Collector width 2.38 m
Ground Cov. Ratio (GCR) 31.8 %
Phi min / max. -/+ 45.0 °

Backtracking strategy

Phi limits for BT -/+ 79.9 °
Backtracking pitch 7.50 m
Backtracking width 2.38 m

User's needs

Unlimited load (grid)

Bifacial model definitions

Ground albedo 0.20
Bifaciality factor 80 %
Rear shading factor 5.0 %
Rear mismatch loss 10.0 %
Shed transparent fraction 0.0 %

PV Array Characteristics**PV module**

Manufacturer Mysolar
Model Mysolar GOLD N-Type HJT BIFACIAL MS710N-HJTGB
(Custom parameters definition)
Unit Nom. Power 710 Wp
Number of PV modules 11928 units
Nominal (STC) 8469 kWp

Array #1 - sottocampo B

Number of PV modules 2464 units
Nominal (STC) 1749 kWp
Modules 88 Strings x 28 In series

At operating cond. (50°C)

Pmpp 1636 kWp
U mpp 1104 V
I mpp 1482 A

Inverter

Manufacturer Ingeteam
Model INGECON SUN 1560TL B600 IP54 H1000
(Custom parameters definition)
Unit Nom. Power 1559 kWac
Number of inverters 5 units
Total power 7795 kWac

Number of inverters 1 unit
Total power 1559 kWac

Operating voltage 853-1300 V
Pnom ratio (DC:AC) 1.12



PVsyst V7.4.2

VC7, Simulation date:
18/10/23 12:47
with v7.4.2

E-Way Finance S.p.A. (Italy)

PV Array Characteristics

Array #8 - sottocampo I

Number of PV modules 7140 units
Nominal (STC) 5069 kWp
Modules 255 Strings x 28 In series

At operating cond. (50°C)

Pmpp 4740 kWp
U mpp 1104 V
I mpp 4293 A

Number of inverters 3 units
Total power 4677 kWac

Operating voltage 853-1300 V
Pnom ratio (DC:AC) 1.08

Array #9 - sottocampo J

Number of PV modules 2324 units
Nominal (STC) 1650 kWp
Modules 83 Strings x 28 In series

At operating cond. (50°C)

Pmpp 1543 kWp
U mpp 1104 V
I mpp 1397 A

Number of inverters 1 unit
Total power 1559 kWac

Operating voltage 853-1300 V
Pnom ratio (DC:AC) 1.06

PV module

Manufacturer Mysolar
Model Mysolar GOLD N-Type HJT BIFACIAL MS710N-HJTGB
(Custom parameters definition)
Unit Nom. Power 710 Wp
Number of PV modules 7840 units
Nominal (STC) 5566 kWp

Inverter

Manufacturer Ingeteam
Model INGECON SUN 1170TL B450 IP54 H1000
(Custom parameters definition)
Unit Nom. Power 1169 kWac
Number of inverters 4 units
Total power 4676 kWac

Array #2 - sottocampo C

Number of PV modules 2044 units
Nominal (STC) 1451 kWp
Modules 73 Strings x 28 In series

At operating cond. (50°C)

Pmpp 1357 kWp
U mpp 1104 V
I mpp 1229 A

Number of inverters 1 unit
Total power 1169 kWac

Operating voltage 645-1300 V
Pnom ratio (DC:AC) 1.24

Array #4 - sottocampo E

Number of PV modules 3836 units
Nominal (STC) 2724 kWp
Modules 137 Strings x 28 In series

At operating cond. (50°C)

Pmpp 2547 kWp
U mpp 1104 V
I mpp 2307 A

Number of inverters 2 units
Total power 2338 kWac

Operating voltage 645-1300 V
Pnom ratio (DC:AC) 1.16

Array #6 - sottocampo G

Number of PV modules 1960 units
Nominal (STC) 1392 kWp
Modules 70 Strings x 28 In series

At operating cond. (50°C)

Pmpp 1301 kWp
U mpp 1104 V
I mpp 1179 A

Number of inverters 1 unit
Total power 1169 kWac

Operating voltage 645-1300 V
Pnom ratio (DC:AC) 1.19



PVsyst V7.4.2

VC7, Simulation date:
18/10/23 12:47
with v7.4.2

E-Way Finance S.p.A. (Italy)

PV Array Characteristics

PV module		Inverter	
Manufacturer	Mysolar	Manufacturer	Ingeteam
Model	Mysolar GOLD N-Type HJT BIFACIAL MS710N-HJTGB (Custom parameters definition)	Model	INGECON SUN 1800TL B690 IP54 H1000 (Custom parameters definition)
Unit Nom. Power	710 Wp	Unit Nom. Power	1793 kWac
Number of PV modules	11060 units	Number of inverters	4 units
Nominal (STC)	7853 kWp	Total power	7172 kWac
Array #3 - sottocampo D			
Number of PV modules	2912 units	Number of inverters	1 unit
Nominal (STC)	2068 kWp	Total power	1793 kWac
Modules	104 Strings x 28 In series		
At operating cond. (50°C)		Operating voltage	978-1300 V
Pmpp	1933 kWp	Pnom ratio (DC:AC)	1.15
U mpp	1104 V		
I mpp	1751 A		
Array #5 - sottocampo F			
Number of PV modules	3052 units	Number of inverters	1 unit
Nominal (STC)	2167 kWp	Total power	1793 kWac
Modules	109 Strings x 28 In series		
At operating cond. (50°C)		Operating voltage	978-1300 V
Pmpp	2026 kWp	Pnom ratio (DC:AC)	1.21
U mpp	1104 V		
I mpp	1835 A		
Array #7 - sottocampo H			
Number of PV modules	5096 units	Number of inverters	2 units
Nominal (STC)	3618 kWp	Total power	3586 kWac
Modules	182 Strings x 28 In series		
At operating cond. (50°C)		Operating voltage	978-1300 V
Pmpp	3383 kWp	Pnom ratio (DC:AC)	1.01
U mpp	1104 V		
I mpp	3064 A		
Total PV power		Total inverter power	
Nominal (STC)	21888 kWp	Total power	19643 kWac
Total	30828 modules	Number of inverters	13 units
Module area	95763 m ²	Pnom ratio	1.11

Array losses

Array Soiling Losses		Thermal Loss factor		LID - Light Induced Degradation				
Loss Fraction	1.0 %	Module temperature according to irradiance		Loss Fraction	1.0 %			
		Uc (const)	29.0 W/m ² K					
		Uv (wind)	0.0 W/m ² K/m/s					
Module Quality Loss		Module mismatch losses		Strings Mismatch loss				
Loss Fraction	-0.2 %	Loss Fraction	1.0 % at MPP	Loss Fraction	0.2 %			
IAM loss factor								
Incidence effect (IAM): Fresnel smooth glass, n = 1.526								
0°	30°	50°	60°	70°	75°	80°	85°	90°
1.000	0.998	0.981	0.948	0.862	0.776	0.636	0.403	0.000

**PVsyst V7.4.2**

VC7, Simulation date:
18/10/23 12:47
with v7.4.2

E-Way Finance S.p.A. (Italy)

Array losses**Spectral correction**

FirstSolar model

Precipitable water estimated from relative humidity

Coefficient Set	C0	C1	C2	C3	C4	C5
Monocrystalline Si	0,85914	-0,02088	-0,0058853	0,12029	0,026814	-0,001781

DC wiring losses

Global wiring resistance 0.065 mΩ
Loss Fraction 0.1 % at STC

Array #1 - sottocampo B

Global array res. 0.58 mΩ
Loss Fraction 0.1 % at STC

Array #3 - sottocampo D

Global array res. 0.50 mΩ
Loss Fraction 0.1 % at STC

Array #5 - sottocampo F

Global array res. 0.50 mΩ
Loss Fraction 0.1 % at STC

Array #7 - sottocampo H

Global array res. 0.64 mΩ
Loss Fraction 0.2 % at STC

Array #9 - sottocampo J

Global array res. 0.68 mΩ
Loss Fraction 0.1 % at STC

Array #2 - sottocampo C

Global array res. 0.69 mΩ
Loss Fraction 0.1 % at STC

Array #4 - sottocampo E

Global array res. 0.49 mΩ
Loss Fraction 0.1 % at STC

Array #6 - sottocampo G

Global array res. 0.69 mΩ
Loss Fraction 0.1 % at STC

Array #8 - sottocampo I

Global array res. 0.63 mΩ
Loss Fraction 0.2 % at STC

System losses**Unavailability of the system**

Time fraction 1.5 %
5.5 days,
3 periods

Auxiliaries loss

constant (fans) 24.0 kW
4774.0 kW from Power thresh.

AC wiring losses**Inv. output line up to MV transfo**

Inverter voltage 600 Vac tri
Loss Fraction 0.35 % at STC

Inverters: INGECON SUN 1560TL B600 IP54 H1000, INGECON SUN 1170TL B450 IP54 H1000, INGECON SUN 1800TL B690 IP54 H1000

Wire section (13 Inv.) Copper 13 x 3 x 1200 mm²
Average wires length 40 m

MV line up to Injection

MV Voltage 36 kV
Wires Copper 3 x 185 mm²
Length 840 m
Loss Fraction 0.14 % at STC



PVsyst V7.4.2

VC7, Simulation date:
18/10/23 12:47
with v7.4.2

E-Way Finance S.p.A. (Italy)

AC losses in transformers

MV transfo

Medium voltage 36 kV

Transformer parameters

Nominal power at STC 21.47 MVA

Iron Loss (24/24 Connexion) 22.75 kVA

Iron loss fraction 0.11 % at STC

Copper loss 214.88 kVA

Copper loss fraction 1.00 % at STC

Coils equivalent resistance 3 x 0.17 mΩ



Horizon definition


Horizon from PVGIS website API, Lat=37°55'53", Long=13°0'14", Alt=221m

Average Height	4.1 °	Albedo Factor	0.77
Diffuse Factor	0.96	Albedo Fraction	100 %

Horizon profile

Azimuth [°]	-180	-173	-165	-158	-150	-143	-135	-128	-120	-113	-105	-90	-83
Height [°]	8.0	6.1	5.3	5.3	5.7	5.7	3.4	3.8	3.8	3.1	2.7	2.7	1.9
Azimuth [°]	-75	-68	-60	-53	-45	-38	-15	-8	15	23	38	45	68
Height [°]	1.5	2.7	2.7	2.3	1.9	1.5	1.5	1.1	1.1	2.3	2.3	3.8	3.8
Azimuth [°]	75	105	113	120	128	135	143	150	158	165	173	180	
Height [°]	4.2	4.2	5.7	6.5	7.6	8.4	8.8	8.8	7.6	8.4	8.8	8.0	


Sun Paths (Height / Azimuth diagram)






Near shadings parameter

Perspective of the PV-field and surrounding shading scene



Iso-shadings diagram

Orientation #1






Main results


System Production

Produced Energy (P50) 46027.86 MWh/year Specific production (P50) 2103 kWh/kWp/year Perf. Ratio PR 87.10 %
 Produced Energy (P90) 44208.71 MWh/year Specific production (P90) 2020 kWh/kWp/year
 Produced Energy (P95) 43696.87 MWh/year Specific production (P95) 1996 kWh/kWp/year

Normalized productions (per installed kWp)



Performance Ratio PR



Balances and main results


	GlobHor kWh/m ²	DiffHor kWh/m ²	T_Amb °C	GlobInc kWh/m ²	GlobEff kWh/m ²	EArray MWh	E_Grid MWh	PR ratio
January	71.0	34.55	11.08	98.0	90.7	2014	1940	0.905
February	79.6	40.26	9.10	107.0	100.6	2247	2167	0.925
March	145.0	53.88	11.04	198.0	188.4	4090	3750	0.865
April	180.1	63.93	14.77	241.3	232.0	4898	4728	0.895
May	224.5	68.21	18.60	295.7	284.8	5864	5661	0.875
June	223.1	69.71	23.77	290.4	279.3	5701	5157	0.811
July	246.3	62.50	28.25	329.7	318.4	6398	6178	0.856
August	204.4	63.43	26.93	274.5	264.1	5441	5255	0.875
September	150.2	56.50	22.33	203.8	195.1	4150	4007	0.898
October	114.7	45.40	17.11	159.1	150.9	3284	2937	0.843
November	79.3	33.14	14.90	112.2	104.5	2292	2210	0.900
December	72.4	31.63	11.01	104.5	95.7	2113	2038	0.891
Year	1790.7	623.17	17.46	2414.2	2304.5	48492	46028	0.871

Legends

GlobHor	Global horizontal irradiation	EArray	Effective energy at the output of the array
DiffHor	Horizontal diffuse irradiation	E_Grid	Energy injected into grid
T_Amb	Ambient Temperature	PR	Performance Ratio
GlobInc	Global incident in coll. plane		
GlobEff	Effective Global, corr. for IAM and shadings		



Loss diagram





PVsyst V7.4.2

VC7, Simulation date:
18/10/23 12:47
with v7.4.2

E-Way Finance S.p.A. (Italy)

P50 - P90 evaluation

Meteo data

Source	PVGIS api TMY
Kind	TMY, multi-year
Year-to-year variability(Variance)	2.5 %

Specified Deviation

Climate change	0.0 %
----------------	-------

Global variability (meteo + system)

Variability (Quadratic sum)	3.1 %
-----------------------------	-------


Simulation and parameters uncertainties

PV module modelling/parameters	1.0 %
Inverter efficiency uncertainty	0.5 %
Soiling and mismatch uncertainties	1.0 %
Degradation uncertainty	1.0 %

Annual production probability

Variability	1.42 GWh
P50	46.03 GWh
P90	44.21 GWh
P95	43.70 GWh

Probability distribution





CO₂ Emission Balance

Total: 467809.9 tCO₂

Generated emissions

Total: 38987.85 tCO₂

Source: Detailed calculation from table below

Replaced Emissions

Total: 584093.5 tCO₂

System production: 46027.86 MWh/yr

Grid Lifecycle Emissions: 423 gCO₂/kWh


Source: IEA List

Country: Italy

Lifetime: 30 years

Annual degradation: 1.0 %

Saved CO₂ Emission vs. Time



System Lifecycle Emissions Details

Item	LCE	Quantity	Subtotal [kgCO ₂]
Modules	1713 kgCO ₂ /kWp	21252 kWp	36398246
Transport1	35.0 gCO ₂ /km	15100 km	613780
Transport2	59.7 gCO ₂ /km	1350 km	93600
Supports	2.82 kgCO ₂ /kg	565440 kg	1595338
Concrete	177 kgCO ₂ /m ³	400 m ³	70800
Inverters	280 kgCO ₂ /units	12.0 units	3354
Wiring	14.8 kgCO ₂ /m	14400 m	212731

PVsyst - Simulation report

Grid-Connected System

Project: Alcamo_Monteleone_Project

Variant: 08_Alcamo_Monteleone_CTR_VIG_7.5m_Sottocampo K

Tracking system with backtracking

System power: 1730 kWp

Casa Valdibella - Italy

Author

E-Way Finance S.p.A. (Italy)



Project: Alcamo_Monte Leone_Project

Variant: 08_Alcamo_Monte Leone_CTR_VIG_7.5m_Sottocampo K

PVsyst V7.4.2

VC8, Simulation date:
18/10/23 09:13
with v7.4.2

E-Way Finance S.p.A. (Italy)

Project summary

Geographical Site Casa Valdibella Italy	Situation Latitude 37.91 °N Longitude 13.00 °E Altitude 180 m Time zone UTC+1	Project settings Albedo 0.20
Meteo data Casa Valdibella PVGIS api TMY		

System summary

Grid-Connected System	Tracking system with backtracking	
PV Field Orientation	Tracking algorithm	Near Shadings
Orientation Tracking plane, tilted axis Avg axis tilt 1.1 ° Avg axis azim. 0 °	Irradiance optimization Backtracking activated Wind stow Wind Speed threshold 12 m/s Wind stow position 0 °	According to strings : Fast (table) Electrical effect 80 % Diffuse shading Automatic
System information	PV Array	Inverters
	Nb. of modules 2436 units Pnom total 1730 kWp	Nb. of units 1 unit Pnom total 1559 kWac Pnom ratio 1.109
User's needs Unlimited load (grid)		

Results summary

Produced Energy 3662.57 MWh/year	Specific production 2118 kWh/kWp/year	Perf. Ratio PR 88.32 %
----------------------------------	---------------------------------------	------------------------

Table of contents

Project and results summary	2
General parameters, PV Array Characteristics, System losses	3
Horizon definition	6
Near shading definition - Iso-shadings diagram	7
Main results	8
Loss diagram	9
P50 - P90 evaluation	10
CO ₂ Emission Balance	11



PVsyst V7.4.2

VC8, Simulation date:
18/10/23 09:13
with v7.4.2

E-Way Finance S.p.A. (Italy)

General parameters

Grid-Connected System

PV Field Orientation

Orientation

Tracking plane, tilted axis
Avg axis tilt 1.1 °
Avg axis azim. 0 °

Models used

Transposition Perez
Diffuse Imported
Circumsolar separate

Horizon

Average Height 4.1 °

Bifacial system

Model 2D Calculation
unlimited trackers

Bifacial model geometry

Tracker Spacing 7.50 m
Tracker width 2.38 m
GCR 31.8 %
Axis height above ground 3.05 m

Tracking system with backtracking

Tracking algorithm

Irradiance optimization
Backtracking activated
Wind stow
Wind Speed threshold 12 m/s
Wind stow position 0 °

Near Shadings

According to strings : Fast (table)
Electrical effect 80 %
Diffuse shading Automatic

Backtracking array

Nb. of trackers 92 units

Sizes

Tracker Spacing 7.50 m
Collector width 2.38 m
Ground Cov. Ratio (GCR) 31.8 %
Phi min / max. -/+ 45.0 °

Backtracking strategy

Phi limits for BT -/+ 79.9 °
Backtracking pitch 7.50 m
Backtracking width 2.38 m

User's needs

Unlimited load (grid)

Bifacial model definitions

Ground albedo 0.20
Bifaciality factor 80 %
Rear shading factor 5.0 %
Rear mismatch loss 10.0 %
Shed transparent fraction 0.0 %

PV Array Characteristics

PV module

Manufacturer Mysolar
Model Mysolar GOLD N-Type HJT BIFACIAL MS710N-HJTGB
(Custom parameters definition)

Unit Nom. Power 710 Wp
Number of PV modules 2436 units
Nominal (STC) 1730 kWp
Modules 87 Strings x 28 In series

At operating cond. (50°C)

Pmpp 1617 kWp
U mpp 1104 V
I mpp 1465 A

Total PV power

Nominal (STC) 1730 kWp
Total 2436 modules
Module area 7567 m²

Inverter

Manufacturer Ingeteam
Model INGECON SUN 1560TL B600 IP54 H1000
(Custom parameters definition)

Unit Nom. Power 1559 kWac
Number of inverters 1 unit
Total power 1559 kWac
Operating voltage 853-1300 V
Pnom ratio (DC:AC) 1.11

Total inverter power

Total power 1559 kWac
Number of inverters 1 unit
Pnom ratio 1.11



PVsyst V7.4.2

VC8, Simulation date:
18/10/23 09:13
with v7.4.2

E-Way Finance S.p.A. (Italy)

Array losses

Array Soiling Losses

Loss Fraction 1.0 %

Thermal Loss factor

Module temperature according to irradiance

Uc (const) 29.0 W/m²K

Uv (wind) 0.0 W/m²K/m/s

DC wiring losses

Global array res. 0.67 mΩ

Loss Fraction 0.1 % at STC

LID - Light Induced Degradation

Loss Fraction 1.0 %

Module Quality Loss

Loss Fraction -0.2 %

Module mismatch losses

Loss Fraction 1.0 % at MPP

Strings Mismatch loss

Loss Fraction 0.2 %

IAM loss factor

Incidence effect (IAM): Fresnel smooth glass, n = 1.526

0°	30°	50°	60°	70°	75°	80°	85°	90°
1.000	0.998	0.981	0.948	0.862	0.776	0.636	0.403	0.000

Spectral correction

FirstSolar model

Precipitable water estimated from relative humidity

Coefficient Set	C0	C1	C2	C3	C4	C5
Monocrystalline Si	0,85914	-0,02088	-0,0058853	0,12029	0,026814	-0,001781

System losses

Unavailability of the system

Time fraction 1.5 %
5.5 days,
3 periods

Auxiliaries loss

constant (fans) 2.00 kW
390.0 kW from Power thresh.

AC wiring losses

Inv. output line up to MV transfo

Inverter voltage 600 Vac tri
Loss Fraction 0.01 % at STC

Inverter: INGECON SUN 1560TL B600 IP54 H1000

Wire section (1 Inv.) Copper 1 x 3 x 1200 mm²
Wires length 2 m

MV line up to Injection

MV Voltage 36 kV
Wires Copper 3 x 185 mm²
Length 900 m
Loss Fraction 0.01 % at STC

AC losses in transformers



PVsyst V7.4.2

VC8, Simulation date:
18/10/23 09:13
with v7.4.2

E-Way Finance S.p.A. (Italy)

AC losses in transformers

MV transfo

Medium voltage 36 kV

Transformer parameters

Nominal power at STC 1.70 MVA

Iron Loss (24/24 Connexion) 1.80 kVA

Iron loss fraction 0.11 % at STC

Copper loss 16.93 kVA

Copper loss fraction 1.00 % at STC

Coils equivalent resistance 3 x 2.11 mΩ



Horizon definition


Horizon from PVGIS website API, Lat=37°55'53", Long=13°0'14", Alt=221m

Average Height	4.1 °	Albedo Factor	0.76
Diffuse Factor	0.95	Albedo Fraction	100 %

Horizon profile

Azimuth [°]	-180	-173	-165	-158	-150	-143	-135	-128	-120	-113	-105	-90	-83
Height [°]	8.0	6.1	5.3	5.3	5.7	5.7	3.4	3.8	3.8	3.1	2.7	2.7	1.9
Azimuth [°]	-75	-68	-60	-53	-45	-38	-15	-8	15	23	38	45	68
Height [°]	1.5	2.7	2.7	2.3	1.9	1.5	1.5	1.1	1.1	2.3	2.3	3.8	3.8
Azimuth [°]	75	105	113	120	128	135	143	150	158	165	173	180	
Height [°]	4.2	4.2	5.7	6.5	7.6	8.4	8.8	8.8	7.6	8.4	8.8	8.0	


Sun Paths (Height / Azimuth diagram)






Near shadings parameter

Perspective of the PV-field and surrounding shading scene



Iso-shadings diagram

Orientation #1






Main results


System Production

Produced Energy (P50) 3662.57 MWh/year Specific production (P50) 2118 kWh/kWp/year Perf. Ratio PR 88.32 %
 Produced Energy (P90) 3517.82 MWh/year Specific production (P90) 2034 kWh/kWp/year
 Produced Energy (P95) 3477.09 MWh/year Specific production (P95) 2010 kWh/kWp/year

Normalized productions (per installed kWp)



Performance Ratio PR



Balances and main results


	GlobHor kWh/m ²	DiffHor kWh/m ²	T_Amb °C	GlobInc kWh/m ²	GlobEff kWh/m ²	EArray MWh	E_Grid MWh	PR ratio
January	71.0	34.55	11.08	95.8	88.5	156.8	151.5	0.914
February	79.6	40.26	9.10	105.4	98.9	176.4	170.6	0.936
March	145.0	53.88	11.04	196.0	185.3	317.8	292.4	0.862
April	180.1	63.93	14.77	240.3	230.6	390.7	378.7	0.911
May	224.5	68.21	18.60	295.3	284.1	469.9	455.6	0.892
June	223.1	69.71	23.77	290.7	278.1	452.6	411.2	0.818
July	246.3	62.50	28.25	329.6	317.9	514.4	499.0	0.875
August	204.4	63.43	26.93	273.6	263.2	434.9	421.8	0.891
September	150.2	56.50	22.33	202.2	193.4	327.6	317.6	0.908
October	114.7	45.40	17.11	157.0	148.6	257.6	231.1	0.851
November	79.3	33.14	14.90	110.0	102.3	180.1	174.3	0.916
December	72.4	31.63	11.01	101.8	93.0	164.2	158.8	0.902
Year	1790.7	623.17	17.46	2397.8	2283.8	3843.1	3662.6	0.883

Legends

GlobHor	Global horizontal irradiation	EArray	Effective energy at the output of the array
DiffHor	Horizontal diffuse irradiation	E_Grid	Energy injected into grid
T_Amb	Ambient Temperature	PR	Performance Ratio
GlobInc	Global incident in coll. plane		
GlobEff	Effective Global, corr. for IAM and shadings		



Loss diagram





PVsyst V7.4.2

VC8, Simulation date:
18/10/23 09:13
with v7.4.2

E-Way Finance S.p.A. (Italy)

P50 - P90 evaluation

Meteo data

Source	PVGIS api TMY
Kind	TMY, multi-year
Year-to-year variability(Variance)	2.5 %

Specified Deviation

Climate change	0.0 %
----------------	-------

Global variability (meteo + system)

Variability (Quadratic sum)	3.1 %
-----------------------------	-------


Simulation and parameters uncertainties

PV module modelling/parameters	1.0 %
Inverter efficiency uncertainty	0.5 %
Soiling and mismatch uncertainties	1.0 %
Degradation uncertainty	1.0 %

Annual production probability

Variability	113 MWh
P50	3663 MWh
P90	3518 MWh
P95	3477 MWh

Probability distribution





CO₂ Emission Balance

Total: 36940.6 tCO₂

Generated emissions

Total: 3386.77 tCO₂

Source: Detailed calculation from table below

Replaced Emissions

Total: 46478.1 tCO₂

System production: 3662.57 MWh/yr

Grid Lifecycle Emissions: 423 gCO₂/kWh


Source: IEA List

Country: Italy

Lifetime: 30 years

Annual degradation: 1.0 %

Saved CO₂ Emission vs. Time



System Lifecycle Emissions Details

Item	LCE	Quantity	Subtotal
			[kgCO ₂]
Modules	1713 kgCO ₂ /kWp	1730 kWp	2962252
Transport1	35.0 gCO ₂ /km	15100 km	49952
Transport2	59.7 gCO ₂ /km	1400 km	7900
Supports	2.82 kgCO ₂ /kg	121800 kg	343648
Concrete	177 kgCO ₂ /m ³	45.0 m ³	7965
Inverters	280 kgCO ₂ /units	1.00 units	280
Wiring	14.8 kgCO ₂ /m	1000 m	14773