



Notes:

- (1) The present drawing is supplied as a reference. It must be adapted to every real project according to the guidelines from the present document.
- (2) Pavement of graded aggregate:
 - Mandatory on cranes working area and nacelle storage area.
 - Necessary on tower sections and blades storage area, if slippery work conditions are expected.
- (3) All units are in meters.

Legend:

- Bearing capacity: Crane pressure + safety factor
- Bearing capacity: 2 Kg/cm²
- Area free of obstacles.



F4 INGEGNERIA
 Signed: ING. GIOVANNI DI SANTO
 Association Number No N° 1895

D				DATE	SCALE 1/500	 Parco Eolico "La Regina" A.16.d.3 - Planimetria di dettaglio piazzola di montaggio Banzi (Pz)	F4 Ingegneria srl	
C				MM/YY	DRAWN F4		CAD Vers.: tr	Page Vers.: X
B				MM/YY	CHECKED XXX		Name collection:	Page: 1
A	DD/MM/YY	INDICATE MODIFICATION	INDICATE PAGES MODIFIED	MM/YY	REVISED-EDPR XXX		Collection	Cont: 1
EDIC.	DATE	MODIFICATION	PAGES MODIFIED	Format A3		CAD N°: A.16.d.3 - Planimet		