

DISTINTA FERRI SPALLA A FONDAZIONE

Sagoma	Pos.	φ (mm)	nb	A (cm)	B (cm)	C (cm)	L (m)	Ltot (m)	Note
1	1	22	103	140	590		8.70	896.10	
	2	26	205	140	590		8.70	1783.50	
	16	26	62	130	140		4.00	248.00	
2	31	16	8	50	590		6.90	55.20	
	3	20	150	255	140		3.95	592.50	
	19	16	34	245	40		2.85	96.90	
3	21	16	34	40	245		2.85	96.90	
	4	20	90	255	140		3.95	350.50	
	29	16	8	1010	50		10.60	84.80	
4	30	16	8	50	1150		12.00	96.00	
	14	26	63	1000	26		12.00	744.00	
	15	26	62	960			9.60	595.20	
5	20	22	100	50	132	60	4.24	424.00	

Massa barre

φ	kg/m	Ltot	kg
16	1.578	23600	372.488
18	1.998	19380	387.127
20	2.466	94800	2337.910
22	2.984	132010	3839.233
26	4.168	337070	14048.383
Tot.			21085.141

Massa totale acciaio: 21085.141 kg

DISTINTA FERRI SPALLA A ELEVAZIONE

Sagoma	Pos.	φ (mm)	nb	A (cm)	B (cm)	C (cm)	D (cm)	E (cm)	F (cm)	L (m)	Ltot (m)	Note
1	5	20	150	140	245					3.85	578.09	
	27	14	20	394	16					4.10	81.99	
	28	14	20	16	1184					12.00	240.02	
2	38	16	13	590	140					12.00	120.00	
	37	16	13	140	590					7.30	94.90	
	46	18	17	40	445/449					4.85/4.89	82.79	
3	6	20	90	140	245					3.85	346.86	
	11	16	6	100	560					6.60	39.80	
	12	16	6	1000	100					12.00	72.00	
4	17	18	17	445/449	40					4.85/4.89	82.79	
	18	18	17	40	445/449					4.85/4.89	82.79	
	25	14	20	1184	16					12.00	239.94	
5	26	14	20	16	394					4.10	82.07	
	38	16	13	590	140					7.30	94.90	
	39	16	13	140	1060					12.00	156.00	
6	47	18	17	40	445/449					4.85/4.89	82.79	
	57	28	20	47	193					2.40	48.00	
	58	16	6	45	555					6.00	36.00	
7	7	16	80	135	30					3.00	240.00	
	32	18	26	40	440					5.20	135.20	
	34	18	26	40	440					5.20	135.20	
8	35	12	20	255	30					5.40	108.00	
	48	18	40	40	330					4.10	164.00	
	53	12	2	30	1042					11.02	22.03	
9	8	16	12	100	99	101				3.00	35.97	
	22	16	14	106	89	106				3.00	41.96	
	9	20	80	235	30					5.00	400.00	
10	82	16	53	52	21					1.25	66.25	
	41	16	75	16	365	23				4.04	302.98	
	10	10	2	600						12.00	24.00	
11	13	16	4	100	255					4.55	18.20	
	23	12	20	1200						12.00	240.00	
	59	16	3	620						6.20	18.60	
12	61	16	4	1000						10.00	40.00	
	33	8	352	10	140					1.60	563.20	
	42	8	280	10	40					0.80	168.00	
13	44	8	308	10	30					0.50	154.00	
	54	8	80	10	200					2.20	176.00	
	40	16	75	23	365	16				4.04	303.05	
14	43	12	6	21	10	87	102	92	98	4.40	26.40	
	52	12	53	23	10	21	46	25	42	2.00	106.00	
	55	16	70	32	198	61	129			4.20	294.00	
15	56	28	20	32	198	61	129			4.20	84.00	
	60	16	8	35	365					4.00	32.00	

Massa barre

φ (mm)	M/L (kg/m)	Ltot (m)	Mtot (kg)
8	0.395	1081.20	418.7
10	0.617	24.00	14.8
12	0.888	502.43	446.1
14	1.208	644.01	778.2
16	1.578	2042.41	3223.6
18	1.998	765.56	1529.3
20	2.466	1324.95	3267.5
26	4.854	132.00	638.0
Tot.			10316.30

Massa totale acciaio: 10316.30 Kg
Posizioni inutilizzate : 24, 45, 49, 50, 51.

DISTINTA FERRI SPALLA B FONDAZIONE

Sagoma	Pos.	φ (mm)	nb	A (cm)	B (cm)	C (cm)	L (m)	Ltot (m)	Note
1	1	22	103	140	590		8.70	896.10	
	2	26	205	140	590		8.70	1783.50	
	16	26	62	130	140		4.00	248.00	
2	31	16	8	50	590		6.90	55.20	
	3	20	150	255	140		3.95	592.50	
	19	16	34	245	40		2.85	96.90	
3	21	16	34	40	245		2.85	96.90	
	4	20	90	255	140		3.95	350.50	
	29	16	8	1010	50		10.60	84.80	
4	30	16	8	50	1150		12.00	96.00	
	14	26	63	1000	26		12.00	744.00	
	15	26	62	960			9.60	595.20	
5	20	22	100	50	132	60	4.24	424.00	

Massa barre

φ	kg/m	Ltot	kg
16	1.578	23600	372.488
18	1.998	19380	387.127
20	2.466	94800	2337.910
22	2.984	132010	3839.233
26	4.168	337070	14048.383
Tot.			21085.141

Massa totale acciaio: 21085.141 kg

DISTINTA FERRI SPALLA B ELEVAZIONE

Sagoma	Pos.	φ (mm)	nb	A (cm)	B (cm)	C (cm)	D (cm)	E (cm)	F (cm)	L (m)	Ltot (m)	Note
1	5	20	150	140	195					3.35	503.08	
	27	14	20	394	16					4.10	81.99	
	28	14	20	16	1184					12.00	240.02	
2	38	16	13	590	140					12.00	120.00	
	37	16	13	140	590					7.30	73.00	
	46	18	17	40	395/398					4.35/4.38	74.20	
3	6	20	90	140	195					3.35	301.86	
	11	16	6	100	560					6.60	39.80	
	12	16	6	1000	100					12.00	72.00	
4	17	18	17	395/398	40					4.35/4.38	74.20	
	18	18	17	40	395/398					4.35/4.38	74.20	
	25	14	20	1184	16					12.00	239.94	
5	26	14	20	16	394					4.10	82.07	
	38	16	13	590	140					7.30	73.00	
	39	16	13	140	1060					12.00	120.00	
6	47	18	17	40	395/398					4.35/4.38	74.20	
	57	28	20	47	193					2.40	48.00	
	58	16	6	45	555					6.00	36.00	
7	7	16	80	135	30					3.00	240.00	
	32	18	26	40	440					5.20	135.20	
	34	18	26	40	440					5.20	135.20	
8	35	12	20	255	30					5.40	108.00	
	48	18	40	40	330					4.10	164.00	
	53	12	2	30	1042					11.02	22.03	
9	8	16	12	101	98					3.00	36.00	
	22	16	14	106	88					3.00	42.00	
	9	20	80	235	30					5.00	400.00	
10	82	16	53	52	21					1.25	66.25	
	41	16	75	16	365	23				4.04	302.98	
	10	10	2	600						12.00	24.00	
11	13	16	4	100	255					4.55	18.20	
	23	12	20	1200						12.00	240.00	
	59	16	3	620						6.20	18.60	
12	61	16	4	1000						10.00	40.00	
	33	8	308	10	140					1.60	492.80	
	42	8	280	10	40					0.80	168.00	
13	44	8	308	10	30					0.50	154.00	
	54	8	80	10	200					2.20	176.00	
	40	16	75	23	365	16				4.04	303.05	
14	43	12	6	21	10	87	102	92	98	4.40	26.40	
	52	12	53	23	10	21	46	25	42	2.00	106.00	
	55	16	70	32	198	61	129			4.20	294.00	
15	56	28	20	32	198	61	129			4.20	84.00	
	60	16	8	35	365					4.00	32.00	

Massa barre

φ (mm)	M/L (kg/m)	Ltot (m)	Mtot (kg)
8	0.395	990.80	391.0
10	0.617	24.00	14.8
12	0.888	502.43	446.1
14	1.208	644.01	778.2
16	1.578	1926.68	3049.9
18	1.998	668.82	1336.0
20	2.466	1204.95	2971.6
26	4.854	132.00	638.0
Tot.			9616.60

Massa totale acciaio: 9616.60 Kg
Posizioni inutilizzate : 24, 45, 49, 50, 51.

DISTINTA FERRI SOLETTA IMPALCATO

Sagoma	Pos.	φ (mm)	nb	A (cm)	B (cm)	C (cm)</
--------	------	--------	----	--------	--------	----------