

PROGETTO DI FATTIBILITA' TECNICA ED ECONOMICA

CUP C39B18000060006

CIG 7690329440

RIF. PERIZIA

P.3062

TITOLO PROGETTO

NUOVA DIGA FORANEA DEL PORTO DI GENOVA AMBITO BACINO SAMPIERDARENA

TITOLO ELABORATO:

**RAPPORTO INDAGINE GEOTECNICA A MARE
FACTUAL REPORT**

ELABORATO N°:

MI046R-PF-D-G-R-014-00


NOME FILE:

MI046R-PF-D-G-R-014-00.docx

| DATA | ELABORATO | CONTROLLATO | APPROVATO |
|-----------|--------------------------|-------------|----------------------------|
| 30/4/2021 | J.Davies/C.Brandish-Lowe | P.Smorgon | A.Lizzadro |
| REVISIONE | N° | DATA | DESCRIZIONE |
| | 00 | 30/4/2021 | EMISSIONE PER APPROVAZIONE |
| | | | |
| | | | |
| | | | |

| PROGETTISTI | PROGETTAZIONE |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <p>Mandatario: </p> <p>Responsabile dell'integrazione delle prestazioni specialistiche Dott. Ing. Antonio Lizzadro</p> <p>   </p> <p>STUDIO BALLERINI INGEGNERI ASSOCIATI  ALBERTO ALBERT INGEGNERE</p> | <p></p> <p>Dott. Ing. Antonio Lizzadro</p> |

| D.E.C. | VERIFICATO | VALIDATO R.U.P. | IL RESP. DELL'ATTUAZIONE |
|----------------------|------------|--------------------|--------------------------|
| Ing. Francesca Arena | RINA CHECK | Ing. Marco Vaccari | Dott. Umberto Benezzoli |
| | | | |



VOLUME II – MEASURED AND DERIVED GEOTECHNICAL PARAMETERS AND FINAL RESULTS

Genoa Port Extension Geotechnical Survey (PFTE)

Prepared for: TECHNITAL S.p.A and Modimar S.r.l



Geoquip Marine Ref: GMOP20-G-013-FAC-01

Project No: GMOP20-G-013

Revision: B3

Date: 10 February 2021

DOCUMENT CONTROL AND REVISION STATUS

Document Title Volume II – Measured and Derived Geotechnical Parameters and Final Results

Project Genoa Port Extension Geotechnical Survey (PFTE)

Client TECHNITAL S.p.A and Modimar S.r.l

Project No. GMOP20-G-013

GEOQUIP Document Ref. GMOP20-G-013-FAC-01

Revision No. B3

| Document Distribution | | |
|-----------------------|-----------------------------------|------------------|
| Copy Number | Distributed to | Date |
| Master | GEOQUIP Server | 10 February 2021 |
| 1 | TECHNITAL S.p.A and Modimar S.r.l | 10 February 2021 |

| Revision History | | Date | Original | Checked | Approved | Client |
|------------------|------------------------|------------------|----------|---------|----------|--------|
| A1 | Draft | 25 January 2021 | JWD | CBL | | |
| B1 | Draft Issue to COMPANY | 26 January 2021 | JWD | CBL | TJP | |
| B2 | Draft Issue to COMPANY | 02 February 2021 | RBB | CBL | TJP | |
| B3 | Draft Issue to COMPANY | 10 February 2021 | JWD | CBL | TJP | |

Signatory Legend:

| | |
|-----|---------------------|
| JWD | Josh Davies |
| CBL | Chris Brandish-Lowe |
| TJP | Torran Purchase |
| RBB | Ryan Benjamin Bates |

Geoquip Marine Operations AG designated contact for any queries regarding this document:

| Name | Job Title | Telephone | Email |
|-----------------|-----------------|-----------------|------------------------------------|
| Torran Purchase | Project Manager | +44 7980 611379 | torran.purchase@geoquip-marine.com |

EXECUTIVE SUMMARY

Geoquip Marine Operations AG (GEOQUIP) has been contracted by TECHNITAL S.p.A and Modimar S.r.l (COMPANY), for the provision of an interim geotechnical investigation close to the entrance to the Port of Genoa, Italy. The objective of the project is to determine the technical and economic feasibility to construct a new breakwater.

The purpose of the site investigation was to determine soil stratigraphy, classification, engineering parameters and depth to rockhead for a planned offshore breakwater extension.

Fieldwork operations for this project commenced on 10 December 2020 in the port of Genoa, Italy and were conducted from the GEOQUIP owned and operated vessel MV Geoquip Saentis, on which the GEOQUIP owned and operated GMR600 drill rig is installed. Details of the operations completed during the fieldworks, including preliminary in situ results, positioning and water depth data, daily logs, and equipment calibrations and verifications are outlined in the Field report (GMOP20-G-013-FLD-01).

Water depth measurements were conducted at the start of each location by measuring the drill string length from the Seabed Frame (SBF) on the seabed to the Drill Floor on the vessel with compensation (minimal weight) to ensure that both accurate water depth measurements and undisturbed samples could be obtained from mudline. The measurements are then reduced to sea level at Lowest Astronomical Tide (LAT).

The nominal Scope of Work (SOW) consisted of 14 boreholes. An additional alternating borehole was later requested during the fieldwork operations and agreed by the COMPANY totalling 15 boreholes. The proposed borehole locations were in close proximity to the existing breakwater which required close coordination with the local harbour authority to ensure the safety of the operations given marine traffic entering and exiting the existing port. The completed scope of works included:

- 7 x continuous PCPT (PCPT)
- 5 x continuous sampling (CC)
- 5 x alternating to 80m (PCPT/CC) incl. 2 bumpover locations

Due to adverse weather conditions some locations were investigated by more than one attempt, for the purpose of this report, all data collected at these locations have been presented on combined plots in Appendix A.

The onshore laboratory testing has been contracted to COMPANY contractor SOCOTEC ITALIA, therefore no results of any onshore testing will be included in this report.

The geology at the site under Order No.204/2020 for the purpose of Geotechnical Investigation consists of an extremely variable stratigraphy ranging from loose gravels to very high strength clays with the isolated presence of competent rock. Six preliminary primary soil units have been identified, unitised in correspondence with the existing onshore investigation (L1, Ch1, S1, L2, A and G), two rock units (MR and F) and one made ground unit for human activity (MG). These have been subdivided based on changing geotechnical and geological properties and are presented below and in more detail in Table 2.2.

| Soil Unit | Description |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| L1A | Extremely low to low strength sandy CLAY with rare fibrous organic matter and rare shell fragments. |
| L1B | Interbedded very low to medium strength CLAY with occasional pockets of fibrous organic matter and rare shell fragments and rare closely spaced thin beds of sand. |
| Ch1 | Low to high strength sandy SILT with occasional closely spaced thin beds of silty sand. |
| S1A | Extremely loose to medium dense silty fine SAND with rare mica and rare shell fragments with very closely spaced thick laminations of medium to coarse sand. |
| S1B | Dense to very dense clayey gravelly fine to coarse SAND. Gravel is fine to coarse and subangular to rounded. |
| L2 | High to very high strength CLAY with occasional pockets of fine to coarse sand and rare shell fragments. |
| A | Interbedded very high to extremely high strength sandy CLAY with rare shell fragments and occasional closely spaced thin to thick laminations of dark grey fine sand and clayey SAND with frequent extremely closely to very closely spaced thin laminations of clay. |
| G | Fine to coarse angular to rounded GRAVEL with rare sand and rare clay. Sand is medium to coarse. |
| MR | Extremely weak thinly laminated fissured weathered fine grained MUDROCK with occasional closely to medium spaced thin to medium beds of strong black marlstone, occasional calcite pockets. |
| F | Medium strong to strong weathered fine grained MARLSTONE with occasional thin laminations and pockets of calcite. |
| MG | MADE GROUND with silty fine to medium SAND with rare gravel, rare pockets of decayed wood, rare textile material (clothes and threads) and rare shell fragments. Gravel is fine to coarse and angular. |

The site investigation correlates with the wider geological understanding that during a period of lateral extension, normal faulting occurred in a general SSW-NNE trend resulting in the formation of a horst and graben structure. The borehole logs and fence diagrams demonstrate these dramatic lateral changes in unit depth below seabed and successfully depicted the expected structure. The geology can be generally split between 'horst' geology and 'graben' geology with typical properties of basin style deposits.

From mudline (ML) the site is generally dominated by up to 18.00m thick sandy CLAYS (L1A) overlaying silty fine SAND (S1A). Below Units L1 & S1 the geology is characterised predominantly stratigraphic sequence of CLAY (L2) found at depths of 9.00m to 45.00m bml and in some instances a thick >24.10m bed of GRAVEL (G). This stratigraphy structure dominates the general trend across most of the site, particularly in the southern and western parts. However, as expected, the geology is significantly different in the raised horst sections where competent rock is encountered.

Location CC-5 is positioned on the western horst and dominated by 7.95m of fissured and weathered CLAYSTONE (MR) and 15.00m of overlying silty fine SAND (S1A). Similar geology was experienced at location PCPT-7, south of CC-5 but with the introduction of 4.90m of GRAVEL overlying competent MARLSTONE (F) and weathered MUDSTONE (MR).

Locations PCPT-1, CC-1 and PCPT-8 located on the eastern horst along the eastern extremity of the site and are also dominated by up to 7.80m of weathered fine grained MARLSTONE (F) overlaid by a series of L1A, S1A and L2. The deeper locations experienced GRAVEL which is thought to be of the same lithology as Unit F.

In northern part of the site in both the western and central graben, 4 channels (2 in CC-6 and 2 in CC-2) of sandy SILT (Ch1) experienced between depths 2.60m and 19.00m bml. In addition, location CC-3 encountered MADE GROUND (MG) at depth 0.50m bml.

The interpreted soil behaviour type from in situ PCPT data has a good correlation with the logged descriptions of recovered samples.

OVERVIEW MAP

Genoa Port Extension Geotechnical Survey (PFTE)



Map 1

Map showing General Location of Site

REPORTING STRUCTURE

| |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Volume I – Field Report |
| Field operations and preliminary results |
| Cover Page |
| Revision status and QA/QC |
| |
| Executive summary, including an overview map of investigated points |
| Table of contents |
| List of symbols and terms used |
| Chapter 1: Scope of field operations with description of the soil investigation platform (vessel/rig), overview over investigated points, with maps and coordinates, HSE, and organisation of work |
| Chapter 2: Log of drilling operations |
| Chapter 3: In situ testing operations, procedures and preliminary results |
| Chapter 4: Sampling operations, procedures and preliminary results, including inventory of recovered samples |
| Chapter 5: Field laboratory operations, procedures and test results |
| Chapter 6: Preliminary geotechnical borehole logs |
| Chapter 7: Log of daily field operations |
| Chapter 8: Positioning and survey, including water depth and tidal measurements |
| References |
| Appendix A-Z |

| |
|----------------------------------------------------------------------------------------------------|
| Volume II – Factual Report |
| Measured and derived geotechnical parameters and final results |
| Cover Page |
| Revision status and QA/QC |
| Summary of main report modifications from previous revision |
| Executive summary, including an overview map of investigated points |
| Table of contents |
| List of symbols and terms used |
| Chapter 1: Scope of field operations |
| Chapter 2: Summary of soil conditions and material overview |
| Chapter 3: Final geotechnical borehole logs,, lateral variation and PCPT results |
| Chapter 4: Final in situ test results, including discussion on validity of results |
| Chapter 5: Laboratory test procedures and final results including commentary on the results |
| References |
| Appendix A-C |
| |
| |
| |

*Current report is highlighted

TABLE OF CONTENTS

| | | |
|-----------|------------------------------------------------|-----------|
| 1. | SCOPE OF FIELD OPERATIONS | 1 |
| 1.1 | Overview | 1 |
| 1.2 | Related Documents..... | 1 |
| 1.3 | Summary of Fieldworks | 1 |
| 2. | SOIL CONDITIONS | 3 |
| 2.1 | Preliminary Site Overview..... | 3 |
| 2.2 | Preliminary Material Overview | 3 |
| 3. | FIELD BOREHOLE LOGS | 6 |
| 3.1 | Overview | 6 |
| 3.2 | Soil Descriptions and Layering | 7 |
| 3.3 | Lateral Variation | 7 |
| 3.4 | PCPT Results..... | 7 |
| 4. | IN SITU TEST RESULTS | 9 |
| 4.1 | Overview | 9 |
| 4.2 | Equipment Calibrations and Verifications | 9 |
| 4.3 | Downhole PCPT Tests | 9 |
| 5. | LABORATORY TEST RESULTS | 11 |
| 5.1 | Overview | 11 |
| 5.2 | Soil Classification Tests | 13 |
| 5.3 | Rock Classification Tests | 14 |
| 5.4 | Soil Strength Tests | 14 |
| 5.5 | Rock Strength Tests | 14 |
| 6. | REFERENCES | 16 |

LIST OF TABLES IN REPORT

| | |
|-----------|---------------------------------------|
| Table 1.1 | Summary of Completed Fieldworks |
| Table 2.1 | Material Overview Summary |
| Table 4.1 | Offshore Laboratory Testing Standards |
| Table 4.2 | Summary of Tests Completed Offshore |

LIST OF FIGURES AFTER REPORT

| | |
|-----------|----------------------------------------|
| Figure 1 | General Location Map |
| Figure 2 | Completed Borehole Location Plan |
| Figure 3 | Cross Section Location Plan |
| Figure 4A | Cross Section A'-A'' |
| Figure 4B | Cross Section B'-B'' |
| Figure 4C | Cross Section A'-A'' with CPT Results |
| Figure 4D | Cross Section B'-D with CPT Results |
| Figure 4E | Cross Section E-B' with CPT Results |
| Figure 4F | Cross Section C-E-B'' with CPT Results |

LIST OF TABLES AFTER REPORT

| | |
|----------|----------------------------------------|
| Table 1 | Borehole Summary |
| Table 2A | Generalised Stratigraphy (CC-1) |
| Table 2B | Generalised Stratigraphy (CC-2) |
| Table 2C | Generalised Stratigraphy (CC-3) |
| Table 2D | Generalised Stratigraphy (CC-4) |
| Table 2E | Generalised Stratigraphy (CC-5) |
| Table 2F | Generalised Stratigraphy (CC-6) |
| Table 2G | Generalised Stratigraphy (CC-7) |
| Table 2H | Generalised Stratigraphy (PCPT-1) |
| Table 2I | Generalised Stratigraphy (PCPT-2) |
| Table 2J | Generalised Stratigraphy (PCPT-3) |
| Table 2K | Generalised Stratigraphy (PCPT-4) |
| Table 2L | Generalised Stratigraphy (PCPT-5) |
| Table 2M | Generalised Stratigraphy (PCPT-6 & 6A) |
| Table 2N | Generalised Stratigraphy (PCPT-7) |
| Table 2O | Generalised Stratigraphy (PCPT-8 & 8A) |
| Table 3 | Project Geodetics |
| Table 4 | Fence Diagram Coordinates |

LIST OF APPENDICES

| | |
|------------|------------------------------|
| Appendix A | In situ Test Results |
| Appendix B | Offshore Laboratory Testing |
| Appendix C | Methodologies and Procedures |

LIST OF SYMBOLS AND ABBREVIATIONS

English

| | |
|-----------|-----------------------------------------|
| B_q | pore pressure ratio |
| D_r | relative density |
| e_{max} | maximum voids ratio |
| e_{min} | minimum voids ratio |
| f_s | sleeve friction |
| h | depth (below seabed) at start of test |
| m | metre |
| q_c | measured cone resistance |
| q_{net} | net cone resistance |
| q_t | corrected cone resistance |
| R_f | friction ratio |
| s_u | undrained shear strength |
| u_2 | measured pore pressure |
| z | test depth below bottom of the borehole |

Greek

| | |
|---------------|-----------------------------------------------------------|
| α | net area ratio of cone |
| Δu | excess pore pressure |
| γ' | submerged unit weight |
| γ_w | unit weight of water, assumed to be 9.81kN/m ³ |
| σ'_0 | In situ vertical effective stress |
| σ_{v0} | in situ vertical total stress |

Abbreviations

| | |
|---------|----------------------------------------------|
| ASTM | American Society for Testing and Material |
| BHA | Bottom Hole Assembly |
| bml | Below Mud Line |
| CC | Continuous Coring/Sampling Boreholes |
| COMPANY | TECHNITAL S.p.A and Modimar S.r.l |
| DGPS | Differential Geographical Positioning System |
| DOR | Daily Operations Report |
| DP | Dynamic Positioning |
| GEOQUIP | Geoquip Marine Operations AG |
| GMR | Geoquip Marine Derrick Rig |
| GSI | Geological Strength Index |
| HSE | Health Safety and Environment |
| ITRF | International Terrestrial Reference Frame |

| | |
|------|-----------------------------------------------------------|
| LAT | Lowest Astronomical Tide |
| LT | Local Time |
| ML | Mud Line |
| PCPT | Piezocone Penetration Test with pore pressure measurement |
| PLI | Point Load Index |
| PLT | Point Load Test |
| PM | Project Manager |
| RMR | Rock Mass Rating |
| SBF | Seabed Frame |
| USBL | Ultra-short baseline |
| UU | Unconsolidated Undrained Triaxial |

1. SCOPE OF FIELD OPERATIONS

1.1 Overview

Geoquip Marine Operations AG (GEOQUIP) were contracted by TECHNITAL S.p.A and Modimar S.r.l (COMPANY) to complete a geotechnical investigation, located in close proximity to the Port of Genoa, Italy. The purpose of the site investigation was to determine soil stratigraphy, classification, engineering parameters and depth to rockhead for a planned breakwater extension.

COMPANY required the completion of a series of boreholes across the site. The completed scope of work is summarised in Table 1.1.

The site for the proposed Port Extension/Breakwater is located south of the current breakwater between the western and eastern entrances to the Port of Genoa. The site is approximately 5.50km long by 1.00km wide south of the Port of Genoa, Italy, in water depths ranging between 26.07m to 54.76m LAT as calculated by recording drill string measurements at the start of each location from the compensated SBF on the seabed to the Drill Floor on the vessel and then reduced to sea level at LAT.

Fieldwork operations for this project commenced on 10 December 2020 in the port of Genoa, Italy and were conducted from the GEOQUIP owned and operated vessel MV Geoquip Saentis, on which the GEOQUIP owned and operated GMR600 drill rig is installed. Details of the operations completed during the fieldworks, including preliminary in situ results, positioning and water depth data, daily logs, and equipment calibrations and verifications are outlined in the Field report (GMOP20-G-013-FLD-01).

1.2 Related Documents

Further documents that apply to this project, and which may be referenced herein, include:

- Contract between GEOQUIP and COMPANY
- GEOQUIP Group Integrated Management System Documentation
- GEOQUIP Quality Health Safety and Environment Management System
- GEOQUIP Project Safety Plan including Emergency Response Plan (B3-PSP-01)
- GEOQUIP Project Execution Plan (B3-PEP-01)
- GEOQUIP Mobilisation Report (B3-MOB-01)
- GEOQUIP Field Report (B3-FLD-01)

1.3 Summary of Fieldworks

The completed fieldworks are summarised in Table 1.1.

Table 1.1 Summary of Completed Fieldworks

| Soil Investigation – Sampling and PCPT | | | |
|-----------------------------------------------|----------|-------------------------|-------------------------|
| Borehole No (n.) | Priority | Actual Depth (m) | Type (-) |
| CC-1 | 5 | 16.20 | CC |
| PCPT-1 | 6 | 25.00 | PCPT |
| CC-2 | 8 | 40.40 | CC |
| PCPT-2 | 1 | 41.86 | PCPT |
| CC-3 | 3 | 46.15 | CC |
| PCPT-3 | 2 | 34.40 | PCPT |
| CC-4 | 11 | 80.36 | 0-40m CC/40-80m CC/PCPT |
| PCPT-4 | 7 | 42.52 | PCPT |
| PCPT-5 | 4 | 42.32 | PCPT |
| CC-5 | 14 | 22.95 | CC |
| PCPT-7 | 9 | 10.85 | PCPT |
| CC-7 | 10 | 42.38 | CC (1 x PCPT stroke) |
| PCPT-6 | 15 | 47.25 | PCPT |
| PCPT-6A | 15a | 81.28 (42.20 Drill Out) | PCPT/CC |
| CC-6 | 13 | 47.90 | PCPT/CC |
| PCPT-8 | 12 | 4.30 | PCPT/CC |
| PCPT-8A | 16 | 65.05 | PCPT/CC |
| Total | - | 648.97 | - |
| Notes: | | | |
| Coring/ Sampling (CC) total length of 168.08m | | | |
| PCPT (PCPT) total length of 244.20m | | | |
| CC/PCPT Alternating total length of 236.69m. | | | |

The addition of PCPT-8 was agreed between GEOQUIP and COMPANY during the campaign. PCPT-6 and PCPT-8 were terminated early due to safety concerns over deteriorating weather conditions. Target depths were not reached and subsequent bump over locations were performed (PCPT-6A and PCPT-8A).

2. SOIL CONDITIONS

2.1 Preliminary Site Overview

The geology at the site under Order No.204/2020 for the purpose of Geotechnical Investigation consists of an extremely variable stratigraphy ranging from loose gravels to very high strength clays with the isolated presence of competent rock. Six preliminary primary soil units have been identified, unitised similarly to the existing onshore investigation (L1, Ch1, S1, L2, A and G), two rock units (MR and F) and one made ground unit for human activity (MG). These have been subdivided based on changing geotechnical and geological properties and are presented in Table 2.2.

The site investigation correlates with the wider geological understanding that during a period of lateral extension, normal faulting occurred in a general SSW-NNE trend resulting in the formation of a horst and graben structure. The cross-sections demonstrate these dramatic lateral changes in unit depth below seabed and successfully depicted the expected structure. The geology can be generally split between 'horst' geology and 'graben' geology with typical properties of basin style deposits.

From mudline (ML) the site is generally dominated by extremely low to low strength very dark greenish grey sandy CLAY (L1A) with thicknesses between 0.50m and 18.00m, overlaying extremely loose to medium dense very dark grey silty fine SAND (S1A) with a thickness of 1.00m to 15.00m.

Below Units L1 & S1, the geology is characterised predominantly by Unit L2 which consists of high to very high strength dark grey CLAY found at depths of 9.00m to 45.00m bml with a thickness of 3.40m and 25.25m. A thick >24.1m bed of greenish grey fine to coarse angular to rounded GRAVEL (G) is observed at 22.05m bml at the projected base of the graben. This stratigraphy structure dominates the general trend across most of the site, particularly in the southern and western parts and are typical of basin deposits within the grabens. However, as expected, the geology is significantly different in horst structures where competent rock is encountered as well as thick gravels in the eastern extents of the site.

Location CC-5 is positioned on the western horst and dominated by 7.95m of very weak to weak dark grey fissured and weathered CLAYSTONE (MR) at 15.00m bml with 15.00m of overlying very dark grey silty fine to coarse SAND (S1A). Relatively similar geology was experienced at location PCPT-7, south of CC-5 but with the introduction of 4.90m of greenish grey fine to coarse angular to rounded GRAVEL overlying competent MARLSTONE (F) and weathered MUDSTONE (MR).

Locations PCPT-1, CC-1 and PCPT-8 located on the eastern horst along the eastern extremity of the site and are also dominated by up to 7.80m of medium strong to strong black and brown weathered fine grained MARLSTONE (F) overlaid by a series of L1A, S1A and L2. The deeper locations experienced very dense black to greyish brown angular to subrounded fine to coarse GRAVEL which is thought to be of the same lithology as Unit F.

In northern part of the site in both the western and central graben, 4 channels (2 in CC-6 and 2 in CC-2) of low to high strength sandy SILT (Ch1) of 1.60m to 6.00m are experienced between depths 2.60m and 19.00m bml. The unit is typical of a channel feature.

At location CC-3, the investigation encountered MADE GROUND (MG) with silty fine to medium sand and rare gravel at depth 0.50m bml. The recovery included rare pockets of decayed wood, rare textile material (clothes and threads) and rare shell fragments.

2.2 Preliminary Material Overview

The materials found at the site can be split into the following broad categories based on finding of the ground investigation. On the absence of further onshore laboratory testing for each soil unit identified the range of PCPT parameters have been provided.

Table 2.2 Material Overview Summary

| Soil Unit | Description | Comment | Characteristics (CPT Profile) |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| L1A | Extremely low to low strength very dark greenish grey (GLEY 1 5GY 3/1) sandy CLAY with rare fibrous organic matter and rare shell fragments | - Seabed sediment | Qnet (MPa): -0.079 to 1.557 Rf (%): 0.278 to 12.256 Bq: -0.266 to 1.034 |
| L1B | Interbedded very low to medium strength greenish grey (GLEY 1 10GY 4/1) CLAY with occasional pockets of fibrous organic matter and rare shell fragments and rare closely spaced thin beds of sand | - Slightly higher strength than unit L1A - Less sand content - Rare interbedded CLAY/sandy CLAY/beds of sand | Qnet (MPa): 0.001 to 0.901 Rf (%): 0.000 to 4.941 Bq: 0.301 to 2.575 |
| Ch1 | Low to high strength sandy SILT with occasional closely spaced thin beds of silty sand | - Shallow and thin channel of silt rarely encountered in the northern part of the site | Qnet (MPa): 0.354 to 1.733 Rf (%): 0.918 to 2.760 Bq: -0.096 to 0.270 |
| S1A | Extremely loose to medium dense very dark grey (GLEY 1 N 3/) silty fine SAND with rare mica and rare shell fragments with very closely spaced thick laminations of medium to coarse sand | - Sand underlying unit L1A | Qnet (MPa): -0.167 to 80.720 Rf (%): 0.000 to 5.111 Bq: -0.195 to 0.223 |
| S1B | Dense to very dense dark greyish brown (2.5Y 4/2) to light olive brown (2.5Y 5/3) clayey gravelly fine to coarse SAND. Gravel is grey to black, fine to coarse and subangular to rounded | - Denser than unit S1A, coarse grains and gravelly | Qnet (MPa): 8.616 to 80.183 Rf (%): 0.000 to 1.349 Bq: -0.015 to 0.007 |
| L2 | High to very high strength dark grey (GLEY 1 N 4/) CLAY with occasional pockets of fine to coarse sand and rare shell fragments | - High to very high strength layers of clay mostly underlying B units | Qnet (MPa): -0.371 to 56.919 Rf (%): 0.000 to 6.951 Bq: -0.068 to 0.843 |
| A | Interbedded very high to extremely high strength dark greenish grey (GLEY 1 10Y 4/1) sandy CLAY with rare shell fragments and occasional closely spaced thin to thick laminations of dark grey fine sand and dark greenish grey (GLEY 1 10Y 4/1) clayey SAND with frequent extremely closely to very closely spaced thin laminations of clay | - Higher strength than L2A, underlying L2A, sometimes with gravel - Interbedded sandy CLAY/clayey SAND. Only encountered once in the south-western part of the site | Qnet (MPa): -0.556 to 31.604 Rf (%): 0.000 to 2.457 Bq: 0.000 to 0.745 |
| G | Very dark grey (GLEY1 10Y 3/1), olive (5Y 5/4) and greenish grey (GLEY1 10Y 6/1) fine to coarse angular to rounded GRAVEL with rare sand and rare clay. Sand is medium to coarse | - Rare layers of gravel, sometimes between B and C or overlying Rock layers | Qnet (MPa): -0.072 to 70.212 Rf (%): 0.000 to 9.913 Bq: -0.166 to 0.029 |
| MR | Extremely weak to weak thinly laminated fissured weathered fine-grained grey (GLEY1 N 5/) to dark grey (GLEY 1 N4/) MUDROCK with occasional closely to medium | - Rare and very thin layer of Mudstone encountered in the northern and southern parts of the site | N/A |

| | | | |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| | spaced thin to medium beds of strong black marlstone and occasional pockets of calcite. RMR=N/A, GSI=10, FI=N/A | | |
| F | Medium strong to strong black (5Y 2.5/1) and brown (7.5YR 4/6) weathered fine grained MARLSTONE with occasional thin laminations and pockets of calcite. RMR=12-13, GIS=20-35, FI=2-6 | - Marlstone mostly encountered in eastern part of the site | N/A |
| FG | Very dense black (GLE Y 1 N 2.5/) to greyish brown (2.5Y 4/2) angular to subrounded fine to coarse GRAVEL of marlstone with rare thin laminations of calcite and rare light brown clay | - Likely to be drilling induced. Mostly encountered in eastern part of the site | Qnet (MPa): -0.163 to 70.658 Rf (%): 0.000 to 3.554 Bq: -0.004 to 0.001 |
| MG | Dark grey (GLE Y 1 N 4/1) MADE GROUND (silty fine to medium SAND) with rare gravel, rare pockets of decayed wood, rare textile material (clothes and threads) and rare shell fragments. Gravel is fine to coarse and angular | - Made Ground (from human activity) encountered once in the northern part of the site | N/A |

3. FIELD BOREHOLE LOGS

The field borehole logs are based on the field descriptions, and in situ and offshore laboratory tests outlined in Sections 4 and 5. Further onshore testing should be completed to confirm the soil type and characteristics.

3.1 Overview

All combined PCPT and sampling data are presented on the borehole logs available in Appendix A. The water depths shown on logs are as measured by the drill string at commencement of the borehole and reduced to Lowest Astronomical Tide (LAT).

Raw and derived in situ test logs along with acquisition parameters and observation summaries are presented in Appendix A.

The following are presented respective logs and reports:

1. Combined Borehole Log for Sampling and PCPT locations:
 - a. PCPT and Sampling key
 - b. Depth
 - c. Legend (including geological unit designation)
 - d. Soil Layering
 - e. Raw Results
 - i. Sleeve Friction
 - f. Derived Results
 - ii. Net Cone Resistance
 - iii. Pore Pressure Ratio
 - iv. Undrained Shear Strengths derived from q_{net}
 - v. Relative Density derived from q_t
 - g. Offshore laboratory test results
 - vi. Water Content, and Bulk and Dry Densities
 - vii. Undrained Shear Strength from UU, Laboratory Vane, Torvane and Pocket Penetrometers
2. Borehole Log for PCPT location
 - a. PCPT key
 - b. Depth
 - c. Legend (including geological unit designation)
 - d. Interpreted Soil Layering
 - e. Raw Results
 - i. Sleeve Friction
 - f. Derived Results
 - i. Net Cone Resistance
 - ii. Pore Pressure Ratio
 - iii. Undrained Shear Strengths derived from q_{net}

iv. Relative Density derived from q_t

3. Logs of Raw In Situ Test Results

- a. PCPT key
- b. Depth
- c. Raw Results
 - i. Measured Cone resistance
 - ii. Sleeve Friction
 - iii. Excess Pore Pressure

4. Logs of Derived In Situ Test Results

- a. PCPT key
- b. Depth
- c. Raw Results
 - i. Sleeve Friction
- d. Derived Results
 - i. Net Cone Resistance
 - ii. Pore Pressure Ratio
 - iii. Friction Ratio

3.2 Soil Descriptions and Layering

The soil descriptions presented on the combined borehole logs are based on the field descriptions of recovered samples and interpretations of the PCPT data. These have been developed using the results from the offshore laboratory testing and in situ results. Descriptions are in accordance with ISO 19901-8 and the guidelines presented in Appendix C. Preliminary (with the absence of further onshore laboratory testing) borehole stratigraphy descriptions are presented in Table 2A to Table 2N.

3.3 Lateral Variation

Cross sections showing the extent of each geological Unit are presented in Figure 4A to Figure 4F with a cross section plan presented in Figure 3.

3.4 PCPT Results

Raw and derived PCPT results are presented in Appendix A. A summary of these results including details of calculations is presented in Appendix C.

3.4.1 Undrained Shear Strength

Undrained shear strength can be estimated from PCPT data using the following relationship (Lunne et al., 1997).

$$s_u = \frac{q_{net}}{N_{kt}}$$

where:

s_u = Undrained shear strength

q_{net} = net cone resistance

N_{kt} = cone factor

For the purpose of this report a N_{kt} values between 15 and 20 have been used for all cohesive soil units found across the site. These values showed good correlation with the measured offshore undrained shear strength results apart from Unit L2 between 19.75 to 45.00m at location CC-4 where the derived shear strength is higher than the measured values. On completion of further onshore laboratory strength testing it is suggested these N_{kt} values are reviewed and amended if appropriate.

A graphical representation of the derived undrained shear strength alongside measured laboratory data is presented on the borehole logs presented in Appendix A.

3.4.2 Relative Density

In situ relative density was determined from the results of PCPTs based on the cone resistance as follows (Jamiolkowski et al., 2003):

$$D_r(dry) = \frac{1}{0.0296} \cdot \ln \left[q_c / \left[2.494 \cdot \left[\frac{\sigma'_{v0} \cdot \left[\frac{1 + 2 \cdot K_0}{3} \right]^{0.467}}{100} \right] \right] \right]$$

$$D_r(saturated) = \left[\frac{-1.87 + 2.32 \cdot \ln \frac{1000 \cdot q_c}{(100 \cdot \sigma'_{v0})^{0.5}}}{100} + 1 \right] \cdot D_r(dry)$$

| | | | |
|--------|------------------|---|--------------------------------------------|
| where: | $D_r(dry)$ | = | Estimated dry relative density (%) |
| | $D_r(saturated)$ | = | Estimated saturated relative density (%) |
| | q_c | = | Measured cone resistance (MPa) |
| | σ'_{v0} | = | Vertical effective overburden stress (kPa) |
| | K_0 | = | Coefficient of lateral earth pressure |

A graphical representation of the relative density for $K_0=1.0$ is presented on the borehole logs presented in Appendix A.

4. IN SITU TEST RESULTS

4.1 Overview

A total of 13 boreholes involving in situ testing were completed at 10 locations during this campaign. The completed boreholes and subsequent testing regimes are presented below.

A total of 3 continuous PCPT boreholes:

- PCPT-2
- PCPT-3
- PCPT-4

A total of 4 primarily continuous PCPT boreholes with sample collection where necessary:

- PCPT-1
- PCPT-5
- PCPT-6
- PCPT-7

A total of 4 alternating sampling/PCPT boreholes:

- CC-6
- PCPT-6A (bumpover)
- PCPT-8
- PCPT-8A (bumpover)

1 borehole involving continuous sampling from seabed to 40 m, followed by alternating sampling/PCPT to 80 m:

- CC-4

1 primarily continuous sampling borehole with the exception of 1 PCPT stroke:

- CC-7

4.2 Equipment Calibrations and Verifications

All relevant offshore laboratory equipment and PCPT equipment were calibrated during the mobilisation phase of the project. Calibration certificates and verification data for PCPT cones are presented in “Volume I – Field Operations and Preliminary Results” (B3-FLD-01).

4.3 Downhole PCPT Tests

4.3.1 Equipment and Results Overview

All PCPT testing was completed using the GEOQUIP downhole PCPT tool. Several PCPT cones were made available during the project which included both 10cm² compression and subtraction cones. Two tool lengths were available; 1.6m and 3.0m.

A summary of the cones used during this project are presented in “Volume I – Field Operations and Preliminary Results” (B3-FLD-01).

During testing, all data was observed topside in real time. The following channels were recorded during testing:

- Penetration depth

- Cone resistance
- Local friction
- Pore water pressure

Presentation of PCPT results is presented in Appendix A.

4.3.2 Downhole PCPT Testing Procedure

All PCPT testing was conducted by the Tool Operators with direction from the Shift Engineers. PCPT testing was conducted with a rate of penetration of approximately 2cm/s. All tests were taken to full stroke unless the Tool Operator terminated the test early. Refusal of the test may occur for a variety of reasons including but not limited to avoidance of equipment damage and to ensure data integrity.

The testing was conducted in accordance with ISO 22476-1 and with GEOQUIP procedures. Nominally all PCPT tests aimed to recover ISO 19901-8 (2014) application class 1 for soft or loose soil and application class 2 in stiff clays and sands. PCPT data acquired are presented graphically against depth in Borehole logs in Appendix A including Raw and Derived results.

4.3.3 Commentary on Downhole PCPT Tests

All the tests achieved application class 1 as set out in ISO 19901-8 (2014). A summary of PCPT test results including deck to deck offset is presented in Table 3 of the “Volume I – Field Operations and Preliminary Results” (B3-FLD-01) report. A good correlation has been found between the logged descriptions of recovered samples and of the interpreted soil behaviour from PCPT data.

The PCPT baselines and calculated application classes are presented in “Volume I – Field Operations and Preliminary Results” (B3-FLD-01).

4.3.4 Dissipation Tests

The dissipation test measures the decay of pore water pressure over a specified amount of time.

A PPDT was undertaken during PCPT at a selected depth as directed by the onboard client representative. To start the test the penetration during the selected PCPT was stopped and the initial pore pressure was recorded. The pore water pressure (u_2) was then continuously measured against time in seconds. When the required dissipation value has been met, in this case it was at least 60% dissipation, the dissipation test is deemed complete and the PCPT penetration resumes to complete the PCPT as required.

Dissipation results are presented in Appendix A.

4.3.5 Commentary on Dissipation Tests

The majority of the dissipation tests performed yielded good results. A few tests performed in granular soils and very soft clays near mudline, did not produce successful results due to little or no excess pressure at the start of the test.

5. LABORATORY TEST RESULTS

5.1 Overview

A total of 14 boreholes involving sampling were completed at 12 locations during this campaign. The completed boreholes and subsequent testing regimes are presented below. Presentation of recovered sample results is discussed in Section 6.

A total of 4 continuous sampling boreholes:

- CC-1
- CC-2
- CC-3
- CC-5

A total of 4 primarily continuous PCPT boreholes with sample collection where necessary:

- PCPT-1
- PCPT-5
- PCPT-6
- PCPT-7

A total of 4 alternating sampling/PCPT boreholes:

- CC-6
- PCPT-6A (bumpover)
- PCPT-8
- PCPT-8A (bumpover)

1 borehole involving continuous sampling from seabed to 40 m, followed by alternating sampling/PCPT to 80 m:

- CC-4

1 primarily continuous sampling borehole with the exception of 1 PCPT stroke:

- CC-7

It has been agreed between GEOQUIP and COMPANY that no onshore laboratory testing shall be conducted by GEOQUIP. No onshore laboratory testing results have been included in this report.

Offshore laboratory testing was completed in the offshore laboratory mobilised for the project.

Table 5.1 details the standards to which all testing for offshore testing were to be conducted to, with the quantities of completed tests outlined in Table 5.2.

Table 5.1 Offshore Laboratory Testing Standards

| Test | Standard |
|----------------------------------------|---------------------------------------------------------------|
| Density Tests | ISO 17892-02 (2004) (as per GEOQUIP procedures ¹) |
| Miniature Vane Tests | ASTM D4648-05 (as per GEOQUIP procedures ¹) |
| Pocket Penetrometer | NGI (1989) (as per GEOQUIP procedures ¹) |
| Point Load | ISRM (1985) (as per GEOQUIP procedures ²) |
| Torvane Tests | BS1377 (as per GEOQUIP procedures ¹) |
| Unconsolidated Undrained Triaxial Test | ISO 17892-08 (2004) (as per GEOQUIP procedures ¹) |
| Water Content | ISO 17892-01 (2004) (as per GEOQUIP procedures ¹) |

¹ Offshore Sample Handling, Soil Description & Laboratory Testing (GM-MSP-OI-5-3-3)

² Offshore Sample Handling, Rock Description & Laboratory Testing (GM-MSP-OI-5-3-4)

Table 5.2 Summary of Tests Completed Offshore

| BH ID | Density tests | Water Content Tests | Pocket Penetrometer Tests | Torvane Tests | Miniature Vane Tests | Unconsolidated Undrained Triaxial Tests | Point Load |
|---------|---------------|---------------------|---------------------------|---------------|----------------------|-----------------------------------------|------------|
| CC-1 | 12 | 14 | 9 | 6 | 2 | - | 5 |
| PCPT-1 | - | - | 1 | - | - | - | 5 |
| CC-2 | 49 | 49 | 54 | 50 | 7 | 1 | - |
| PCPT-2 | - | - | - | - | - | - | - |
| CC-3 | 37 | 22 | 26 | 22 | 4 | 1 | - |
| PCPT-3 | - | - | - | - | - | - | - |
| CC-4 | 95 | 21 | 92 | 49 | 5 | - | - |
| PCPT-4 | - | - | - | - | - | - | - |
| PCPT-5 | - | 2 | - | - | - | - | - |
| CC-5 | 27 | 12 | - | - | - | - | 3 |
| PCPT-7 | - | 7 | - | - | - | - | - |
| CC-7 | 66 | 8 | 68 | 60 | 6 | - | 1 |
| PCPT-6 | 1 | 3 | - | - | - | - | - |
| PCPT-6A | 8 | - | 11 | - | - | - | - |
| CC-6 | 18 | 10 | 16 | 6 | - | - | - |
| PCPT-8 | 3 | 1 | - | 6 | 1 | - | - |
| PCPT-8A | 17 | 8 | 13 | - | 3 | - | - |
| Total | 333 | 157 | 290 | 199 | 28 | 2 | 14 |

5.2 Soil Classification Tests

5.2.1 Water Content

Moisture content tests were carried out shortly after extrusion on samples recovered in the field and alongside strength and consolidation tests on undisturbed clay samples in accordance with ISO 17989-1. The results are ranging between 11% and 84%.

The results are plotted against depth on the borehole logs presented in Appendix A and also in tabular form in Appendix B.1.

5.2.2 Density

Bulk (or wet) and dry density was determined on appropriate extruded samples in the field alongside strength tests on undisturbed clay samples in accordance with ISO 17989-1. The results are ranging from 1.45 to 2.25Mg/m³ (bulk density) and 0.94 to 1.90Mg/m³ (dry density).

The results are plotted against depth on the borehole logs presented in Appendix A and also in tabular form in Appendix B.1.

5.3 Rock Classification Tests

5.3.1 Water Content

Moisture content tests were carried out shortly after cutting the core barrel in the field and alongside strength tests in accordance with ISO 17989-1. The results are ranging between 1% and 17%.

The results are plotted against depth on the borehole logs presented in Appendix A and also in tabular form in Appendix B.1.

5.3.2 Density

Bulk (or wet) and dry density was determined on appropriate rock samples in the field alongside strength tests in accordance with ISO 17989-1. The results are ranging from 2.52 to 2.99Mg/m³ (bulk density) and 2.50Mg/m³ to 2.50Mg/m³ (dry density).

The results are plotted against depth on the borehole logs presented in Appendix A and also in tabular form in Appendix B.1.

5.4 Soil Strength Tests

5.4.1 Pocket Penetrometer & Torvane

Pocket penetrometer tests were performed in the field on cohesive soil samples to determine the undrained shear strength. The results are plotted against depth on the borehole logs presented in Appendix A and also in tabular form in Appendix B.2.

5.4.2 Miniature Vane

Miniature laboratory vane tests were completed on cohesive soils in the offshore laboratory in accordance with ASTM D4648. This test is most suitable for extremely soft to medium strength clays especially when the soil is too soft for conventional unconsolidated undrained triaxial tests.

The tests conducted offshore were performed on the sample before it was extruded. The vanes utilised had a diameter of 12.7 or 25.4 mm and the rotation rate was set to 60°/min.

These results are presented on the logs in Appendix A and tabulated in Appendix B.2.

On selected offshore samples remoulded vane tests were performed by completing the undisturbed test then quickly rotating the vane a minimum of 5 times before commencing the test again.

These results are tabulated in Appendix B.2.

5.4.3 Unconsolidated Undrained Triaxial

UU tests have been conducted in the offshore laboratory on cohesive soil samples to determine the undrained shear strength. The triaxial test was completed in line with ISO 17892-08 (2004). The results are plotted against depth on the borehole logs presented in Appendix A. Individual test reports are presented graphically, and results are summarised in tabular form in Appendix B.2.

UU tests ran to generally 15% axial strain and were conducted with confining pressures equal to the total in situ vertical stress or maximum cell pressure of 3000kPa.

5.5 Rock Strength Tests

This group of tests are used to organise the principal strengths of rock as appropriate.

5.5.1 Point Load Tests

Point load testing (PLT) is used to determine rock strength indexes in geotechnical practice. PLTs were conducted in the offshore laboratory on rock samples in accordance with ISRM Suggested Method for Determining Point Load Strength (1985) and ASTM D5731-16. The results are plotted against depth on the borehole logs presented in Appendix A.

The tests conducted offshore were performed on the competent rock samples. The $PLT_{(1s50)}$ results range between 0.5MPa and 4.4MPa.

6. REFERENCES

ASTM D2850, Standard Test Method for Unconsolidated-Undrained Triaxial Compression Test on Cohesive Soils, ASTM International, West Conshohocken, PA, 2015, www.astm.org

ASTM D2974-20e1, Standard Test Methods for Determining the Water (Moisture) Content, Ash Content, and Organic Material of Peat and Other Organic Soils, ASTM International, West Conshohocken, PA, 2020, www.astm.org

ASTM D4253-16, Standard Test Methods for Maximum Index Density and Unit Weight of Soils Using a Vibratory Table, ASTM International, West Conshohocken, PA, 2016, www.astm.org

ASTM D4254-16, Standard Test Methods for Minimum Index Density and Unit Weight of Soils and Calculation of Relative Density, ASTM International, West Conshohocken, PA, 2016, www.astm.org

ASTM D4648, Standard Test Methods for Laboratory Miniature Vane Shear Test for Saturated Fine-Grained Clayey Soil, ASTM International, West Conshohocken, PA, 2016, www.astm.org

ASTM D6528-17, Standard Test Method for Consolidated Undrained Direct Simple Shear Testing of Fine Grain Soils, ASTM International, West Conshohocken, PA, 2017, www.astm.org

International Standards Organisation (ISO), "Soil quality — Determination of carbonate content — Volumetric method, International Standard ISO 10693", Geneva, ISO

International Standards Organisation (ISO), "Geotechnical investigation and testing — Laboratory testing of soil — Part 1: Determination of water content, International Standard ISO 17892-1", Geneva, ISO

International Standards Organisation (ISO), 2014, "Petroleum and Natural Gas Industries – Specific Requirements for Offshore Structures – Part 8: Marine Soil Investigations, International Standard ISO 19901-8:2014", Geneva, ISO

ISRM (1985), "Suggested Methods for Determining Point Load Strength", International Society for Rock Mechanics Commission on Testing Methods, Int. J. Rock. Mech. Min. Sci. and Geomechanical Abstr., Vol 22, No. 2, 1985, pp. 51–60.

Ladd, C.C., Foott, R., Ishihara, K., Schlosser, F., and Poulos, H.G., (1977), "Stress-Deformation and Strength Characteristics", Proceedings 9th International Conference Soil Mechanics and Foundation Engineering, Tokyo, Japan, Vol 2., pp 421-494.

Ladd, R.S., (1978) "Preparing Test Specimens Using Undercompaction," Geotechnical Testing Journal, GTJODJ, Vol. 1, No. 1, pp. 16-23.

Lunne, T. and Christoffersen, H.P., (1983), "Interpretation of Cone Penetrometer Data for Offshore Sands.", Proceedings of 15th Offshore Technology Conference, Houston, Paper No. OTC 4464, pp. 181-192.

Lunne, T., Robertson, P.K. and Powell, J.J.M., (1997), "Cone Penetration Testing", Blackie Academic & Professional, pp. 64-67.

Mesri, G., (1975) New design procedure for stability of soft clays: Discussion. ASCE Journal of the Geotechnical Engineering Division, 101(GT4), pp. 409-412.

Schmidt, B., (1966), "Discussion of Earth Pressure at rest related to stress history", Proc. 8th Int. Conf. on Soil Mechanics and Foundation Engineering, Moscow, Vol. 4, pp. 26-28.

FIGURES

Figure 1 General Location Map

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port Extension Geotechnical Survey (PFTE)
Project Number: GMOP20-G-013



General Location Plan


Ref.: GMOP20-G-013-FAC-01

Figure Number:

1

Figure 2 Completed Borehole Location Plan

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port Extension Geotechnical Survey (PFTE)
Project Number: GMOP20-G-013



Completed Borehole Location Plan


Ref.: GMOP20-G-013-FAC-01

Figure Number:

2

Figure 3 Cross Section Location Plan

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port Extension Geotechnical Survey (PFTE)
 Project Number: GMOP20-G-013




Cross Section Location Plan


Ref.: GMOP20-G-013-FAC-01

Figure Number:

3

Figure 4A Cross Section A'-A''

| | | | |
|-------------------------------------------|------------------|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: A'-A'' | Coordinates ¹ of Baseline: Start of Baseline: 1491022mE 4916194mN End of Baseline: 1494852mE 4915038mN |  |
| Project Name: Genoa Port (PFTE) | | | |
| Project No.: GMOP20-G-013 | | | |




Local Geodetic Datum: Gauss-Boaga Fuso W



SITE STRATIGRAPHY

Ref: GMOP20-G-013-FAC-01














Figure Number:

Figure 4B Cross Section B'-B''

| | | | |
|-------------------------------------------|------------------|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: B'-B'' | Coordinates ¹ of Baseline: Start of Baseline: 1490873mE 4915562mN End of Baseline: 1494758mE 4914609mN |  |
| Project Name: Genoa Port (PFTE) | | | |
| Project No.: GMOP20-G-013 | | | |



Legend

| | | | |
|---------------------------------------------------------------------------------------|--------------------------------|---------------------------------------------------------------------------------------|-------------|
|  | = Clay |  | = Siltstone |
|  | = Silt |  | = Mudstone |
|  | = Sand |  | = Limestone |
|  | = Gravel |  | = Chalk |
|  | = Sandstone |  | = Peat |
|  | = Layer boundary | | |
|  | = Inferred layer boundary | | |
|  | = Baseline (see location plan) | | |

Local Geodetic Datum: Gauss-Boaga Fusu W


SITE STRATIGRAPHY


Ref: GMOP20-G-013-FAC-01

Figure Number:

4B

Figure 4C Cross Section A'-A'' with CPT Results


| | | | |
|-------------------------------------------|---------------------|----------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Line Number: A'-A'' | Coordinates ¹ of Baseline: |  |
| Project Name: Genoa Port (PFTE) | | Start of Baseline: 1491037mE 4916199mN | |
| Project No.: GMOP20-G-013 | | End of Baseline: 1494865mE 4915038mN | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W
² Maximum CPTU Tip (MPa): 75

FENCE DIAGRAM

Figure 4D Cross Section B'-D with CPT Results


| | | | |
|-------------------------------------------|-------------------|----------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Line Number: B'-D | Coordinates ¹ of Baseline: |  |
| Project Name: Genoa Port (PFTE) | | Start of Baseline: 1490862mE 4915542mN | |
| Project No.: GMOP20-G-013 | | End of Baseline: 1492813mE 4915101mN | |




¹ Local Geodetic Datum: Gauss-Boaga Fusu W
² Maximum CPTU Tip (MPa): 75

FENCE DIAGRAM

Figure 4E Cross Section C-B' with CPT Results

| | | | |
|-------------------------------------------|-------------------|----------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Line Number: E'-B | Coordinates ¹ of Baseline: |  |
| Project Name: Genoa Port (PFTE) | | Start of Baseline: 1493409mE 4914971mN | |
| Project No.: GMOP20-G-013 | | End of Baseline: 1494567mE 4914659mN | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W
² Maximum CPTU Tip (MPa): 75

FENCE DIAGRAM

Figure 4F Cross Section C-E-B'' with CPT Results

| | | | |
|-------------------------------------------|--------------------|----------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Line Number: C-E-B | Coordinates ¹ of Baseline: |  |
| Project Name: Genoa Port (PFTE) | | Start of Baseline: 1492779mE 4915804mN | |
| Project No.: GMOP20-G-013 | | End of Baseline: 1494529mE 4914674mN | |



¹ Local Geodetic Datum: Gauss-Boaga Fuso W
² Maximum CPTU Tip (MPa): 75

FENCE DIAGRAM

TABLES

Table 1 Borehole Summary

| Location ID | Target | | Actual | | Depth (m) | Water Depth | |
|-------------------------------------------------|-------------|------------|------------|-------------|-----------|---------------------|------------------|
| | Easting | Northing | Easting | Northing | | Drillstring LAT (m) | Echo Sounder (m) |
| CC-1 | 49146575.28 | 1494466.30 | 1494465.74 | 49146575.37 | 16.20 | 54.56 | 53.69 |
| CC-2 | 1493639.00 | 4915593.00 | 1493639.29 | 4915594.01 | 40.40 | 29.76 | 29.00 |
| CC-3 | 1493367.00 | 4915272.00 | 1493366.57 | 4915273.48 | 46.15 | 42.30 | 42.00 |
| CC-4 | 1492614.00 | 4915142.00 | 1492614.56 | 4915142.05 | 80.36 | 52.46 | 52.6 |
| CC-5 | 1491957.00 | 4915903.00 | 1491957.9 | 4915902.97 | 22.95 | 25.87 | 25.00 |
| CC-6 | 1491091.00 | 4916168.00 | 1491089.76 | 4916168.30 | 47.90 | 28.86 | 28.00 |
| CC-7 | 1490921.00 | 4915539.00 | 1490921.21 | 4915539.58 | 42.38 | 52.36 | 52.20 |
| PCPT-1 | 1494402.16 | 4915164.12 | 1494401.45 | 4915165.63 | 25.00 | 36.46 | 35.50 |
| PCPT-2 | 1493464.00 | 4914951.00 | 1493463.58 | 4914952.56 | 41.86 | 52.66 | 52.27 |
| PCPT-3 | 1493382.00 | 4915272.00 | 1493381.68 | 4915273.18 | 34.30 | 42.01 | 41.92 |
| PCPT-4 | 1492629.00 | 4915142.00 | 1492628.33 | 4915143.62 | 42.52 | 52.48 | 51.45 |
| PCPT-5 | 1492799.00 | 4915773.00 | 1492799.06 | 4915774.54 | 42.32 | 30.96 | 30.20 |
| PCPT-6 | 1490971.00 | 4915539.00 | 1490970.95 | 49155347.5 | 47.25 | 50.31 | 50.10 |
| PCPT-6A | 1490972.73 | 4915540.49 | 1490972.65 | 49155340.08 | 81.28 | 50.43 | 50.40 |
| PCPT-7 | 1491771.00 | 4915317.00 | 1491770.27 | 4915316.78 | 10.85 | 52.56 | 51.60 |
| PCPT-8 | 1493948.14 | 4914839.86 | 1493948.25 | 4914839.38 | 4.30 | 54.26 | 54.40 |
| PCPT-8A | 1493946.81 | 4914843.01 | 1493946.67 | 4914843.08 | 65.05 | 52.06 | 52.20 |
| NOTE | | | | | | | |
| 1 Coordinates displayed in local datum, Table 3 | | | | | | | |

Table 2A Generalised Stratigraphy (CC-1)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 0.00 | 0.40 | Extremely low strength black (GLE Y1 N 2.5/) sandy CLAY with frequent shell fragments and occasional organic matter | L1A |
| 0.40 | 3.00 | Extremely low to very low strength very dark grey (GLE Y1 N 3/) becoming dark greenish grey (GLE Y1 10Y 4/1) sandy CLAY with occasional shell fragments | L1A |
| 3.00 | 8.50 | Very dark greenish grey (GLE Y1 10Y 3/1) becoming very dark grey (GLE Y1 N 3/) silty fine to medium SAND with rare fibrous organic matter and medium sand-sized shell fragments and shells | S1A |
| 8.50 | 10.25 | Dark grey (5Y 4/1) to very dark grey (5Y 3/1) fine to coarse angular clayey GRAVEL of fine to coarse grained sandstone and marlstone with occasional calcite veins, with oxidation staining | FG |
| 10.25 | 16.20 | Strong black (5Y 2.5/1) MARLSTONE with occasional veins and pockets (0.5-15.0mm) of calcite, with rare dark yellowish brown (10YR 4/6) areas of surface staining, weathered | F |

Table 2B Generalised Stratigraphy (CC-2)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|----------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 0.00 | 2.60 | Very dark grey (GLE Y 1 N 3/) fine SAND with occasional shell fragments, rare widely spaced thin to medium beds of medium to high strength clay and rare angular fine to medium gravel | S1A |
| 2.60 | 4.85 | Very low to low strength very dark greenish grey (GLE Y 1 10Y 3/1) sandy SILT with rare angular fine to medium gravel. From 4.45 m - with occasional gravel | Ch1 |
| 4.85 | 9.70 | Very low to low strength very dark greenish grey (GLE Y 1 10Y 3/1) silty CLAY with rare shell fragments, rare angular fine to coarse gravel | L1A |
| 9.70 | 13.00 | Low to medium strength very dark greenish grey (GLE Y 1 10Y 3/1) sandy CLAY with rare shells and shell fragments and rare closely spaced thin laminations and pockets (<10mm) of fibrous organic matter | L1B |
| 13.00 | 19.00 | Low to medium strength very dark greenish grey (GLE Y 1 10Y 3/1) clayey SILT with rare pockets (2-4mm) of fine sand, rare pockets (<2mm) of organic matter and rare shell fragments | Ch1 |
| 19.00 | 24.00 | Very dark greenish grey (GLE Y 1 10Y 3/1) silty fine SAND with rare shell fragments, rare mica and rare pockets (<10mm) of organic matter | S1A |
| 24.00 | 28.10 | Very dark greenish grey (GLE Y 1 10Y 3/1) fine SAND with rare shells and shell fragments and rare mica | S1A |
| 28.10 | 31.50 | High to very high strength very dark grey (5Y 3/1) sandy CLAY with frequent extremely closely to very closely spaced thin to thick laminations of black (5Y 2.5/1) medium to coarse sand, frequent shell fragments and rare subrounded fine gravel | L2 |
| 31.50 | 40.40 | Black (GLE Y 1 N 2.5/) medium to coarse SAND with occasional pockets (10-50mm) of very dark greenish grey firm clay, occasional subangular to subrounded fine to medium gravel and rare shells and shell fragments | S1B |

Table 2C Generalised Stratigraphy (CC-3)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 0.00 | 0.50 | Dark grey (GLE Y1 N 4/1) silty CLAY with rare gravel. Gravel is angular fine to medium | L1A |
| 0.50 | 1.65 | Dark grey (GLE Y1 N 4/1) MADE GROUND (silty fine to medium SAND) with rare gravel, rare pockets of decayed wood, rare textile material (clothes and threads) and rare shell fragments. Gravel is angular fine to coarse | MG |
| 1.65 | 7.00 | Extremely low to very low strength very dark greenish grey (GLE Y1 5GY 3/1) silty CLAY with frequent pockets of decayed wood and organic matter, rare shell fragments | L1A |
| 7.00 | 12.90 | Low to medium strength very dark greenish grey (GLE Y1 5GY 3/1) silty CLAY with frequent shell fragments and rare pockets of organic matter | L1B |
| 12.90 | 22.05 | Greenish black (GLE Y1 10Y 2.5/1) silty fine to medium SAND with frequent mica and occasional shell fragments | S1A |
| 22.05 | 46.15 | Very dark grey (GLE Y1 10Y 3/1), olive (5Y 5/4) and greenish grey (GLE Y1 10Y 6/1) angular to rounded fine to coarse GRAVEL with rare sand and rare clay. Sand is medium to coarse | G |

Table 2D Generalised Stratigraphy (CC-4)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|----------------|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 0.00 | 1.75 | Extremely low strength very dark greenish grey (GLEY 1 5GY 3/1) sandy CLAY with rare fibrous organic matter and decayed wood, and rare shell fragments | L1A |
| 1.75 | 6.90 | Extremely low to low strength very dark greenish grey (GLEY 1 5GY 3/1) CLAY with rare pockets of fibrous organic material, rare shell fragments and rare pockets and extremely closely spaced thin laminations of sandy clay | L1A |
| 6.90 | 7.90 | Low strength very dark greenish grey (GLEY 1 10Y 3/1) sandy CLAY with intact shells | L1A |
| 7.90 | 16.70 | Medium dense very dark grey (GLEY 1 N 3/) silty fine SAND with rare mica and rare shell fragments | S1A |
| 16.70 | 19.75 | Loose to medium dense very dark grey (GLEY 1 N 3/) fine to medium SAND with rare rounded fine gravel | S1A |
| 19.75 | 37.00 | High to very high strength greenish grey (GLEY 1 10Y 5/1) CLAY with occasional shell fragments | L2 |
| 37.00 | 45.00 | High to very high strength dark olive grey (5Y 3/2) CLAY with occasional closely spaced thin laminations of silty fine sand and rare shell fragments | L2 |
| 45.00 | 54.30 | Very high to extremely high strength dark olive grey (5Y 3/2) CLAY with rare shell fragments | A |
| 54.30 | 64.00 | Extremely high strength olive grey (5Y 4/2) CLAY with rare shell fragments and rare mica | A |
| 64.00 | 80.36 | Extremely high strength olive grey (5Y 4/2) CLAY with rare shell fragments and rare pockets of yellowish red silt | A |

Table 2E Generalised Stratigraphy (CC-5)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 0.00 | 2.00 | Very dark grey (GLEY 1 N 3/) fine SAND with rare shell fragments and rare fibrous organic material | S1A |
| 2.00 | 12.00 | Very dark grey (GLEY 1 N 3/) silty fine SAND with rare shells and shell fragments and rare mica | S1A |
| 12.00 | 13.00 | Very dark grey (GLEY 1 N 3/) clayey fine to medium SAND with rare shells and shell fragments, rare pockets of fibrous organic matter and wood fragments, and rare mica | S1A |
| 13.00 | 15.00 | Dark grey (GLEY 1 N 4/1) silty coarse SAND with occasional subrounded fine gravel, occasional shell fragments and rare fibrous organic matter | S1A |
| 15.00 | 22.95 | Very weak to weak dark grey (GLEY 1 N 4/) fissured weathered CLAYSTONE with occasional closely to medium spaced thin to medium beds of strong black marlstone, occasional calcite pockets and occasional closely spaced thin laminations of clay. RMR=15; GSI=25 ; FI=7-10 | MR |

Table 2F Generalised Stratigraphy (CC-6)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|----------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 0.00 | 2.80 | Low to medium strength very dark grey (GLEY 1 N 3/) sandy CLAY with rare shell fragments and rare organic material. Sand is fine | L1B |
| 2.80 | 3.90 | Very loose to loose silty SAND | S1A |
| 3.90 | 6.20 | Medium to high strength sandy SILT with occasional closely spaced thin beds of silty sand | Ch1 |
| 6.20 | 8.80 | Loose very dark grey (GLEY 1 N 3/) silty fine SAND with rare shell fragments | S1A |
| 8.80 | 11.10 | Low to medium strength very dark grey (GLEY 1 N 3/) sandy SILT with rare shells and shell fragments. Sand is fine | Ch1 |
| 11.10 | 23.40 | Loose to medium dense very dark grey (GLEY 1 N 3/) silty fine SAND with rare shell fragments and rare mica | S1A |
| 23.40 | 24.60 | Dense to very dense dark grey (GLEY 1 N 4/) gravelly medium to coarse SAND. Gravel is subangular to rounded fine to coarse | S1A |
| 24.60 | 40.50 | Very high to extremely high strength greenish grey (GLEY 1 10Y 5/1) CLAY with rare dark grey fine sand and rare shell fragments | L2 |
| 40.50 | 44.80 | Extremely high strength greenish grey (GLEY 1 10Y 5/1) CLAY with rare pockets of shell fragments | A |
| 44.80 | 47.90 | Extremely high strength greenish grey (GLEY 1 5G_ /1 6/1) CLAY with rare fine sand, rare pockets of black fine sand and rare shell fragments | A |

Table 2G Generalised Stratigraphy (CC-7)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|----------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 0.00 | 0.75 | Extremely low strength dark greenish grey (GLEY 1 10Y 4/1) CLAY with rare shells and shell fragments | L1A |
| 0.75 | 4.45 | Extremely low strength dark greenish grey (GLEY 1 10Y 4/1) CLAY with rare shells and shell fragments and rare pockets of fibrous organic material | L1A |
| 4.45 | 7.00 | Dark greenish grey (GLEY 1 4/1) silty fine SAND with occasional shells and shell fragments, rare pockets of fibrous organic matter and wood fragments | S1A |
| 7.00 | 9.00 | Light grey (GLEY 1 N 7/), dark greenish grey (GLEY 1 10Y 4/1) and dark grey (2.5Y 4/1) sandy silty subrounded fine to coarse GRAVEL with rare shell fragments. Sand is fine | G |
| 9.00 | 11.00 | Medium to high strength olive grey (5Y 5/2) CLAY with rare shell fragments | L2 |
| 11.00 | 24.00 | High to very high strength olive grey (5Y 4/2) CLAY with rare shell fragments | L2 |
| 24.00 | 28.00 | Very high strength greenish grey (GLEY 1 5GY 5/1) CLAY with occasional extremely closely spaced thin laminations of silt and rare shell fragments | L2 |
| 28.00 | 29.60 | Very high strength greenish grey (GLEY 1 5GY 5/1) CLAY with rare pockets of organic matter, rare extremely closely spaced thin laminations of silt | L2 |
| 29.60 | 32.00 | Interbedded very high to extremely high strength dark greenish grey (GLEY 1 10Y 4/1) sandy CLAY with occasional closely spaced thin to thick laminations of dark grey fine sand and dark greenish grey (GLEY 1 10Y 4/1) clayey SAND with frequent extremely closely to very closely spaced thin laminations of clay | A |
| 32.00 | 33.00 | Extremely high strength dark greenish grey (GLEY 1 10Y 4/1) CLAY with occasional closely spaced thin laminations and pockets of fine sand, and occasional pockets of organic matter | A |
| 33.00 | 38.20 | Very high to extremely high strength dark greenish grey (GLEY 1 10Y 4/1) CLAY with rare shell fragments | A |
| 38.20 | 39.70 | Medium to high strength dark greenish grey (GLEY 1 10Y 4/1) CLAY with occasional subrounded fine gravel and rare pockets of shell fragments | A |
| 39.70 | 42.38 | Very high to extremely high strength CLAY | A |

Table 2H Generalised Stratigraphy (PCPT-1)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 0.00 | 1.10 | Low strength sandy CLAY | L1B |
| 1.10 | 5.75 | Extremely low strength CLAY with occasional closely to medium spaced very thin to thin beds of clayey sand | L1A |
| 5.75 | 9.70 | Interbedded very low to low strength CLAY and clayey SAND | L1B |
| 9.70 | 11.05 | Very loose to loose silty SAND with very thin beds of clay | S1A |
| 11.05 | 17.20 | Loose SAND | S1A |
| 17.20 | 25.00 | Medium strong to strong black (5Y 2.5/1) and brown (7.5YR 4/6) weathered fine grained MARLSTONE with occasional thin laminations and pockets of calcite. RMR=12-13, GIS=20-35, FI=2-6 | F |

Table 21 Generalised Stratigraphy (PCPT-2)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|-----------------------------------------------------------------------------|------------------------|
| 0.00 | 3.20 | Extremely low strength CLAY with rare medium spaced thin beds of silty sand | L1A |
| 3.20 | 7.15 | Extremely low to very low strength CLAY | L1A |
| 7.15 | 15.90 | Medium dense SAND | S1A |
| 15.90 | 19.60 | Very dense SAND | S1B |
| 19.60 | 41.86 | High to very high strength CLAY | L2 |

Table 2J Generalised Stratigraphy (PCPT-3)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|------------------------------------------------------------------------------------------|------------------------|
| 0.00 | 0.50 | Extremely low strength CLAY | L1A |
| 0.50 | 1.60 | Loose gravelly SAND | S1A |
| 1.60 | 13.30 | Extremely low to very low strength CLAY with rare medium spaced thin beds of clayey sand | L1A |
| 13.30 | 22.05 | Medium dense SAND | S1A |
| 22.05 | 34.30 | Very dense SAND | S1B |

Table 2K Generalised Stratigraphy (PCPT-4)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|-------------------------------------------------------------------------------------------------|------------------------|
| 0.00 | 1.70 | Extremely low strength CLAY with rare closely spaced very thin beds of clayey sand | L1A |
| 1.70 | 5.00 | Very low strength CLAY with rare medium spaced thin to medium beds of clayey sand | L1A |
| 5.00 | 7.85 | Extremely to very low strength CLAY with rare medium to widely spaced thin beds of clayey sand | L1A |
| 7.85 | 16.70 | Medium dense SAND | S1A |
| 16.70 | 20.90 | Loose to medium dense SAND with rare closely to medium spaced thin to medium beds of sandy clay | S1A |
| 20.90 | 22.70 | High to very high strength CLAY | L2 |
| 22.70 | 25.10 | Very high strength CLAY | L2 |
| 25.10 | 42.52 | Very high to extremely high strength CLAY | L2 |

Table 2L Generalised Stratigraphy (PCPT-5)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|-----------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------|------------------------|
| 0.00 | 1.00 | Medium dense SAND | S1A |
| 1.00 | 4.00 | Very low to low strength CLAY with rare closely to medium spaced very thin to thin beds of sandy clay | L1A |
| 4.00 | 15.00 | Low to medium strength CLAY with occasional medium spaced thin to medium beds of sandy clay | L1B |
| 15.00 | 19.00 | Low to medium strength CLAY | L1B |
| 19.00 | 28.50 | Loose to medium dense SAND | S1A |
| 28.50 | 33.00 | Very high strength CLAY | L2 |
| 33.00 | 40.30 | Very high to extremely high strength greenish grey (GLEY1 10Y 5/1) silty CLAY with rare pockets of dark grey staining | L2 |
| 40.30 | 42.32 | Extremely high strength CLAY | L2 |

Table 2M Generalised Stratigraphy (PCPT-6 & 6A)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|----------------|--------------|---------------------------------------------------------------------------------------------------------------------------|-----------------|
| 0.00 | 5.25 | Extremely low to very low strength CLAY with rare closely to medium spaced thin to medium beds of sandy clay | L1A |
| 5.25 | 8.35 | Loose to medium dense SAND | S1A |
| 8.35 | 9.15 | Very low to low strength CLAY | L1A |
| 9.15 | 10.40 | Medium dense SAND | S1A |
| 10.40 | 12.00 | High to very high strength CLAY | L2 |
| 12.00 | 21.00 | Very high strength CLAY | L2 |
| 21.00 | 23.05 | Very high strength CLAY with rare medium spaced thin beds of sandy clay | L2 |
| 23.05 | 27.15 | Very high strength CLAY | L2 |
| 27.15 | 30.00 | Very high to extremely high strength CLAY | A |
| 30.00 | 40.50 | Extremely high strength dark greenish grey (GLEY 1 10Y 4/1) CLAY | A |
| 40.50 | 43.50 | Very high strength to extremely high strength CLAY | A |
| 43.50 | 63.00 | Extremely high strength dark greenish grey (GLEY 1 10Y 4/1) CLAY with rare shell fragments and rare pockets of black silt | A |
| 63.00 | 81.28 | Extremely high strength dark greenish grey (GLEY 1 10Y4/1) CLAY with rare shell fragments and rare pockets of black silt | A |

Table 2N Generalised Stratigraphy (PCPT-7)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|----------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 0.00 | 2.70 | Very low strength CLAY with occasional closely to medium spaced thin beds of sandy clay | L1A |
| 2.70 | 4.40 | Medium dense SAND | S1A |
| 4.40 | 5.40 | Medium dense GRAVEL | G |
| 5.40 | 9.30 | Very dense light grey (GLE Y1 N 7/) to dark grey (GLE Y1 N 3/) clayey angular fine to coarse GRAVEL with subangular cobbles | G |
| 9.30 | 10.40 | Weak to medium strong grey (GLE Y1 N 6/) to greenish grey (GLE Y1 5GY 5/1) fine grained MARLSTONE. Discontinuities 50 to 80 deg, very closely to medium spaced, planar to stepped, infilled with clay, rarely stained dark greenish grey. RMR=51, GSI=60, FI=3 | F |
| 10.40 | 10.85 | Extremely weak thinly laminated weathered fine grained grey (GLE Y1 N 5/) to dark grey (GLE Y 1 N4/) MUDSTONE. RMR=N/A, GSI=10, FI=N/A | MR |

Table 20 Generalised Stratigraphy (PCPT-8 & 8A)

| Depth from (m) | Depth to (m) | Description | Geological Unit |
|----------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 0.00 | 6.20 | Extremely low to very low strength very dark greenish grey (GLEY 1 10Y 3/1) CLAY with occasional angular fine to medium gravel and rare pockets of fibrous organic matter and wood fragments | L1A |
| 6.20 | 9.50 | Loose dark grey (GLEY 1 N 4/) silty fine SAND with rare shell fragments and rare mica | S1A |
| 9.50 | 14.00 | Loose to medium dense SAND with rare medium spaced thin to medium beds of sandy clay | S1A |
| 14.00 | 16.50 | High to very high strength dark grey (GLEY 1 N 4/) CLAY with occasional pockets of fine to coarse sand and rare shell fragments | L2 |
| 16.50 | 19.50 | High strength dark grey (GLEY 1 N 4/) CLAY with rare shell fragments | L2 |
| 19.50 | 20.95 | Very high strength gravelly CLAY | L2 |
| 20.95 | 29.10 | High to very high strength dark grey (GLEY 1 N 4/) CLAY with rare shell fragments, rare rounded fine gravel and rare pockets and widely spaced thin laminations and beds of silty sand | L2 |
| 29.10 | 33.00 | Dense dark greyish brown (2.5Y 4/2) to light olive brown (2.5Y 5/3) clayey gravelly fine to coarse SAND. Gravel is grey to black subangular to rounded fine to coarse | S1B |
| 33.00 | 37.00 | Very dense black (GLEY 1 N 2.5/) to greyish brown (2.5Y 4/2) angular to subrounded fine to coarse GRAVEL of marlstone with rare thin laminations of calcite and rare light brown clay | FG |
| 37.00 | 42.00 | Dense to very dense very dark greyish brown (2.5Y 3/2) fine to coarse SAND with rare pockets of light brown clay and rare subrounded fine to medium gravel | S1B |
| 42.00 | 65.05 | Dense to very dense black (2.5Y 2.5/1) subrounded coarse GRAVEL of marlstone with occasional cobbles and occasional pockets of calcite | FG |

Table 3

| Working Spheroid | |
|---------------------------------|--------------|
| Datum: | Roma 40 |
| Spheroid: | WGS84 |
| Semi-major, a: | 6378388 |
| Semi-minor, b: | TBC |
| Inverse flattening, 1/f: | 297.00000000 |

Project Geodetics

| Working Projection | |
|----------------------------|---------------------|
| Grid: | UTM 32N |
| Projection Type: | Transverse Mercator |
| Zone: | 32N |
| Central Meridian: | 09° 00'00.00" |
| Latitude Origin: | 00° 00'00.00" |
| Grid Easting: | 1500000.00 |
| Grid Northing: | 0.00 |
| Scale Factor on CM: | 0.9996 |
| Units: | Meter |

Table 4 Fence Diagram Coordinates

| Location ID | Easting | Northing |
|--------------------|----------------|-----------------|
| A' | 1491089.76 | 4916168.30 |
| A'' | 1494401.45 | 4915165.63 |
| B' | 1490921.21 | 4915539.58 |
| B'' | 1494465.74 | 4914675.37 |
| C | 1492799.06 | 4915774.54 |
| D | 1492628.33 | 4915143.62 |
| E | 1493463.58 | 4914952.56 |

NOTE

- 1 Coordinates displayed in local datum, Table 3
- 2 Water depths reduced to LAT and recorded at commencement of borehole

APPENDIX A IN SITU TEST RESULTS

Appendix A.1

Borehole Log Legend

Genoa Port Extension Geotechnical Survey (PFTE)



Client: TECHNITAL S.p.A and Modimar S.r.l

Project Number:
GMOP20-G-013

Report Reference:
GMOP20-G-013-FAC-01

Samples and Tests



Soil Sample

In Situ PCPT

Core Run

Sampling/Testing Method

PS/P Push/piston with Shelby Tube


H Hammer

CR Core Run


C PCPT

All lengths of sample or test represent actual recovery or tested depth range


Legend of Soil Types




CLAY




SILT



SAND




GRAVEL



PEAT




MUDSTONE



SILTSTONE




SANDSTONE



LIMESTONE / CALCAREOUS /
CARBONATE ROCKS

Rock Core Recovery (based on ASTM Vol 04.08)



| Term | Definition | Strength | UCS(MPa) |
|------|--------------------------------------------------------------------------------|-------------------|-----------|
| TCR | Core Recovered (ΣT) Length Drilled | Very Weak | < 1.25 |
| | | Weak | 1.25 - 5 |
| SCR | Core Recovered at Full Diam. (ΣS) Length Drilled | Moderately Weak | 5 - 12.5 |
| | | Moderately Strong | 12.5 - 50 |
| | | Strong | 50 - 100 |
| RQD | Core Recovered at Full Diam., >0.1m in length (ΣR) Length Drilled | Very Strong | 100 - 200 |
| | | Extremely Strong | > 200 |

Strength of Fine Grained Soils

| Strength | Su(kPa) |
|------------|-----------|
| Very Soft | < 12 |
| Soft | 12 - 25 |
| Firm | 25 - 50 |
| Stiff | 50 - 100 |
| Very Stiff | 100 - 200 |
| Hard | 200 - 400 |
| Very Hard | > 400 |

Relative Density of Coarse Grained Soils (based on Lunne and Chrstoffersen, 1983)

| Density | Relative Density (%) |
|--------------|----------------------|
| Very Loose | < 15 |
| Loose | 15 - 35 |
| Medium Dense | 35 - 65 |
| Dense | 65 - 85 |
| Very Dense | > 85 |

Borehole Log Legend


Appendix A.2


Borehole Logs

| | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-1 Date Commenced: 16/12/2020 Coordinates ¹ : 1494466mE 4914675mN Water Depth ² : 54.56m | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|

| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | FRACTURE STATE RQD / SCR / TCR 25 50 75 | CONE PENETROMETER TEST | | | | POINT LOAD STRENGTH INDEX ⁴ (MPa) ■ Axial ◆ Diametrel ▲ Irregular Lump 2 3 | UNDRAINED SHEAR STRENGTH ⁴ (kPa) | | | | | DENSITY ⁴ (Mg/m ³) | | | CLASSIFICATION ⁴ (%) | | |
|-----------|--------|--------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------------------------------------|--|-----------------------------------------------------|--|---------------------------------------------------------------------------------------------------|---------------------------------------------|-------------------|----------------|-----------------|--------------------|-------------------------------------------|--|--|---------------------------------|--|--|
| | | | | | | Net Cone Resistance q _{net} (MPa) 10 20 30 40 50 60 70 0.375 0.750 1.125 | | Sleeve Friction f _s (MPa) 0.0 0.5 1.0 | | | ▲ Torvane | ● Laboratory Vane | ● Bulk Density | ● Water Content | ◆ Plasticity Index | | | | | | |
| 1 | P01 | | | 00.00m Extremely low strength black (GLE Y1 N 2.5/) sandy CLAY with frequent shell fragments and occasional organic matter | | | | | | | | | | | | | | | | | |
| 2 | P02 | | | 00.40m Extremely low to very low strength very dark grey (GLE Y1 N 3/) becoming dark greenish grey (GLE Y1 10Y 4/1) sandy CLAY with occasional shell fragments | | | | | | | | | | | | | | | | | |
| 3 | P03 | | | 01.60m - with frequent organic matter (poorly decayed plant and wood) | | | | | | | | | | | | | | | | | |
| 4 | P04 | | | 03.00m Very dark greenish grey (GLE Y1 10Y 3/1) becoming very dark grey (GLE Y1 N 3/) silty fine to medium SAND with rare fibrous organic matter and medium sand-sized shell fragments and shells | | | | | | | | | | | | | | | | | |
| 5 | P05 | | | | | | | | | | | | | | | | | | | | |
| 6 | P06 | | | | | | | | | | | | | | | | | | | | |
| 7 | P07 | | | | | | | | | | | | | | | | | | | | |
| 8 | P08 | | | 07.00m to 07.30m - with occasional very closely spaced thin laminations of coarse sand | | | | | | | | | | | | | | | | | |
| 9 | P09 | | | 07.30m to 07.55m - medium bed of black (GLE Y1 N 2.5/) gravelly sand with rare shells and shell fragments. Gravel is subangular fine to medium | | | | | | | | | | | | | | | | | |
| 10 | PU09A | | | | | | | | | | | | | | | | | | | | |
| 10 | PU09B | | | | | | | | | | | | | | | | | | | | |
| 10 | PU10 | | | 08.50m Dark grey (5Y 4/1) to very dark grey (5Y 3/1) fine to coarse angular clayey GRAVEL of fine to coarse grained sandstone and marlstone with occasional calcite veins, with oxidation staining | | | | | | | | | | | | | | | | | |
| 11 | H10A | | | | | | | | | | | | | | | | | | | | |
| 11 | H10B | | | | | | | | | | | | | | | | | | | | |
| 11 | H11 | | | | | | | | | | | | | | | | | | | | |
| 11 | H11A | | | | | | | | | | | | | | | | | | | | |
| 11 | H12 | | | | | | | | | | | | | | | | | | | | |
| 11 | H13 | | | | | | | | | | | | | | | | | | | | |
| 11 | H14 | | | | | | | | | | | | | | | | | | | | |
| 12 | CR14A | | | 10.25m Strong black (5Y 2.5/1) MARLSTONE with occasional veins and pockets (0.5-15.0mm) of calcite, with rare dark yellowish brown (10YR 4/6) areas of surface staining, weathered | | | | | | | | | | | | | | | | | |
| 12 | CR15 | | | | | | | | | | | | | | | | | | | | |
| 13 | CR16 | | | 11.10m to 11.30m - medium bed of strong grey (5Y 6/1) medium grained sandstone with frequent veins of calcite (0.5-15.0mm) | | | | | | | | | | | | | | | | | |
| 13 | CR16A | | | | | | | | | | | | | | | | | | | | |
| 13 | CR17 | | | 11.30m to 11.40m - thin bed of olive grey (5Y 4/3) gravelly clay. Gravel is subangular fine to coarse | | | | | | | | | | | | | | | | | |
| 14 | CR18 | | | | | | | | | | | | | | | | | | | | |
| 15 | CR19 | | | | | | | | | | | | | | | | | | | | |
| 16 | | | | 16.05m to 16.10m - very thin bed of weak very dark grey (5Y 3/1) mudstone | | | | | | | | | | | | | | | | | |
| 17 | | | | End of borehole at 16.20m | | | | | | | | | | | | | | | | | |

¹ : Gauss-Boaga Fuso W ² Water Depth: LAT ³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0 ⁴ Hollow symbols represent offshore results Ref: GMOP20-G-013-FAC-01 Page 1 of 1

| | | | | | |
|---------------------------------|--------------------|----------------------------|------------------------------------------------|-----------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A | Borehole No.: CC-2 | Date Commenced: 18/12/2020 | Coordinates ¹ : 1493639mE 4915594mN | Water Depth ² : 29.76m |  |
| Project Name: Genoa Port (PFTE) | | | | | |
| Project No.: GMOP20-G-013 | | | | | |
| Location: Genoa Port | | | | | |



¹ Local Geodetic Datum: Gauss-Boaga Fusso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

² Water Depth: LAT


| | | |
|-----------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-2 Date Commenced: 18/12/2020 Coordinates ¹ : 1493639mE 4915594mN Water Depth ² : 29.76m | |
|-----------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--|


| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | | UNDRAINED SHEAR STRENGTH ⁴ (kPa) | DENSITY ⁴ (Mg/m ³) | CLASSIFICATION ⁴ (%) |
|-----------|--------|--------------|--------|---------------------------|-------------------------------------|-----------------------------|----------------------------|--------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| | | | | | Net Cone Resistance q_{net} (MPa) | Sleeve Friction f_s (MPa) | Pore Pressure Ratio, B_q | ▲ Torvane ◆ Pocket Penetrometer ● CIU Triaxial Test ● CAU Triaxial Test ● UU Triaxial Test | ● Laboratory Vane ■ DSS ● Bulk Density ◆ Dry Density | ● Water Content ■ Carbonate Content ▲ Fines Content ~ Relative Density ³ |
| | P42 | | | End of borehole at 40.40m | | | | | | |
| 41 | | | | | | | | | | |
| 42 | | | | | | | | | | |
| 43 | | | | | | | | | | |
| 44 | | | | | | | | | | |
| 45 | | | | | | | | | | |
| 46 | | | | | | | | | | |
| 47 | | | | | | | | | | |
| 48 | | | | | | | | | | |
| 49 | | | | | | | | | | |
| 50 | | | | | | | | | | |
| 51 | | | | | | | | | | |
| 52 | | | | | | | | | | |
| 53 | | | | | | | | | | |
| 54 | | | | | | | | | | |
| 55 | | | | | | | | | | |
| 56 | | | | | | | | | | |
| 57 | | | | | | | | | | |
| 58 | | | | | | | | | | |
| 59 | | | | | | | | | | |

¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | | | | |
|---------------------------------|--------------------|----------------------------|------------------------------------------------|----------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A | Borehole No.: CC-3 | Date Commenced: 14/12/2020 | Coordinates ¹ : 1493367mE 4915273mN | Water Depth ² : 42.3m |  |
| Project Name: Genoa Port (PFTE) | | | | | |
| Project No.: GMOP20-G-013 | | | | | |
| Location: Genoa Port | | | | | |



¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results

² Water Depth: LAT

| | | |
|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-3 Date Commenced: 14/12/2020 Coordinates ¹ : 1493367mE 4915273mN Water Depth ² : 42.3m | |
|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|

| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | | UNDRAINED SHEAR STRENGTH ⁴ (kPa) | | | | | DENSITY ⁴ (Mg/m ³) | | | | CLASSIFICATION ⁴ (%) | | | | | | | |
|-----------|-------------------------------------------------------|--------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-----------------------------|----------------------------|---------------------------------------------|-----------------------|---------------------|---------------------|---------------------------|-------------------------------------------|-------|----------------|---------------|---------------------------------|---------------------|-----------------|-----------------|----------------|--------------------|---------------------------------|----|
| | | | | | Net Cone Resistance q_{net} (MPa) | Sleeve Friction f_s (MPa) | Pore Pressure Ratio, B_q | ▲ Torvane | ◆ Pocket Penetrometer | ● CIU Triaxial Test | ● CAU Triaxial Test | ● UU Triaxial Test | ● Laboratory Vane | ■ DSS | ● Bulk Density | ◆ Dry Density | ● Water Content | ■ Carbonate Content | ▲ Fines Content | ◆ Plastic Limit | ◆ Liquid Limit | ◆ Plasticity Index | ~ Relative Density ³ | |
| | | | | | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 20.0 40.0 60.0 80.0 100.0 | | | | | 1.4 | 1.8 | 2.2 | 2.6 | 20 | 40 | 60 | 80 |
| 21 | P21 | | | 20.35m to 20.55m - medium bed of black (GLE Y1 N 2.5/) very gravelly coarse sand. Gravel is subangular to subrounded fine to medium | | | | | | | | | | | | | | | | | | | | |
| 22 | P22 | | | 20.55m - becoming olive grey (5Y 4/2) | | | | | | | | | | | | | | | | | | | | |
| 23 | P23 PU23A PU24 PU24A H24B PU25 H25A | | △ | 21.70m - with occasional very closely spaced thin laminations of calcite, occasional gravel and rare shells. Gravel is subrounded to subangular medium | | | | | | | | | | | | | | | | | | | | |
| 24 | CR25E H26 | | △ | 22.05m Very dark grey (GLE Y1 10Y 3/1), olive (5Y 5/4) and greenish grey (GLE Y1 10Y 6/1) angular to rounded fine to coarse GRAVEL with rare sand and rare clay. Sand is medium to coarse | | | | | | | | | | | | | | | | | | | | |
| 25 | H27 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 26 | H28 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 27 | PU29 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 28 | H30 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 29 | H31 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 30 | H32 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 31 | H33 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 32 | H34 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 33 | H35 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 34 | H36 H36A | | △ | | | | | | | | | | | | | | | | | | | | | |
| 35 | H37 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 36 | H38 PU39 H39A PU40 | | △ | 35.50m to 35.70m - medium bed of olive (5Y 5/4) silty clay with rare thick laminations of yellowish red (5YR 5/6) clay | | | | | | | | | | | | | | | | | | | | |
| 37 | H41 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 38 | H42 H43 PU44 | | △ | | | | | | | | | | | | | | | | | | | | | |
| 39 | H45 H46 | | △ | | | | | | | | | | | | | | | | | | | | | |

¹ Local Geodetic Datum: Gauss-Boaga Fusso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

² Water Depth: LAT

| | | |
|---------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-3 Date Commenced: 14/12/2020 Coordinates¹: 1493367mE 4915273mN Water Depth²: 42.3m |  |
|---------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|


| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | UNDRAINED SHEAR STRENGTH ⁴ (kPa) | DENSITY ⁴ (Mg/m ³) | CLASSIFICATION ⁴ (%) |
|-----------|----------------------------------------|--------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|--------------------------------------|---------------------------------------------|--------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| | | | | | Net Cone Resistance q _{net} (MPa) | Sleeve Friction f _s (MPa) | Pore Pressure Ratio, Bq | ▲ Torvane ◆ Pocket Penetrometer ● CIU Triaxial Test ● CAU Triaxial Test ● UU Triaxial Test | ● Laboratory Vane ■ DSS ● Bulk Density ◆ Dry Density |
| 41 | PU47 PU47A PU48 PU49 PU49A | | △ △ △ | 45.00m to 45.15m - thin bed of olive grey (5Y 5/2) sandy clay with occasional gravel. Gravel is subangular to subrounded fine to medium | | | | | |
| 42 | H49B H50 PU50A | | △ △ △ | | | | | | |
| 43 | | | △ △ △ | | | | | | |
| 44 | | | △ △ △ | | | | | | |
| 45 | PU51A PU51 | | △ △ △ | | | | | | ○ |
| 46 | PU52 | | △ △ △ | End of borehole at 46.15m | | | | | |
| 47 | | | | | | | | | |
| 48 | | | | | | | | | |
| 49 | | | | | | | | | |
| 50 | | | | | | | | | |
| 51 | | | | | | | | | |
| 52 | | | | | | | | | |
| 53 | | | | | | | | | |
| 54 | | | | | | | | | |
| 55 | | | | | | | | | |
| 56 | | | | | | | | | |
| 57 | | | | | | | | | |
| 58 | | | | | | | | | |
| 59 | | | | | | | | | |


¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results

² Water Depth: LAT


| | | | | | | | | | | | |
|---------------|-----------------------------------|---------------|----------------|-----------------|--------------------------|----------------------------|------------------------|------------------------|----------------------------|------------------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | CC-4 PCPT-4 | Date Commenced: | 22/12/2020 17/12/2020 | Coordinates ¹ : | 1492615mE 1492628mE | 4915142mN 4915144mN | Water Depth ² : | 52.46m 52.48m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results


| | | | | | | | | | | | |
|---------------|-----------------------------------|---------------|----------------|-----------------|--------------------------|----------------------------|------------------------|------------------------|----------------------------|------------------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | CC-4 PCPT-4 | Date Commenced: | 22/12/2020 17/12/2020 | Coordinates ¹ : | 1492615mE 1492628mE | 4915142mN 4915144mN | Water Depth ² : | 52.46m 52.48m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results

| | | | | | | | | | | | |
|---------------|-----------------------------------|---------------|----------------|-----------------|--------------------------|----------------------------|------------------------|------------------------|----------------------------|------------------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | CC-4 PCPT-4 | Date Commenced: | 22/12/2020 17/12/2020 | Coordinates ¹ : | 1492615mE 1492628mE | 4915142mN 4915144mN | Water Depth ² : | 52.46m 52.48m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | | |



¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-4 PCPT-4 Date Commenced: 22/12/2020 17/12/2020 Coordinates ¹ : 1492615mE 1492628mE 4915142mN 4915144mN Water Depth ² : 52.46m 52.48m | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|

| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | UNDRAINED SHEAR STRENGTH ⁴ (kPa) | | | | | DENSITY ⁴ (Mg/m ³) | | | | CLASSIFICATION ⁴ (%) | | | | | |
|-----------|--------|--------------|--------|---------------------------|--------------------------------------------|--------------------------------------|---------------------------------------------|-----------|-----------------------|---------------------|---------------------|-------------------------------------------|-------------------|-------|----------------|---------------------------------|-----------------|-----------------|---------------------|----------------|-----------------|
| | | | | | Net Cone Resistance q _{net} (MPa) | Sleeve Friction f _s (MPa) | Pore Pressure Ratio, Bq | ▲ Torvane | ◆ Pocket Penetrometer | ● CIU Triaxial Test | ● CAU Triaxial Test | ● UU Triaxial Test | ● Laboratory Vane | ■ DSS | ● Bulk Density | ◆ Dry Density | ● Water Content | ◆ Plastic Limit | ■ Carbonate Content | ◆ Liquid Limit | ▲ Fines Content |
| 81 | | | | End of borehole at 80.36m | | | | | | | | | | | | | | | | | |
| 82 | | | | | | | | | | | | | | | | | | | | | |
| 83 | | | | | | | | | | | | | | | | | | | | | |
| 84 | | | | | | | | | | | | | | | | | | | | | |
| 85 | | | | | | | | | | | | | | | | | | | | | |
| 86 | | | | | | | | | | | | | | | | | | | | | |
| 87 | | | | | | | | | | | | | | | | | | | | | |
| 88 | | | | | | | | | | | | | | | | | | | | | |
| 89 | | | | | | | | | | | | | | | | | | | | | |
| 90 | | | | | | | | | | | | | | | | | | | | | |
| 91 | | | | | | | | | | | | | | | | | | | | | |
| 92 | | | | | | | | | | | | | | | | | | | | | |
| 93 | | | | | | | | | | | | | | | | | | | | | |
| 94 | | | | | | | | | | | | | | | | | | | | | |
| 95 | | | | | | | | | | | | | | | | | | | | | |
| 96 | | | | | | | | | | | | | | | | | | | | | |
| 97 | | | | | | | | | | | | | | | | | | | | | |
| 98 | | | | | | | | | | | | | | | | | | | | | |
| 99 | | | | | | | | | | | | | | | | | | | | | |

¹ Local Geodetic Datum: Gauss-Boaga Fuso W ³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0 ⁴ Hollow symbols represent offshore results Ref: GMOP20-G-013-FAC-01
 Water Depth: LAT Page 5 of 5

| | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-5 Date Commenced: 30/12/2020 Coordinates ¹ : 1491958mE 4915903mN Water Depth ² : 25.87m | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|

| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | FRACTURE STATE RQD / SCR / TCR 25 50 75 | CONE PENETROMETER TEST | | | | | POINT LOAD STRENGTH INDEX ⁴ (MPa) ■ Axial ◆ Diametrel ▲ Irregular Lump | UNDRAINED SHEAR STRENGTH ⁴ (kPa) ▲ Torvane ◆ Pocket Penetrometer ● Undrained Triaxial Test | DENSITY ⁴ (Mg/m ³) ● Bulk Density ◆ Dry Density | CLASSIFICATION ⁴ (%) ● Water Content ■ Carbonate Content ▲ Fines Content ◆ Plasticity Index Relative Density ³ | |
|-----------|----------------------------------------|--------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|--------------------------------------------------------------------|-----------------------------------------------------------|--|--|--|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| | | | | | | Net Cone Resistance q _{net} (MPa) 10 20 30 40 50 60 70 | Sleeve Friction f _s (MPa) 0.375 0.750 1.125 | | | | | | | | 0.0 0.5 1.0 |
| 1 | P01 | | | 00.00m Very dark grey (GLEY 1 N 3/) fine SAND with rare shell fragments and rare fibrous organic material | | | | | | | | | | | |
| 2 | P02 | | | 01.00m - with rare subangular to subrounded fine to medium gravel and rare fibrous organic matter | | | | | | | | | | | |
| 3 | P03 | | | 02.00m Very dark grey (GLEY 1 N 3/) silty fine SAND with rare shells and shell fragments and rare mica | | | | | | | | | | | |
| 4 | P04 | | | 04.00m to 05.00m - with rare fibrous organic matter | | | | | | | | | | | |
| 5 | P05 | | | | | | | | | | | | | | |
| 6 | P06 | | | | | | | | | | | | | | |
| 7 | P07 | | | | | | | | | | | | | | |
| 8 | P08 | | | 08.00m - becoming very dark greenish grey (GLEY 1 5GY 3/1) 08.00m to 08.55m - fine to medium | | | | | | | | | | | |
| 9 | P09 | | | | | | | | | | | | | | |
| 10 | P10 | | | | | | | | | | | | | | |
| 11 | P11 | | | 12.00m Very dark grey (GLEY 1 N 3/) clayey fine to medium SAND with rare shells and shell fragments, rare pockets of fibrous organic matter and wood fragments, and rare mica | | | | | | | | | | | |
| 12 | P12 | | | | | | | | | | | | | | |
| 13 | P13 | | | 13.00m Dark grey (GLEY 1 N 4/1) silty coarse SAND with occasional subrounded fine gravel, occasional shell fragments and rare fibrous organic matter | | | | | | | | | | | |
| 14 | P14 | | | | | | | | | | | | | | |
| 15 | P15 | | | 15.00m Very weak to weak dark grey (GLEY 1 N 4/) fissured weathered CLAYSTONE with occasional closely to medium spaced thin to medium beds of strong black marlstone, occasional calcite pockets and occasional closely spaced thin laminations of clay. RMR=15; GSI=25 ; FI=7-10 | | | | | | | | | | | |
| 16 | P16 | | | | | | | | | | | | | | |
| 17 | P17 | | | | | | | | | | | | | | |
| 18 | PU18 CR19 | | | | | | | | | | | | | | |
| 19 | PU20 | | | | | | | | | | | | | | |
| 20 | PU21 PU21A H21B CR21C CR22 | | | | | | | | | | | | | | |
| 21 | PU22 | | | | | | | | | | | | | | |
| 22 | PU23 | | | | | | | | | | | | | | |
| 23 | PU24 | | | | | | | | | | | | | | |
| 24 | PU25 CR26 | | | | | | | | | | | | | | |


¹ : Gauss-Boaga Fuso W ³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0 ⁴ Hollow symbols represent offshore results Ref: GMOP20-G-013-FAC-01


² Water Depth: LAT Page 1 of 2

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-5 Date Commenced: 30/12/2020 Coordinates ¹ : 1491958mE 4915903mN Water Depth ² : 25.87m | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--|

| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | FRACTURE STATE RQD / SCR / TCR 25 50 75 | CONE PENETROMETER TEST | | POINT LOAD STRENGTH INDEX ⁴ (MPa) ■ Axial ◆ Diametrel ▲ Irregular Lump | UNDRAINED SHEAR STRENGTH ⁴ (kPa) ▲ Torvane ◆ Pocket Penetrometer ● Undrained Triaxial Test | DENSITY ⁴ (Mg/m ³) ● Bulk Density ◆ Dry Density | CLASSIFICATION ⁴ (%) ● Water Content ■ Carbonate Content ▲ Fines Content ◆ Plasticity Index ◇ Relative Density ³ |
|-----------|--------|--------------|--------|---------------------------|-----------------------------------------------|----------------------------------------------------------------------------------|--------------------------------------------|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | | | | | Net Cone Resistance q_{net} (MPa) 10 20 30 40 50 60 70 0.375 0.750 1.125 | Sleeve Friction f_s (MPa) 0.0 0.5 1.0 | | | | |
| 21 | CR27 | | | | | | | | | | |
| 21 | CR28 | | | | | | | | | | |
| 21 | CR29 | | | | | | | | | | |
| 22 | CR30 | | | | | | | | | | |
| 22 | CR31 | | | | | | | | | | |
| 23 | CR32 | | | | | | | | | | |
| 24 | | | | End of borehole at 22.95m | | | | | | | |
| 25 | | | | | | | | | | | |
| 26 | | | | | | | | | | | |
| 27 | | | | | | | | | | | |
| 28 | | | | | | | | | | | |
| 29 | | | | | | | | | | | |
| 30 | | | | | | | | | | | |
| 31 | | | | | | | | | | | |
| 32 | | | | | | | | | | | |
| 33 | | | | | | | | | | | |
| 34 | | | | | | | | | | | |
| 35 | | | | | | | | | | | |
| 36 | | | | | | | | | | | |
| 37 | | | | | | | | | | | |
| 38 | | | | | | | | | | | |
| 39 | | | | | | | | | | | |

¹ : Gauss-Boaga Fuso W ³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$ ⁴ Hollow symbols represent offshore results Ref: GMOP20-G-013-FAC-01
² Water Depth: LAT Page 2 of 2


| | | | | | | |
|-------------------------------------------------------|--------------------------------------------------------------------------------------|-----------------------|-------------------------------|------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|
| Client: Project Name: Project No.: Location: | TECHNITAL S.p.A and Modimar S.r.l Genoa Port (PFTE) GMOP20-G-013 Genoa Port | Borehole No.: CC-6 | Date Commenced: 25/12/2020 | Coordinates ¹ : 1491090mE 4916168mN | Water Depth ² : 28.86m |  |
|-------------------------------------------------------|--------------------------------------------------------------------------------------|-----------------------|-------------------------------|------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|




¹ Local Geodetic Datum: Gauss-Boaga Fusio W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results


| | | | | | | | | | | |
|---------------|-----------------------------------|---------------|------|-----------------|------------|----------------------------|---------------------|----------------------------|--------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | CC-6 | Date Commenced: | 25/12/2020 | Coordinates ¹ : | 1491090mE 4916168mN | Water Depth ² : | 28.86m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | | | | | | | | | | |
|---------------|-----------------------------------|---------------|------|-----------------|------------|----------------------------|---------------------|----------------------------|--------|-------------------------------------------------------------------------------------|--|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | CC-6 | Date Commenced: | 25/12/2020 | Coordinates ¹ : | 1491090mE 4916168mN | Water Depth ² : | 28.86m |  | |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | | |



¹ Local Geodetic Datum: Gauss-Boaga Fuso W


³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$


⁴ Hollow symbols represent offshore results

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-7 Date Commenced: 20/12/2020 Coordinates ¹ : 1490921mE 4915540mN Water Depth ² : 52.36m | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|--|

| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | UNDRAINED SHEAR STRENGTH (kPa) | DENSITY (Mg/m ³) | CLASSIFICATION (%) |
|-----------|--------|--------------|--------|-------------------------------------------|-------------------------------------|-----------------------------|--------------------------------|--------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| | | | | | Net Cone Resistance q_{net} (MPa) | Sleeve Friction f_s (MPa) | Pore Pressure Ratio, Bq | ● Torvane ◆ Pocket Penetrometer ● CIU Triaxial Test ● CAU Triaxial Test ● UU Triaxial Test | ● Laboratory Vane ◆ DSS S _u from q _{net} . For N _u values please see the report |
| 39.70m | | | | Very high to extremely high strength CLAY | | | | | |
| 40.80m | | | A | - dissipation test | | | | | |
| 41.70m | | | | - dissipation test | | | | | |
| 42.38m | | | | End of borehole at 42.38m | | | | | |
| 43 | | | | | | | | | |
| 44 | | | | | | | | | |
| 45 | | | | | | | | | |
| 46 | | | | | | | | | |
| 47 | | | | | | | | | |
| 48 | | | | | | | | | |
| 49 | | | | | | | | | |
| 50 | | | | | | | | | |
| 51 | | | | | | | | | |
| 52 | | | | | | | | | |
| 53 | | | | | | | | | |
| 54 | | | | | | | | | |
| 55 | | | | | | | | | |
| 56 | | | | | | | | | |
| 57 | | | | | | | | | |
| 58 | | | | | | | | | |
| 59 | | | | | | | | | |

¹ Local Geodetic Datum: Gauss-Boaga Fuso W ³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0 ⁴ Hollow symbols represent offshore results Ref: GMOP20-G-013-FAC-01
 Water Depth: LAT Page 3 of 3

| | | | | | | | | | | |
|---------------|-----------------------------------|---------------|--------|-----------------|------------|----------------------------|------------------------|----------------------------|--------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | PCPT-1 | Date Commenced: | 17/12/2020 | Coordinates ¹ : | 1494401mE 4915166mN | Water Depth ² : | 36.46m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | |



¹ : Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

² Water Depth: LAT

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: PCPT-1 Date Commenced: 17/12/2020 Coordinates ¹ : 1494401mE 4915166mN Water Depth ² : 36.46m | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--|


| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | FRACTURE STATE RQD / SCR / TCR 25 50 75 | CONE PENETROMETER TEST | | POINT LOAD STRENGTH INDEX ⁴ (MPa) ■ Axial ◆ Diametrel ▲ Irregular Lump 2 3 | UNDRAINED SHEAR STRENGTH ⁴ (kPa) ▲ Torvane ◆ Pocket Penetrometer ● Undrained Triaxial Test ● Laboratory Vane ◆ CIU Triaxial S _v from q _{net} For N _s values please see the report | DENSITY ⁴ (Mg/m ³) ● Bulk Density ◆ Dry Density | CLASSIFICATION ⁴ (%) ● Water Content ■ Carbonate Content ▲ Fines Content ◆ Plasticity Index Relative Density ³ |
|-----------|--------|--------------|--------|----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------------------|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| | | | | | | Net Cone Resistance q _{net} (MPa) 10 20 30 40 50 60 70 0.375 0.750 1.125 | Sleeve Friction f _s (MPa) 0.0 0.5 1.0 | | | | |
| 21 | CR10 | | | 21.30m to 21.50m - medium bed of (10YR 5/3) thinly laminated clay | | | | | | | |
| 22 | CR11 | | | | | | | | | | |
| 23 | CR12 | | | | | | | | | | |
| 24 | CR13 | | | 24.00m to 24.20m - medium bed of dark grey (2.5Y 4/1) clay with occasional gravel of marlstone. Gravel is angular fine to coarse | | | | | | | |
| 25 | CR14 | | | | | | | | | | |
| 25 | | | | End of borehole at 25.00m | | | | | | | |
| 26 | | | | | | | | | | | |
| 27 | | | | | | | | | | | |
| 28 | | | | | | | | | | | |
| 29 | | | | | | | | | | | |
| 30 | | | | | | | | | | | |
| 31 | | | | | | | | | | | |
| 32 | | | | | | | | | | | |
| 33 | | | | | | | | | | | |
| 34 | | | | | | | | | | | |
| 35 | | | | | | | | | | | |
| 36 | | | | | | | | | | | |
| 37 | | | | | | | | | | | |
| 38 | | | | | | | | | | | |
| 39 | | | | | | | | | | | |


¹ : Gauss-Boaga Fuso W

² Water Depth: LAT

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results


| | | | | | | | | | | |
|---------------|-----------------------------------|---------------|--------|-----------------|------------|----------------------------|---------------------|----------------------------|--------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | PCPT-2 | Date Commenced: | 12/12/2020 | Coordinates ¹ : | 1493464mE 4914953mN | Water Depth ² : | 52.66m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | |



¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: PCPT-2 Date Commenced: 12/12/2020 Coordinates ¹ : 1493464mE 4914953mN Water Depth ² : 52.66m |  |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|


| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | UNDRAINED SHEAR STRENGTH (kPa) | | | | | DENSITY (Mg/m ³) | | | | CLASSIFICATION (%) | | | | | | |
|-----------|--------|--------------|--------|---------------------------|--------------------------------------------|--------------------------------------|--------------------------------|------------------------------|---------------------|-------------------|-------------------|------------------------------|-----------------|-----------------|----------------------------------------------------------------------------------------|--------------------|-------------|---------------|---------------|-------------------|---------------|--------------|
| | | | | | Net Cone Resistance q _{net} (MPa) | Sleeve Friction f _s (MPa) | Pore Pressure Ratio, Bq | Torvane | Pocket Penetrometer | CIU Triaxial Test | CAU Triaxial Test | UU Triaxial Test | Laboratory Vane | DSS | S _w from q _{net} . For N _v values please see the report | Bulk Density | Dry Density | Water Content | Plastic Limit | Carbonate Content | Fines Content | Liquid Limit |
| | | | | | 10 20 30 40 50 60 70 | 0.375 0.750 1.125 | -0.4 0.4 1.2 | 50.0 100.0 150.0 200.0 250.0 | | | | | | 1.4 1.8 2.2 2.6 | | | | | | | 20 40 60 80 | |
| 41 | | | C16 | | | | | | | | | | | | | | | | | | | |
| 42 | | | | End of borehole at 41.86m | | | | | | | | | | | | | | | | | | |
| 43 | | | | | | | | | | | | | | | | | | | | | | |
| 44 | | | | | | | | | | | | | | | | | | | | | | |
| 45 | | | | | | | | | | | | | | | | | | | | | | |
| 46 | | | | | | | | | | | | | | | | | | | | | | |
| 47 | | | | | | | | | | | | | | | | | | | | | | |
| 48 | | | | | | | | | | | | | | | | | | | | | | |
| 49 | | | | | | | | | | | | | | | | | | | | | | |
| 50 | | | | | | | | | | | | | | | | | | | | | | |
| 51 | | | | | | | | | | | | | | | | | | | | | | |
| 52 | | | | | | | | | | | | | | | | | | | | | | |
| 53 | | | | | | | | | | | | | | | | | | | | | | |
| 54 | | | | | | | | | | | | | | | | | | | | | | |
| 55 | | | | | | | | | | | | | | | | | | | | | | |
| 56 | | | | | | | | | | | | | | | | | | | | | | |
| 57 | | | | | | | | | | | | | | | | | | | | | | |
| 58 | | | | | | | | | | | | | | | | | | | | | | |
| 59 | | | | | | | | | | | | | | | | | | | | | | |

¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: PCPT-3 Date Commenced: 13/12/2020 Coordinates ¹ : 1493382mE 4915273mN Water Depth ² : 42.01m | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results


| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: PCPT-3 Date Commenced: 13/12/2020 Coordinates ¹ : 1493382mE 4915273mN Water Depth ² : 42.01m | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: PCPT-5 Date Commenced: 15/12/2020 Coordinates ¹ : 1492799mE 4915775mN Water Depth ² : 30.96m |  |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results


| | | | | | | |
|-------------------------------------------------------|--------------------------------------------------------------------------------------|-------------------------|-------------------------------|---------------------------------------------------|--------------------------------------|--|
| Client: Project Name: Project No.: Location: | TECHNITAL S.p.A and Modimar S.r.l Genoa Port (PFTE) GMOP20-G-013 Genoa Port | Borehole No.: PCPT-5 | Date Commenced: 15/12/2020 | Coordinates ¹ : 1492799mE 4915775mN | Water Depth ² : 30.96m | |
|-------------------------------------------------------|--------------------------------------------------------------------------------------|-------------------------|-------------------------------|---------------------------------------------------|--------------------------------------|--|



¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results

| | | | | | | |
|-------------------------------------------------------|--------------------------------------------------------------------------------------|-------------------------|-------------------------------|------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|
| Client: Project Name: Project No.: Location: | TECHNITAL S.p.A and Modimar S.r.l Genoa Port (PFTE) GMOP20-G-013 Genoa Port | Borehole No.: PCPT-5 | Date Commenced: 15/12/2020 | Coordinates ¹ : 1492799mE 4915775mN | Water Depth ² : 30.96m |  |
|-------------------------------------------------------|--------------------------------------------------------------------------------------|-------------------------|-------------------------------|------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|


| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | UNDRAINED SHEAR STRENGTH (kPa) | DENSITY (Mg/m ³) | CLASSIFICATION (%) |
|-----------|--------|--------------|--------|-------------------------------------|-------------------------------------|-----------------------------|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| | | | | | Net Cone Resistance q_{net} (MPa) | Sleeve Friction f_s (MPa) | Pore Pressure Ratio, Bq | <ul style="list-style-type: none"> ▲ Torvane ◆ Pocket Penetrometer ● CIU Triaxial Test ● CAU Triaxial Test ● UU Triaxial Test ● Laboratory Vane ◆ DSS ○ S_u from q_{net}. For N_c values please see the report | <ul style="list-style-type: none"> ● Bulk Density ◆ Dry Density |
| 41 | | | L2 | 40.30m Extremely high strength CLAY | | | | | |
| 42 | | | | | | | | | |
| 43 | | | | End of borehole at 42.32m | | | | | |
| 44 | | | | | | | | | |
| 45 | | | | | | | | | |
| 46 | | | | | | | | | |
| 47 | | | | | | | | | |
| 48 | | | | | | | | | |
| 49 | | | | | | | | | |
| 50 | | | | | | | | | |
| 51 | | | | | | | | | |
| 52 | | | | | | | | | |
| 53 | | | | | | | | | |
| 54 | | | | | | | | | |
| 55 | | | | | | | | | |
| 56 | | | | | | | | | |
| 57 | | | | | | | | | |
| 58 | | | | | | | | | |
| 59 | | | | | | | | | |

¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: PCPT-6 PCPT-6A Date Commenced: 31/12/2020 03/01/2020 Coordinates ¹ : 1490971mE 1490973mE 4915538mN 4915540mN Water Depth ² : 50.31m 50.43m | |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results


| | | | | | |
|---------------|-----------------------------------|---------------|-----------------|----------------------------|----------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | Date Commenced: | Coordinates ¹ : | Water Depth ² : |
| Project Name: | Genoa Port (PFTE) | PCPT-6 | 31/12/2020 | 1490971mE | 50.31m |
| Project No.: | GMOP20-G-013 | PCPT-6A | 03/01/2020 | 4915538mN | 50.43m |
| Location: | Genoa Port | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results


| | | | | | | | | | | | |
|---------------|-----------------------------------|---------------|-------------------|-----------------|--------------------------|----------------------------|------------------------|------------------------|----------------------------|------------------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | PCPT-6 PCPT-6A | Date Commenced: | 31/12/2020 03/01/2020 | Coordinates ¹ : | 1490971mE 1490973mE | 4915538mN 4915540mN | Water Depth ² : | 50.31m 50.43m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | | | | | | | | | | |
|---------------|-----------------------------------|---------------|-------------------|-----------------|--------------------------|----------------------------|------------------------|------------------------|----------------------------|------------------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | PCPT-6 PCPT-6A | Date Commenced: | 31/12/2020 03/01/2020 | Coordinates ¹ : | 1490971mE 1490973mE | 4915538mN 4915540mN | Water Depth ² : | 50.31m 50.43m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | | |



¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$


⁴ Hollow symbols represent offshore results


| | | | | | |
|---------------|-----------------------------------|---------------|-----------------|----------------------------|----------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | Date Commenced: | Coordinates ¹ : | Water Depth ² : |
| Project Name: | Genoa Port (PFTE) | PCPT-6 | 31/12/2020 | 1490971mE | 50.31m |
| Project No.: | GMOP20-G-013 | PCPT-6A | 03/01/2020 | 4915538mN | 50.43m |
| Location: | Genoa Port | | | | |



| DEPTH (m) | SAMPLE | IN SITU TEST | LEGEND | STRATA DESCRIPTION | CONE PENETROMETER TEST | | UNDRAINED SHEAR STRENGTH ⁴ (kPa) | DENSITY ⁴ (Mg/m ³) | CLASSIFICATION ⁴ (%) | |
|-----------|--------|--------------|--------|---------------------------------------|-------------------------------------|-----------------------------|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | | | | Net Cone Resistance q_{net} (MPa) | Sleeve Friction f_s (MPa) | Pore Pressure Ratio, Bq | <ul style="list-style-type: none"> ▲ Torvane ◆ Pocket Penetrometer ● CIU Triaxial Test ● CAU Triaxial Test ● UU Triaxial Test ● Laboratory Vane ■ DSS | <ul style="list-style-type: none"> ● Bulk Density ◆ Dry Density | <ul style="list-style-type: none"> ● Water Content ■ Carbonate Content ▲ Fines Content Relative Density³ ◆ Plastic Limit ◆ Liquid Limit ◆ Plasticity Index |
| 81 | | | | 80.10m to 80.40m - medium bed of sand | 10 20 30 40 50 60 70 | 0.375 0.750 1.125 | -0.4 0.4 1.2 | 100.0 200.0 300.0 400.0 500.0 | 1.4 1.8 2.2 2.6 | 20 40 60 80 |
| 82 | | | | End of borehole at 81.28m | | | | | | |
| 83 | | | | | | | | | | |
| 84 | | | | | | | | | | |
| 85 | | | | | | | | | | |
| 86 | | | | | | | | | | |
| 87 | | | | | | | | | | |
| 88 | | | | | | | | | | |
| 89 | | | | | | | | | | |
| 90 | | | | | | | | | | |
| 91 | | | | | | | | | | |
| 92 | | | | | | | | | | |
| 93 | | | | | | | | | | |
| 94 | | | | | | | | | | |
| 95 | | | | | | | | | | |
| 96 | | | | | | | | | | |
| 97 | | | | | | | | | | |
| 98 | | | | | | | | | | |
| 99 | | | | | | | | | | |

¹ Local Geodetic Datum: Gauss-Boaga Fuso W
² Water Depth: LAT
³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$
⁴ Hollow symbols represent offshore results
 Ref: GMOP20-G-013-FAC-01
 Page 5 of 5

| | | | | | |
|---------------------------------|----------------------|----------------------------|------------------------------------------------|-----------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A | Borehole No.: PCPT-7 | Date Commenced: 19/12/2020 | Coordinates ¹ : 1491770mE 4915317mN | Water Depth ² : 52.56m |  |
| Project Name: Genoa Port (PFTE) | | | | | |
| Project No.: GMOP20-G-013 | | | | | |
| Location: Genoa Port | | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

² Water Depth: LAT

| | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: PCPT-8 Date Commenced: 23/12/2020 Coordinates¹: 1493948mE 4914839mN Water Depth²: 54.26m | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results


| | | | | | | |
|-------------------------------------------------------|--------------------------------------------------------------------|--------------------------|-------------------------------|------------------------------------------------------|--------------------------------------|--|
| Client: Project Name: Project No.: Location: | TECHNITAL S.p.A Genoa Port (PFTE) GMOP20-G-013 Genoa Port | Borehole No.: PCPT-8A | Date Commenced: 04/01/2021 | Coordinates ¹ : 1493947mE 4914843mN | Water Depth ² : 52.06m | |
|-------------------------------------------------------|--------------------------------------------------------------------|--------------------------|-------------------------------|------------------------------------------------------|--------------------------------------|--|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), K₀=1.0

⁴ Hollow symbols represent offshore results


| | | | | | | |
|-------------------------------------------------------|--------------------------------------------------------------------|--------------------------|-------------------------------|------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|
| Client: Project Name: Project No.: Location: | TECHNITAL S.p.A Genoa Port (PFTE) GMOP20-G-013 Genoa Port | Borehole No.: PCPT-8A | Date Commenced: 04/01/2021 | Coordinates ¹ : 1493947mE 4914843mN | Water Depth ² : 52.06m |  |
|-------------------------------------------------------|--------------------------------------------------------------------|--------------------------|-------------------------------|------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$

⁴ Hollow symbols represent offshore results

| | | | | | |
|---------------------------------|-----------------------|----------------------------|------------------------------------------------|-----------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A | Borehole No.: PCPT-8A | Date Commenced: 04/01/2021 | Coordinates ¹ : 1493947mE 4914843mN | Water Depth ² : 52.06m |  |
| Project Name: Genoa Port (PFTE) | | | | | |
| Project No.: GMOP20-G-013 | | | | | |
| Location: Genoa Port | | | | | |



¹ Local Geodetic Datum: Gauss-Boaga Fuso W

³ Relative densities derived from Jamiolkowski et al. (2003), $K_0=1.0$


⁴ Hollow symbols represent offshore results

Appendix A.3

Raw In Situ Test Results

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-4
 PCPT-4
 Date Commenced: 22/12/2020
 17/12/2020
 Coordinates¹: 1492615mE 4915142mN
 1492628mE 4915144mN
 Water Depth²: 52.46m
 52.48m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-4
 PCPT-4
 Date Commenced: 22/12/2020
 17/12/2020
 Coordinates¹: 1492615mE 4915142mN
 1492628mE 4915144mN
 Water Depth²: 52.46m
 52.48m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-4
 PCPT-4
 Date Commenced: 22/12/2020
 17/12/2020
 Coordinates¹: 1492615mE 4915142mN
 1492628mE 4915144mN
 Water Depth²: 52.46m
 52.48m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-4
 Date Commenced: 22/12/2020
 Coordinates¹: 1492615mE 4915142mN
 Water Depth²: 52.46m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-4
 Date Commenced: 22/12/2020
 Coordinates¹: 1492615mE 4915142mN
 Water Depth²: 52.46m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-6
 Date Commenced: 25/12/2020
 Coordinates¹: 1491090mE 4916168mN
 Water Depth²: 28.86m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-6
 Date Commenced: 25/12/2020
 Coordinates¹: 1491090mE 4916168mN
 Water Depth²: 28.86m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-6
 Date Commenced: 25/12/2020
 Coordinates¹: 1491090mE 4916168mN
 Water Depth²: 28.86m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-7
 Date Commenced: 20/12/2020
 Coordinates¹: 1490921mE 4915540mN
 Water Depth²: 52.36m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-7
 Date Commenced: 20/12/2020
 Coordinates¹: 1490921mE 4915540mN
 Water Depth²: 52.36m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-1
 Date Commenced: 17/12/2020
 Coordinates¹: 1494401mE 4915166mN
 Water Depth²: 36.46m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-2
 Date Commenced: 12/12/2020
 Coordinates¹: 1493464mE 4914953mN
 Water Depth²: 52.66m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-2
 Date Commenced: 12/12/2020
 Coordinates¹: 1493464mE 4914953mN
 Water Depth²: 52.66m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-3
 Date Commenced: 13/12/2020
 Coordinates¹: 1493382mE 4915273mN
 Water Depth²: 42.01m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-3
 Date Commenced: 13/12/2020
 Coordinates¹: 1493382mE 4915273mN
 Water Depth²: 42.01m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-5
 Date Commenced: 15/12/2020
 Coordinates¹: 1492799mE 4915775mN
 Water Depth²: 30.96m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-5
 Date Commenced: 15/12/2020
 Coordinates¹: 1492799mE 4915775mN
 Water Depth²: 30.96m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-5
 Date Commenced: 15/12/2020
 Coordinates¹: 1492799mE 4915775mN
 Water Depth²: 30.96m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fusu W

² Water Depth: LAT

RAW PCPT RESULTS

| | | | | | | | | | | | |
|---------------|-----------------------------------|---------------|-------------------|-----------------|--------------------------|----------------------------|------------------------|------------------------|----------------------------|------------------|-------------------------------------------------------------------------------------|
| Client: | TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: | PCPT-6 PCPT-6A | Date Commenced: | 31/12/2020 03/01/2020 | Coordinates ¹ : | 1490971mE 1490973mE | 4915538mN 4915540mN | Water Depth ² : | 50.31m 50.43m |  |
| Project Name: | Genoa Port (PFTE) | | | | | | | | | | |
| Project No.: | GMOP20-G-013 | | | | | | | | | | |
| Location: | Genoa Port | | | | | | | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-7
 Date Commenced: 19/12/2020
 Coordinates¹: 1491770mE 4915317mN
 Water Depth²: 52.56m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8
 Date Commenced: 23/12/2020
 Coordinates¹: 1493948mE 4914839mN
 Water Depth²: 54.26m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8A
 Date Commenced: 04/01/2021
 Coordinates¹: 1493947mE 4914843mN
 Water Depth²: 52.06m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8A
 Date Commenced: 04/01/2021
 Coordinates¹: 1493947mE 4914843mN
 Water Depth²: 52.06m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

RAW PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8A
 Date Commenced: 04/01/2021
 Coordinates¹: 1493947mE 4914843mN
 Water Depth²: 52.06m



¹ Local Geodetic Datum: Gauss-Boaga Fusso W


² Water Depth: LAT

RAW PCPT RESULTS

Appendix A.4 Derived In Situ Test Results

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project No.: GMOP20-G-013
Location: Genoa Port

Borehole No.: CC-4
PCPT-4
Date Commenced: 22/12/2020
17/12/2020
Coordinates¹: 1492615mE 4915142mN
1492628mE 4915144mN
Water Depth²: 52.46m
52.48m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-4
 PCPT-4
 Date Commenced: 22/12/2020
 17/12/2020
 Coordinates¹: 1492615mE 4915142mN
 1492628mE 4915144mN
 Water Depth²: 52.46m
 52.48m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-4
 PCPT-4
 Date Commenced: 22/12/2020
 17/12/2020
 Coordinates¹: 1492615mE 4915142mN
 1492628mE 4915144mN
 Water Depth²: 52.46m
 52.48m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port


Borehole No.: CC-4
 Date Commenced: 22/12/2020
 Coordinates¹: 1492615mE 4915142mN
 Water Depth²: 52.46m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

| | | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project No.: GMOP20-G-013 Location: Genoa Port | Borehole No.: CC-4 Date Commenced: 22/12/2020 Coordinates ¹ : 1492615mE 4915142mN Water Depth ² : 52.46m |  |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-6
 Date Commenced: 25/12/2020
 Coordinates¹: 1491090mE 4916168mN
 Water Depth²: 28.86m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-6
 Date Commenced: 25/12/2020
 Coordinates¹: 1491090mE 4916168mN
 Water Depth²: 28.86m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-6
 Date Commenced: 25/12/2020
 Coordinates¹: 1491090mE 4916168mN
 Water Depth²: 28.86m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: CC-7
 Date Commenced: 20/12/2020
 Coordinates¹: 1490921mE 4915540mN
 Water Depth²: 52.36m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-1
 Date Commenced: 17/12/2020
 Coordinates¹: 1494401mE 4915166mN
 Water Depth²: 36.46m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-2
 Date Commenced: 12/12/2020
 Coordinates¹: 1493464mE 4914953mN
 Water Depth²: 52.66m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-2
 Date Commenced: 12/12/2020
 Coordinates¹: 1493464mE 4914953mN
 Water Depth²: 52.66m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-2
 Date Commenced: 12/12/2020
 Coordinates¹: 1493464mE 4914953mN
 Water Depth²: 52.66m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-3
 Date Commenced: 13/12/2020
 Coordinates¹: 1493382mE 4915273mN
 Water Depth²: 42.01m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

| | | | | |
|-------------------------------------------|----------------------|----------------------------|------------------------------------------------|-----------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Borehole No.: PCPT-3 | Date Commenced: 13/12/2020 | Coordinates ¹ : 1493382mE 4915273mN | Water Depth ² : 42.01m |
| Project Name: Genoa Port (PFTE) | | | | |
| Project No.: GMOP20-G-013 | | | | |
| Location: Genoa Port | | | | |




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-5
 Date Commenced: 15/12/2020
 Coordinates¹: 1492799mE 4915775mN
 Water Depth²: 30.96m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-5
 Date Commenced: 15/12/2020
 Coordinates¹: 1492799mE 4915775mN
 Water Depth²: 30.96m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-5
 Date Commenced: 15/12/2020
 Coordinates¹: 1492799mE 4915775mN
 Water Depth²: 30.96m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE
 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-6
 PCPT-6A
 Date Commenced: 31/12/2020
 03/01/2020
 Coordinates¹: 1490971mE
 1490973mE 4915538mN
 4915540mN
 Water Depth²: 50.31m
 50.43m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port


Borehole No.: PCPT-7
 Date Commenced: 19/12/2020
 Coordinates¹: 1491770mE 4915317mN
 Water Depth²: 52.56m



DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8
 Date Commenced: 23/12/2020
 Coordinates¹: 1493948mE 4914839mN
 Water Depth²: 54.26m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8A
 Date Commenced: 04/01/2021
 Coordinates¹: 1493947mE 4914843mN
 Water Depth²: 52.06m




¹ Local Geodetic Datum: Gauss-Boaga Fusso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8A
 Date Commenced: 04/01/2021
 Coordinates¹: 1493947mE 4914843mN
 Water Depth²: 52.06m




¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT

DERIVED PCPT RESULTS

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project No.: GMOP20-G-013
 Location: Genoa Port

Borehole No.: PCPT-8A
 Date Commenced: 04/01/2021
 Coordinates¹: 1493947mE 4914843mN
 Water Depth²: 52.06m



¹ Local Geodetic Datum: Gauss-Boaga Fuso W

² Water Depth: LAT


DERIVED PCPT RESULTS

Appendix A.5 Dissipation Test Results

GMOP_AGS LIB_REV01-00_GLBGraphPH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|----------------|---------------|------------------------|---------------|
| Borehole: CC-4 | Test No.: C04 | Borehole Depth: 49.00m | u_0 : 20kPa |
|----------------|---------------|------------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGS LIB_REV01-00.GLBGraphPH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|----------------|---------------|------------------------|---------------|
| Borehole: CC-4 | Test No.: C09 | Borehole Depth: 65.00m | u_0 : 20kPa |
|----------------|---------------|------------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGSLIB_REV01-00.GLBGraphPH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|----------------|---------------|------------------------|---------------|
| Borehole: CC-7 | Test No.: C01 | Borehole Depth: 40.70m | u_0 : 10kPa |
|----------------|---------------|------------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGS LIB_REV01-00_GLB_GraphGH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|----------------|---------------|------------------------|---------------|
| Borehole: CC-7 | Test No.: C01 | Borehole Depth: 41.70m | u_0 : 20kPa |
|----------------|---------------|------------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGS LIB_REV01-00.GLB.GraphPH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013


Location: Genoa Port




| | | | |
|------------------|---------------|-----------------------|---------------|
| Borehole: PCPT-1 | Test No.: C02 | Borehole Depth: 5.50m | u_0 : 25kPa |
|------------------|---------------|-----------------------|---------------|

DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

| | | | |
|------------------------------------------------------|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| GMOP_AGSLIB_REV01-00.GLB.GraphGPH10-DISSIPATION TEST | Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| | Project Name: Genoa Port (PFTE) | | |
| | Project Number: GMOP20-G-013 | | |



| | | | |
|------------------|---------------|-----------------------|---------------|
| Borehole: PCPT-1 | Test No.: C03 | Borehole Depth: 8.70m | u_0 : 27kPa |
|------------------|---------------|-----------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGS LIB_REV01-00_GLB_GraphGH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port




| | | | |
|------------------|---------------|------------------------|---------------|
| Borehole: PCPT-2 | Test No.: C04 | Borehole Depth: 10.50m | u_0 : 15kPa |
|------------------|---------------|------------------------|---------------|

DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project Number: GMOP20-G-013

Location: Genoa Port




| | | | |
|------------------|---------------|-----------------------|------------------------|
| Borehole: PCPT-3 | Test No.: C02 | Borehole Depth: 4.00m | u ₀ : 10kPa |
|------------------|---------------|-----------------------|------------------------|

DISSIPATION TEST RESULTS

GMOP_AGS LIB_REV01-00_GLB_GraphGH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
 Project Name: Genoa Port (PFTE)
 Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|------------------|---------------|------------------------|---------------|
| Borehole: PCPT-4 | Test No.: C05 | Borehole Depth: 13.50m | u_0 : 15kPa |
|------------------|---------------|------------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGS LIB_REV01-00_GLB_GraphGH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|------------------|---------------|------------------------|---------------|
| Borehole: PCPT-4 | Test No.: C10 | Borehole Depth: 26.00m | u_0 : 10kPa |
|------------------|---------------|------------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGSLIB_REV01-00.GLBGraphPH10-DISSIPATIONTEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|------------------|---------------|------------------------|------------------------|
| Borehole: PCPT-5 | Test No.: C04 | Borehole Depth: 10.00m | u ₀ : 15kPa |
|------------------|---------------|------------------------|------------------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGSLIB_REV01-00.GLB.GraphGH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|------------------|---------------|-----------------------|---------------|
| Borehole: PCPT-6 | Test No.: C03 | Borehole Depth: 8.50m | u_0 : 25kPa |
|------------------|---------------|-----------------------|---------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGSLIB_REV01-00.GLBGraphPH10-DISSIPATION TEST

Client: TECHNITAL S.p.A
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|------------------|---------------|------------------------|-----------------|
| Borehole: PCPT-6 | Test No.: C06 | Borehole Depth: 17.30m | u_0 : 2224kPa |
|------------------|---------------|------------------------|-----------------|


DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

GMOP_AGS LIB_REV01-00.GLBGraphPH10-DISSIPATION TEST

Client: TECHNITAL S.p.A and Modimar S.r.l
Project Name: Genoa Port (PFTE)
Project Number: GMOP20-G-013

Location: Genoa Port



| | | | |
|-------------------|---------------|------------------------|---------------|
| Borehole: PCPT-8A | Test No.: C08 | Borehole Depth: 26.90m | u_0 : 15kPa |
|-------------------|---------------|------------------------|---------------|

DISSIPATION TEST RESULTS

Ref.: GMOP20-G-013-FAC-01

APPENDIX B OFFSHORE LABORATORY TESTING

Appendix B.1

Classification Laboratory Tests

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-1 | P01 | 0.05 | 59 | | | | | | | | | |
| CC-1 | P01 | 0.25 | 62 | | | | | | | | | |
| CC-1 | P01 | 0.40 | 56 | 1.63 | 1.05 | 2 | | | | | | |
| CC-1 | P01 | 0.60 | | | | 5 | | | | | | |
| CC-1 | P01 | 0.80 | 53 | 1.73 | 1.13 | | | | | | | |
| CC-1 | P01 | 0.90 | | | | | | 3 | 0 | | | |
| CC-1 | P02 | 1.20 | | | | 10 | | | | | | |
| CC-1 | P02 | 1.60 | | | | 11 | | | | | | |
| CC-1 | P03 | 2.04 | 41 | | | | | | | | | |
| CC-1 | P03 | 2.25 | 44 | | | 6 | | | | | | |
| CC-1 | P03 | 2.45 | 53 | 1.99 | 1.30 | | | | | | | |
| CC-1 | P03 | 2.85 | 47 | 1.70 | 1.16 | | | | | | | |
| CC-1 | P03 | 2.95 | | | | | | 12 | 1 | | | |
| CC-1 | P03 | 3.00 | | | | 13 | | | | | | |
| CC-1 | P04 | 3.05 | 45 | | | | | | | | | |
| CC-1 | P04 | 3.50 | 43 | 1.78 | 1.25 | | | | | | | |
| CC-1 | P04 | 3.70 | 41 | | | | | | | | | |
| CC-1 | P06 | 5.15 | 37 | 1.84 | 1.34 | | | | | | | |
| CC-1 | P06 | 5.50 | 41 | | | | | | | | | |
| CC-1 | P06 | 5.80 | 28 | | | | | | | | | |
| CC-1 | P07 | 6.20 | 31 | 1.93 | 1.47 | | | | | | | |
| CC-1 | P07 | 6.80 | 37 | 1.89 | 1.39 | | | | | | | |


PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

¹ Local Geodetic Datum: Gauss-Boaga Fuso W, Actual Coordinates

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-1 | P07 | 6.85 | 34 | | | | | | | | | |
| CC-1 | P08 | 7.15 | 40 | 1.98 | 1.41 | | | | | | | |
| CC-1 | P08 | 7.40 | 22 | | | | | | | | | |
| CC-1 | P08 | 7.60 | 35 | | | | | | | | | |
| CC-1 | P08 | 7.80 | 35 | | | | | | | | | |
| CC-1 | CR15 | 11.50 | | 2.99 | | | | | | | | |
| CC-1 | CR17 | 13.50 | | 2.91 | | | | | | | | |
| CC-1 | CR19 | 16.00 | | 2.80 | | | | | | | | |
| CC-1 | CR19 | 16.15 | 18 | | | | | | | | | |
| CC-1 | CR19 | 16.16 | 17 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|-------------------------------------------------------------------------------------|
| <p>Client: TECHNITAL S.p.A and Modimar S.r.l</p> <p>Project Name: Genoa Port (PFTE)</p> <p>Project Number: GMOP20-G-013</p> | <p>Location: Genoa Port</p> |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|-------------------------------------------------------------------------------------|


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-2 | P01 | 0.01 | 48 | | | | | | | | | |
| CC-2 | P01 | 0.05 | 48 | 1.45 | 0.98 | | | | | | | |
| CC-2 | P01 | 0.60 | | | | 137 | 175 | | | | | |
| CC-2 | P01 | 0.65 | 40 | | | | | | | | | |
| CC-2 | P01 | 0.90 | 35 | | | | | | | | | |
| CC-2 | P02 | 1.05 | 30 | | | | | | | | | |
| CC-2 | P02 | 1.15 | 32 | 1.67 | 1.27 | | | | | | | |
| CC-2 | P02 | 1.50 | 53 | | | | | | | | | |
| CC-2 | P02 | 1.60 | 44 | | | | | | | | | |
| CC-2 | P02 | 1.75 | 32 | | | 60 | 75 | | | | | |
| CC-2 | P03 | 2.10 | 40 | | | | | | | | | |
| CC-2 | P03 | 2.30 | 46 | | | | | | | | | |
| CC-2 | P03 | 2.55 | 44 | | | | | | | | | |
| CC-2 | P04A | 3.40 | 45 | | | | | | | | | |
| CC-2 | P04A | 3.80 | 37 | | | | | | | | | |
| CC-2 | P05 | 4.00 | | | | 20 | 25 | | | | | |
| CC-2 | P05 | 4.05 | 41 | 1.61 | 1.14 | | | | | | | |
| CC-2 | P05 | 5.50 | | | | 20 | | | | | | |
| CC-2 | P05 | 4.45 | | | | 25 | 38 | | | | | |
| CC-2 | P05 | 4.85 | | | | 25 | 25 | | | | | |
| CC-2 | P06 | 5.20 | | 1.67 | | | | | | | | |
| CC-2 | P06 | 5.30 | 21 | 1.82 | 1.50 | | | | | 8 | 1.1 | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-2 | P06 | 5.70 | | | | 20 | | | | | | |
| CC-2 | P06 | 5.85 | | | | | | 18 | 1 | | | |
| CC-2 | P06 | 5.90 | | | | 20 | | | | | | |
| CC-2 | P07 | 6.10 | 43 | | | | | | | | | |
| CC-2 | P07 | 6.20 | 37 | 1.57 | 1.15 | | | | | | | |
| CC-2 | P07 | 6.40 | | | | 20 | | | | | | |
| CC-2 | P07 | 6.60 | | 1.77 | | | | | | | | |
| CC-2 | P07 | 7.00 | | | | 25 | 25 | | | | | |
| CC-2 | P08 | 7.10 | | | | 25 | 25 | | | | | |
| CC-2 | P08 | 7.20 | 35 | 1.80 | 1.33 | | | | | | | |
| CC-2 | P08 | 7.80 | | 1.77 | 1.55 | 20 | 38 | | | | | |
| CC-2 | P08 | 7.95 | | | | | | 22 | 1 | | | |
| CC-2 | P08 | 8.00 | | | | 20 | 38 | | | | | |
| CC-2 | P09 | 8.75 | 34 | | | | | | | | | |
| CC-2 | P10 | 9.10 | 39 | 1.80 | 1.29 | 25 | 25 | | | | | |
| CC-2 | P10 | 9.50 | 36 | 1.80 | 1.32 | | | | | 14 | | |
| CC-2 | P10 | 9.70 | | | | 20 | 25 | | | | | |
| CC-2 | P10 | 9.85 | | | | | | 20 | 2 | | | |
| CC-2 | P10 | 9.90 | | | | 20 | 25 | | | | | |
| CC-2 | P11 | 10.05 | 37 | | | | | | | | | |
| CC-2 | P11 | 10.10 | | | | 30 | 38 | | | | | |
| CC-2 | P11 | 10.30 | 28 | 1.76 | 1.38 | 20 | 25 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-2 | P11 | 10.90 | 41 | 1.63 | 1.16 | | | | | | | |
| CC-2 | P12 | 11.10 | 79 | 1.68 | 0.94 | 40 | 38 | | | | | |
| CC-2 | P12 | 11.40 | | | | 35 | 25 | | | | | |
| CC-2 | P12 | 11.80 | | | | 40 | 38 | 38 | 2 | | | |
| CC-2 | P12 | 11.85 | | | | 35 | 38 | | | | | |
| CC-2 | P13 | 12.00 | 39 | 1.83 | 1.32 | 35 | 30 | | | | | |
| CC-2 | P13 | 12.40 | 36 | 1.81 | 1.33 | 40 | 30 | | | | | |
| CC-2 | P13 | 12.95 | | | | 35 | 50 | | | | | |
| CC-2 | P14 | 13.00 | 39 | 1.86 | 1.34 | 60 | 38 | | | | | |
| CC-2 | P14 | 13.40 | 68 | 1.84 | 1.10 | 45 | 88 | | | | | |
| CC-2 | P14 | 11.84 | | | | | | 44 | 2 | | | |
| CC-2 | P14 | 13.85 | | | | 45 | 50 | | | | | |
| CC-2 | P15 | 14.00 | 41 | 1.88 | 1.33 | 40 | 50 | | | | | |
| CC-2 | P15 | 14.40 | 39 | 1.95 | 1.40 | 40 | 50 | | | | | |
| CC-2 | P15 | 14.80 | | | | 35 | 50 | | | | | |
| CC-2 | P16 | 15.00 | | | | 45 | 50 | | | | | |
| CC-2 | P16 | 15.40 | | | | 40 | 38 | | | | | |
| CC-2 | P16 | 15.60 | 40 | 1.90 | 1.36 | | | | | | | |
| CC-2 | P16 | 15.90 | | | | | | 40 | 5 | | | |
| CC-2 | P16 | 15.95 | | | | 40 | 50 | | | | | |
| CC-2 | P17 | 16.00 | 41 | 1.88 | 1.33 | 45 | 38 | | | | | |
| CC-2 | P17 | 16.40 | 32 | 1.79 | 1.36 | 48 | 50 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-2 | P17 | 16.95 | | | | 55 | 50 | | | | | |
| CC-2 | P18 | 17.00 | 38 | 1.80 | 1.30 | 35 | 30 | | | | | |
| CC-2 | P18 | 17.40 | 39 | 1.85 | 1.33 | 40 | 50 | | | | | |
| CC-2 | P18 | 17.95 | | | | | | 42 | 3 | | | |
| CC-2 | P18 | 18.00 | | | | 35 | 50 | | | | | |
| CC-2 | P19 | 18.00 | 41 | 1.86 | 1.32 | | | | | | | |
| CC-2 | P19 | 18.01 | | | | 35 | 63 | | | | | |
| CC-2 | P19 | 18.40 | | | | 40 | 50 | | | | | |
| CC-2 | P19 | 18.80 | | | | 35 | | | | | | |
| CC-2 | P19 | 18.90 | | | | | 63 | | | | | |
| CC-2 | P20 | 19.10 | 35 | 1.99 | 1.47 | | | | | | | |
| CC-2 | P20 | 19.65 | 38 | 1.98 | 1.43 | | | | | | | |
| CC-2 | P22 | 21.40 | 41 | 1.99 | 1.41 | | | | | | | |
| CC-2 | P22 | 21.60 | 35 | 2.03 | 1.50 | | | | | | | |
| CC-2 | P23 | 22.15 | 33 | 2.04 | 1.53 | | | | | | | |
| CC-2 | P23 | 22.50 | 36 | | | | | | | | | |
| CC-2 | P23 | 22.70 | 37 | 1.89 | 1.37 | | | | | | | |
| CC-2 | P24 | 23.05 | 33 | 1.95 | 1.47 | | | | | | | |
| CC-2 | P24 | 23.50 | 35 | | | | | | | | | |
| CC-2 | P24 | 23.75 | 32 | 1.83 | 1.38 | | | | | | | |
| CC-2 | P24 | 23.85 | 34 | | | | | | | | | |
| CC-2 | P25 | 24.10 | 37 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

¹ Local Geodetic Datum: Gauss-Boaga Fuso W, Actual Coordinates

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-2 | P25 | 24.20 | 13 | 1.85 | 1.64 | | | | | | | |
| CC-2 | P25 | 24.40 | 12 | 1.87 | 1.68 | | | | | | | |
| CC-2 | P25 | 24.60 | 13 | 1.81 | 1.60 | | | | | | | |
| CC-2 | P25 | 24.75 | 21 | | | | | | | | | |
| CC-2 | P26 | 25.05 | 21 | | | | | | | | | |
| CC-2 | P26 | 25.20 | 14 | 1.81 | 1.59 | | | | | | | |
| CC-2 | P26 | 25.70 | 15 | 1.82 | 1.59 | | | | | | | |
| CC-2 | P26 | 25.80 | 23 | | | | | | | | | |
| CC-2 | P27 | 26.20 | 13 | 1.92 | 1.70 | | | | | | | |
| CC-2 | P27 | 26.50 | 19 | | | | | | | | | |
| CC-2 | P27 | 26.70 | 11 | 1.94 | 1.75 | | | | | | | |
| CC-2 | P28 | 27.15 | 21 | | | | | | | | | |
| CC-2 | P28 | 27.35 | 12 | 1.92 | 1.71 | | | | | | | |
| CC-2 | P28 | 27.55 | 11 | 1.94 | 1.74 | | | | | | | |
| CC-2 | P29A | 28.05 | 26 | | | | | | | | | |
| CC-2 | P29A | 28.10 | | | | 40 | 63 | | | | | |
| CC-2 | P29A | 28.30 | 12 | 2.08 | 1.86 | | | | | | | |
| CC-2 | P29A | 28.45 | | | | 50 | 75 | | | | | |
| CC-2 | P30 | 29.40 | | | | 75 | 150 | | | | | |
| CC-2 | P30 | 29.50 | 14 | | | | | | | | | |
| CC-2 | P30 | 29.65 | | | | 100 | 200 | | | | | |
| CC-2 | P30 | 29.80 | 9 | | | | | | | | | |


PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

¹ Local Geodetic Datum: Gauss-Boaga Fuso W, Actual Coordinates

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-2 | P31 | 30.25 | 16 | 2.13 | 1.84 | | 250 | | | | | |
| CC-2 | P31 | 30.65 | 12 | 2.10 | 1.88 | | 210 | | | | | |
| CC-2 | P32 | 31.15 | 11 | 2.11 | 1.90 | 150 | 240 | | | | | |
| CC-2 | P32 | 31.16 | | | | | 270 | | | | | |
| CC-2 | P32 | 31.30 | | | | 150 | 275 | | | | | |
| CC-2 | P32 | 31.40 | 18 | | | | | | | | | |
| CC-2 | P33 | 32.10 | 19 | | | | | | | | | |
| CC-2 | P33 | 32.30 | 23 | | | | | | | | | |
| CC-2 | P33 | 32.50 | 20 | | | | | | | | | |
| CC-2 | P34 | 33.10 | 19 | | | | | | | | | |
| CC-2 | P34 | 33.30 | 22 | | | | | | | | | |
| CC-2 | P34 | 33.60 | 23 | | | | | | | | | |
| CC-2 | P35 | 34.40 | 20 | | | | | | | | | |
| CC-2 | P35 | 34.60 | 30 | | | | | | | | | |
| CC-2 | P36 | 35.05 | 25 | | | | | | | | | |
| CC-2 | P36 | 35.20 | 27 | | | | | | | | | |
| CC-2 | P37 | 35.50 | 19 | | | | | | | | | |
| CC-2 | P37 | 36.00 | 18 | 2.05 | 1.74 | | | | | | | |
| CC-2 | P37 | 36.10 | 16 | | | | | | | | | |
| CC-2 | P38 | 36.90 | 26 | | | | | | | | | |
| CC-2 | P38 | 37.15 | 30 | | | | | | | | | |
| CC-2 | P38 | 37.30 | 29 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-2 | P39 | 37.65 | 30 | | | | | | | | | |
| CC-2 | P39 | 36.20 | 22 | | | | | | | | | |
| CC-2 | P39 | 38.20 | 22 | | | | 200 | | | | | |
| CC-2 | P39 | 38.21 | | | | | 200 | | | | | |
| CC-2 | P40 | 38.55 | 24 | 2.18 | 1.76 | | | | | | | |
| CC-2 | P40 | 38.65 | | | | 175 | 200 | | | | | |
| CC-2 | P40 | 38.66 | | | | | 250 | | | | | |
| CC-2 | P40 | 38.90 | 21 | | | | | | | | | |
| CC-2 | P41 | 39.10 | 15 | | | | | | | | | |
| CC-2 | P41 | 39.40 | 15 | | | | | | | | | |
| CC-2 | P42 | 40.10 | 24 | 2.25 | 1.81 | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-3 | P01 | 0.20 | 47 | | | | | | | | | |
| CC-3 | P01 | 0.60 | 54 | | | | | | | | | |
| CC-3 | P01 | 0.80 | 84 | 1.76 | 0.95 | | | | | | | |
| CC-3 | P02 | 1.20 | 44 | 1.86 | 1.29 | | | | | | | |
| CC-3 | P02 | 1.40 | 37 | 1.81 | 1.32 | | | | | | | |
| CC-3 | P02 | 1.65 | 39 | | | | | | | | | |
| CC-3 | P02 | 1.90 | | | | | | 4 | 0 | | | |
| CC-3 | P04 | 3.05 | 56 | | | | | | | | | |
| CC-3 | P04 | 3.20 | 43 | 1.59 | 1.11 | | | | | | | |
| CC-3 | P04 | 3.60 | 43 | | | | | | | | | |
| CC-3 | P04 | 3.95 | 45 | | | | | | | | | |
| CC-3 | P05 | 4.00 | 63 | | | | | | | | | |
| CC-3 | P05 | 4.15 | 47 | 1.86 | 1.27 | | | | | | | |
| CC-3 | P05 | 4.25 | | | | 15 | 25 | | | | | |
| CC-3 | P05 | 4.45 | | | | 17 | 25 | | | | | |
| CC-3 | P05 | 4.65 | | | | 16 | 25 | | | | | |
| CC-3 | P05 | 4.70 | 71 | 2.09 | 1.22 | | | | | | | |
| CC-3 | P05 | 4.75 | | | | 18 | 25 | | | | | |
| CC-3 | P05 | 4.90 | | 2.21 | | | | | | | | |
| CC-3 | P05 | 5.00 | | | | 6 | 25 | 13 | 3 | | | |
| CC-3 | P06 | 5.05 | 46 | 1.77 | 1.21 | | | | | | | |
| CC-3 | P06 | 5.15 | | 2.03 | | 14 | 25 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-3 | P06 | 5.00 | 45 | 1.77 | 1.22 | | | | | | | |
| CC-3 | P06 | 5.35 | | | | 18 | | | | | | |
| CC-3 | P06 | 5.50 | | 1.91 | | 18 | | | | | | |
| CC-3 | P06 | 5.70 | | | | 14 | | | | | | |
| CC-3 | P06 | 5.80 | 41 | 1.87 | 1.33 | | | | | | | |
| CC-3 | P06 | 6.00 | | | | 12 | | 13 | 3 | | | |
| CC-3 | P08 | 7.00 | 47 | 1.72 | 1.17 | | 50 | | | | | |
| CC-3 | P08 | 7.50 | 55 | 1.98 | 1.28 | 45 | 63 | | | | | |
| CC-3 | P08 | 7.90 | | | | | 50 | | | | | |
| CC-3 | P09 | 8.00 | 56 | 1.74 | 1.12 | | | | | | | |
| CC-3 | P09 | 8.20 | | | | 35 | 50 | | | | | |
| CC-3 | P09 | 8.60 | | | | 45 | 50 | | | | | |
| CC-3 | P09 | 8.80 | 45 | 1.84 | 1.27 | | | | | | | |
| CC-3 | P09 | 8.95 | | | | 50 | 50 | 47 | 11 | | | |
| CC-3 | P10 | 9.05 | 42 | 1.93 | 1.36 | 45 | 50 | | | | | |
| CC-3 | P10 | 9.45 | | | | 45 | 63 | | | | | |
| CC-3 | P10 | 9.65 | 43 | 1.95 | 1.36 | | | | | | | |
| CC-3 | P10 | 9.85 | | | | 40 | 63 | | | | | |
| CC-3 | P12 | 11.10 | 35 | 1.89 | 1.40 | 40 | 50 | | | | | |
| CC-3 | P12 | 11.00 | 42 | 1.81 | 1.27 | | | | | | | |
| CC-3 | P12 | 11.50 | | | | 40 | 75 | | | | | |
| CC-3 | P12 | 11.70 | | | | 45 | 75 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|
| <p>Client: TECHNITAL S.p.A and Modimar S.r.l</p> <p>Project Name: Genoa Port (PFTE)</p> <p>Project Number: GMOP20-G-013</p> | <p>Location: Genoa Port</p> |  |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-3 | P13 | 12.10 | 51 | 1.80 | 1.19 | 45 | 88 | | | | | |
| CC-3 | P13 | 12.50 | 41 | 1.86 | 1.32 | 60 | 113 | | | | | |
| CC-3 | P14 | 13.30 | 37 | | | | | | | | | |
| CC-3 | P14 | 13.50 | 33 | | | | | | | | | |
| CC-3 | P14 | 13.80 | 32 | | | | | | | | | |
| CC-3 | P16 | 15.10 | 33 | 1.91 | 1.44 | | | | | | | |
| CC-3 | P16 | 15.40 | 33 | | | | | | | | | |
| CC-3 | P16 | 15.70 | 31 | 1.85 | 1.41 | | | | | | | |
| CC-3 | P17 | 16.10 | 32 | | | | | | | | | |
| CC-3 | P17 | 16.15 | 30 | 1.89 | 1.45 | | | | | | | |
| CC-3 | P17 | 16.50 | 31 | 1.84 | 1.40 | | | | | | | |
| CC-3 | P18 | 17.20 | 42 | 2.14 | 1.50 | | | | | | | |
| CC-3 | P18 | 17.40 | 23 | | | | | | | | | |
| CC-3 | P18 | 17.50 | 53 | 2.18 | 1.42 | | | | | | | |
| CC-3 | P19 | 18.10 | 32 | 1.92 | 1.45 | | | | | | | |
| CC-3 | P19 | 18.60 | 32 | 1.90 | 1.44 | | | | | | | |
| CC-3 | P20 | 19.10 | 31 | 1.91 | 1.45 | | | | | | | |
| CC-3 | P20 | 19.30 | 32 | 1.91 | 1.45 | | | | | | | |
| CC-3 | P20 | 19.40 | 29 | | | | | | | | | |
| CC-3 | P20 | 19.60 | 29 | 1.93 | 1.50 | | | | | | | |
| CC-3 | P21 | 20.15 | 30 | 2.04 | 1.58 | | | | | | | |
| CC-3 | P21 | 20.30 | 24 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-3 | P21 | 20.60 | 27 | 2.00 | 1.57 | | | | | | | |
| CC-3 | P22 | 21.20 | 29 | 1.92 | 1.49 | | | | | | | |
| CC-3 | P22 | 21.40 | 27 | | | | | | | | | |
| CC-3 | P22 | 21.50 | 25 | 1.93 | 1.55 | | | | | | | |
| CC-3 | P22 | 21.75 | 21 | | | | | | | | | |
| CC-3 | PU23A | 22.05 | 22 | | | | | | | | | |
| CC-3 | H38 | 35.60 | 21 | | | | | | | | | |
| CC-3 | PU51 | 45.05 | 24 | | | | | | | | | |
| CC-3 | PU51 | 45.10 | 22 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | P01 | 0.05 | 52 | | | 2 | | | | | | |
| CC-4 | P01 | 0.30 | 51 | 1.83 | 1.22 | 2 | | | | | | |
| CC-4 | P02 | 0.55 | 46 | | | | | | | | | |
| CC-4 | P02 | 1.25 | 49 | 1.79 | 1.20 | 14 | | | | | | |
| CC-4 | P02 | 1.40 | 47 | | | | | 8 | 1 | | | |
| CC-4 | P02 | 1.45 | | | | 9 | | | | | | |
| CC-4 | P03 | 1.55 | 43 | | | | | | | | | |
| CC-4 | P03 | 1.80 | | | | 5 | | | | | | |
| CC-4 | P03 | 2.20 | | | | 13 | | | | | | |
| CC-4 | P03 | 2.30 | 43 | 1.83 | 1.28 | | | | | | | |
| CC-4 | P04 | 2.55 | 43 | | | | | | | | | |
| CC-4 | P04 | 2.65 | | | | 18 | 25 | | | | | |
| CC-4 | P04 | 3.25 | 46 | 1.91 | 1.31 | | | | | | | |
| CC-4 | P04 | 3.35 | | | | | | 17 | 3 | | | |
| CC-4 | P04 | 3.40 | | | | 30 | 38 | | | | | |
| CC-4 | P05 | 3.70 | | | | 14 | 15 | | | | | |
| CC-4 | P05 | 4.10 | 41 | 1.91 | 1.35 | | | | | | | |
| CC-4 | P05 | 4.35 | | | | 17 | 15 | | | | | |
| CC-4 | P06 | 4.70 | 38 | 1.82 | 1.32 | 35 | 30 | | | | | |
| CC-4 | P06 | 4.90 | | | | 35 | 30 | | | | | |
| CC-4 | P06 | 5.25 | | | | 12 | 25 | | | | | |
| CC-4 | P06 | 5.30 | 45 | | | | | 18 | 3 | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | P07 | 5.55 | 43 | 1.88 | 1.31 | | | | | | | |
| CC-4 | P07 | 5.75 | | | | 30 | 25 | | | | | |
| CC-4 | P07 | 5.95 | | 1.87 | | | | | | | | |
| CC-4 | P07 | 6.05 | | | | 30 | 25 | | | | | |
| CC-4 | P08 | 6.80 | 45 | 1.88 | 1.30 | 35 | 38 | | | | | |
| CC-4 | P08 | 7.00 | 37 | | | | | | | | | |
| CC-4 | P08 | 7.20 | 34 | 1.93 | 1.45 | | | | | | | |
| CC-4 | P09 | 7.60 | 33 | 1.86 | 1.40 | | | | | | | |
| CC-4 | P09 | 8.20 | 32 | 1.91 | 1.46 | | | | | | | |
| CC-4 | P10 | 8.60 | 32 | 1.92 | 1.46 | | | | | | | |
| CC-4 | P10 | 9.00 | 30 | | | | | | | | | |
| CC-4 | P10 | 9.30 | 32 | 1.92 | 1.45 | | | | | | | |
| CC-4 | P11 | 10.40 | 35 | | | | | | | | | |
| CC-4 | P12 | 10.60 | 35 | 1.88 | 1.40 | | | | | | | |
| CC-4 | P12 | 11.00 | 32 | | | | | | | | | |
| CC-4 | P12 | 11.25 | 31 | 1.89 | 1.44 | | | | | | | |
| CC-4 | P13 | 11.70 | 33 | 1.83 | 1.37 | | | | | | | |
| CC-4 | P13 | 11.90 | 33 | | | | | | | | | |
| CC-4 | P13 | 12.10 | 35 | 1.93 | 1.44 | | | | | | | |
| CC-4 | P14 | 12.60 | 36 | 1.83 | 1.35 | | | | | | | |
| CC-4 | P14 | 12.80 | 36 | 1.94 | 1.43 | | | | | | | |
| CC-4 | P14 | 13.30 | 30 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

¹ Local Geodetic Datum: Gauss-Boaga Fuso W, Actual Coordinates

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | P15 | 13.80 | 33 | 1.90 | 1.42 | | | | | | | |
| CC-4 | P15 | 14.00 | 33 | | | | | | | | | |
| CC-4 | P15 | 14.20 | 32 | 1.94 | 1.47 | | | | | | | |
| CC-4 | P16 | 14.55 | 35 | | | | | | | | | |
| CC-4 | P16 | 14.80 | 35 | 1.87 | 1.39 | | | | | | | |
| CC-4 | P16 | 15.10 | 37 | 1.85 | 1.35 | | | | | | | |
| CC-4 | P17 | 15.60 | 36 | 1.89 | 1.38 | | | | | | | |
| CC-4 | P17 | 16.10 | 30 | 1.97 | 1.51 | | | | | | | |
| CC-4 | P17 | 16.20 | 28 | | | | | | | | | |
| CC-4 | P18 | 16.70 | 31 | 1.95 | 1.49 | | | | | | | |
| CC-4 | P18 | 17.00 | 30 | | | | | | | | | |
| CC-4 | P18 | 17.20 | 38 | 1.90 | 1.37 | | | | | | | |
| CC-4 | P19 | 17.55 | 30 | | | | | | | | | |
| CC-4 | P19 | 17.75 | 33 | 1.90 | 1.43 | | | | | | | |
| CC-4 | P19 | 18.10 | 29 | 1.93 | 1.50 | | | | | | | |
| CC-4 | P19 | 18.20 | 32 | | | | | | | | | |
| CC-4 | P20 | 18.60 | 29 | 2.01 | 1.56 | | | | | | | |
| CC-4 | P20 | 18.90 | 27 | 2.00 | 1.57 | | | | | | | |
| CC-4 | P20 | 19.20 | 31 | | | | | | | | | |
| CC-4 | P22 | 20.30 | 32 | 1.98 | 1.50 | | 250 | | | | | |
| CC-4 | P22 | 20.50 | | | | | 250 | | | | | |
| CC-4 | P23 | 21.10 | 32 | 1.96 | 1.48 | | 225 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

¹ Local Geodetic Datum: Gauss-Boaga Fuso W, Actual Coordinates

| | | |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|
| <p>Client: TECHNITAL S.p.A and Modimar S.r.l</p> <p>Project Name: Genoa Port (PFTE)</p> <p>Project Number: GMOP20-G-013</p> | <p>Location: Genoa Port</p> |  |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | P23 | 21.45 | | | | | 230 | | | | | |
| CC-4 | P23 | 21.65 | 30 | 1.99 | 1.53 | | 250 | | | | | |
| CC-4 | P24 | 22.30 | 43 | 1.98 | 1.38 | | 250 | | | | | |
| CC-4 | P24 | 22.50 | | | | | 225 | | | | | |
| CC-4 | P25 | 23.80 | | | | 187 | 200 | | | | | |
| CC-4 | P26 | 24.05 | 40 | 2.17 | 1.55 | | | | | | | |
| CC-4 | P26 | 24.25 | | | | | 250 | | | | | |
| CC-4 | P27 | 24.70 | 53 | 2.01 | 1.31 | 137 | 175 | | | | | |
| CC-4 | P27 | 25.10 | 30 | 1.97 | 1.52 | | | | | | | |
| CC-4 | P27 | 25.40 | | | | 150 | 113 | | | | | |
| CC-4 | P28 | 25.70 | 54 | 2.11 | 1.37 | 112 | 138 | | | | | |
| CC-4 | P28 | 25.90 | | | | 112 | 125 | | | | | |
| CC-4 | P28 | 26.40 | 50 | 2.01 | 1.34 | 100 | 125 | | | | | |
| CC-4 | P28 | 25.40 | | | | | | 56 | 14 | | | |
| CC-4 | P29 | 26.55 | 34 | 2.06 | 1.54 | 200 | 137 | | | | | |
| CC-4 | P29 | 27.00 | 28 | 2.06 | 1.61 | 225 | 150 | | | | | |
| CC-4 | P30 | 27.70 | 27 | 2.04 | 1.61 | 350 | | | | | | |
| CC-4 | P30 | 27.90 | | | | 325 | 200 | | | | | |
| CC-4 | P30 | 28.10 | 30 | 2.09 | 1.61 | | | | | | | |
| CC-4 | P30 | 28.29 | | | | 200 | | | | | | |
| CC-4 | P30 | 28.30 | | | | 188 | 162 | | | | | |
| CC-4 | P31 | 28.50 | | | | | 138 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|
| <p>Client: TECHNITAL S.p.A and Modimar S.r.l</p> <p>Project Name: Genoa Port (PFTE)</p> <p>Project Number: GMOP20-G-013</p> | <p>Location: Genoa Port</p> |  |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | P31 | 28.60 | 31 | | | | | | | | | |
| CC-4 | PU32 | 29.00 | 20 | 2.14 | 1.78 | | | | | | | |
| CC-4 | PU33 | 29.50 | 29 | 2.08 | 1.61 | | | | | | | |
| CC-4 | PU33 | 29.70 | 31 | 1.94 | 1.48 | 162 | 175 | | | | | |
| CC-4 | PU33 | 29.80 | | | | 112 | 400 | | | | | |
| CC-4 | PU34 | 30.00 | 31 | 2.12 | 1.62 | | 75 | | | | | |
| CC-4 | PU34 | 30.40 | | | | 150 | 175 | | | | | |
| CC-4 | PU34 | 30.60 | 29 | 2.05 | 1.59 | | | | | | | |
| CC-4 | PU34 | 30.80 | | | | 150 | 175 | | | | | |
| CC-4 | PU35 | 31.00 | 26 | 2.04 | 1.62 | | | | | | | |
| CC-4 | PU35 | 31.20 | | | | 187 | 310 | | | | | |
| CC-4 | PU35 | 31.40 | 28 | 2.02 | 1.58 | | | | | | | |
| CC-4 | PU35 | 31.65 | | | | | 150 | 156 | 11 | | | |
| CC-4 | PU36 | 32.20 | 31 | 1.90 | 1.45 | | | | | | | |
| CC-4 | PU36 | 32.60 | 31 | 2.00 | 1.53 | | | | | | | |
| CC-4 | PU36 | 32.75 | | | | 100 | 138 | | | | | |
| CC-4 | PU37 | 33.20 | 27 | 2.01 | 1.58 | 175 | 225 | | | | | |
| CC-4 | PU37 | 33.60 | 47 | 2.04 | 1.39 | | | | | | | |
| CC-4 | PU37 | 33.80 | | | | 125 | 138 | | | | | |
| CC-4 | PU38 | 34.00 | | | | | 200 | | | | | |
| CC-4 | PU38 | 34.20 | 29 | 2.02 | 1.57 | | | | | | | |
| CC-4 | PU38 | 34.45 | 28 | 2.07 | 1.62 | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|
| <p>Client: TECHNITAL S.p.A and Modimar S.r.l</p> <p>Project Name: Genoa Port (PFTE)</p> <p>Project Number: GMOP20-G-013</p> | <p>Location: Genoa Port</p> |  |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | PU38 | 34.70 | | | | | 225 | | | | | |
| CC-4 | PU39 | 35.20 | | | | 137 | 153 | | | | | |
| CC-4 | PU39 | 35.40 | 31 | 2.07 | 1.58 | | | | | | | |
| CC-4 | PU39 | 35.65 | | | | 100 | 188 | | | | | |
| CC-4 | PU40 | 36.00 | 33 | 2.02 | 1.52 | | | | | | | |
| CC-4 | PU40 | 36.40 | 27 | 2.08 | 1.64 | 125 | 300 | | | | | |
| CC-4 | PU40 | 36.85 | | | | 137 | 175 | | | | | |
| CC-4 | PU41 | 37.00 | | | | | 175 | | | | | |
| CC-4 | PU42 | 37.55 | 23 | 2.20 | 1.79 | | | | | | | |
| CC-4 | PU43 | 38.00 | 28 | 2.01 | 1.57 | | | | | | | |
| CC-4 | PU43 | 38.30 | | | | 125 | 200 | | | | | |
| CC-4 | PU43 | 38.75 | | | | 137 | 175 | | | | | |
| CC-4 | PU44 | 39.20 | 27 | 2.10 | 1.65 | | | | | | | |
| CC-4 | PU44 | 39.40 | | | | 125 | 200 | | | | | |
| CC-4 | PU44 | 39.80 | 34 | 2.06 | 1.54 | | | | | | | |
| CC-4 | PU44 | 39.90 | | | | 100 | 150 | | | | | |
| CC-4 | PU45 | 40.00 | 27 | 2.12 | 1.67 | 200 | 300 | | | | | |
| CC-4 | PU45 | 40.40 | | | | 187 | 325 | | | | | |
| CC-4 | PU45 | 40.60 | 27 | 2.03 | 1.60 | | | | | | | |
| CC-4 | PU45 | 40.85 | | | | 175 | 300 | | | | | |
| CC-4 | PU46 | 41.20 | 29 | 2.03 | 1.57 | 150 | 325 | | | | | |
| CC-4 | PU46 | 41.60 | 27 | 2.06 | 1.62 | 172 | 200 | | | | | |


PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | PU47 | 44.00 | 31 | 1.93 | 1.47 | | 325 | | | | | |
| CC-4 | PU47 | 44.40 | | | | | 325 | | | | | |
| CC-4 | PU48 | 46.20 | 31 | 1.92 | 1.47 | | 275 | | | | | |
| CC-4 | PU48 | 46.60 | 32 | 1.91 | 1.45 | | 325 | | | | | |
| CC-4 | PU49 | 50.20 | 34 | 2.02 | 1.51 | | 350 | | | | | |
| CC-4 | PU49 | 50.60 | 36 | 2.03 | 1.49 | | 350 | | | | | |
| CC-4 | PU50 | 51.30 | 27 | 2.00 | 1.57 | | 275 | | | | | |
| CC-4 | PU50 | 51.50 | | | | | 250 | | | | | |
| CC-4 | PU51 | 55.10 | 33 | 2.06 | 1.55 | | 350 | | | | | |
| CC-4 | PU51 | 55.50 | | | | | 300 | | | | | |
| CC-4 | PU51 | 55.70 | 34 | 2.03 | 1.51 | | | | | | | |
| CC-4 | PU52 | 56.20 | 29 | 2.00 | 1.55 | | 400 | | | | | |
| CC-4 | PU52 | 56.55 | 31 | 2.00 | 1.53 | | 375 | | | | | |
| CC-4 | PU53 | 60.70 | 30 | 2.07 | 1.59 | | 400 | | | | | |
| CC-4 | PU53 | 60.90 | | | | | 400 | | | | | |
| CC-4 | PU53 | 61.10 | 27 | 2.05 | 1.61 | | 400 | | | | | |
| CC-4 | PU54 | 61.50 | 34 | 2.08 | 1.55 | | 400 | | | | | |
| CC-4 | PU54 | 61.70 | | | | | 400 | | | | | |
| CC-4 | PU54 | 62.10 | 28 | 2.12 | 1.66 | | 400 | | | | | |
| CC-4 | PU55 | 65.70 | | | | | 300 | | | | | |
| CC-4 | PU55 | 65.75 | 32 | 2.04 | 1.55 | | | | | | | |
| CC-4 | PU55 | 65.95 | | | | | 325 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

¹ Local Geodetic Datum: Gauss-Boaga Fuso W, Actual Coordinates

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-4 | PU56 | 66.50 | 27 | 2.05 | 1.61 | | | | | | | |
| CC-4 | PU56 | 66.70 | | | | | 325 | | | | | |
| CC-4 | PU56 | 67.10 | 26 | 2.04 | 1.62 | | 375 | | | | | |
| CC-4 | PU57 | 70.50 | 28 | 2.04 | 1.59 | | 300 | | | | | |
| CC-4 | PU57 | 71.15 | 30 | 2.01 | 1.55 | | 425 | | | | | |
| CC-4 | PU57 | 71.35 | | | | | 300 | | | | | |
| CC-4 | PU58 | 71.50 | 31 | 1.98 | 1.51 | | | | | | | |
| CC-4 | PU58 | 71.70 | | | | | 425 | | | | | |
| CC-4 | PU58 | 71.90 | | | | | 350 | | | | | |
| CC-4 | PU58 | 72.10 | 28 | 2.05 | 1.60 | | | | | | | |
| CC-4 | PU59 | 75.50 | | | | | 350 | | | | | |
| CC-4 | PU59 | 75.70 | 27 | 2.04 | 1.61 | | | | | | | |
| CC-4 | PU59 | 75.90 | | | | | 450 | | | | | |
| CC-4 | PU59 | 76.10 | 25 | 2.04 | 1.63 | | | | | | | |
| CC-4 | PU59 | 76.50 | | | | | 425 | | | | | |
| CC-4 | PU60 | 76.50 | 25 | 2.08 | 1.66 | | | | | | | |
| CC-4 | PU60 | 76.70 | 27 | 2.10 | 1.65 | | 425 | | | | | |
| CC-4 | PU60 | 77.10 | 26 | 2.09 | 1.66 | | | | | | | |
| CC-4 | PU60 | 77.30 | | | | | 425 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-5 | P01 | 0.10 | 26 | 1.83 | 1.46 | | | | | | | |
| CC-5 | P01 | 0.55 | 23 | 1.88 | 1.53 | | | | | | | |
| CC-5 | P02 | 1.10 | 27 | 1.81 | 1.42 | | | | | | | |
| CC-5 | P02 | 1.50 | 26 | 1.91 | 1.51 | | | | | | | |
| CC-5 | P03 | 2.10 | 29 | 1.95 | 1.51 | | | | | | | |
| CC-5 | P03 | 2.60 | 30 | 1.84 | 1.42 | | | | | | | |
| CC-5 | P04 | 3.75 | 12 | | | | | | | | | |
| CC-5 | P05 | 4.10 | 31 | 1.88 | 1.43 | | | | | | | |
| CC-5 | P05 | 4.60 | 28 | 1.90 | 1.49 | | | | | | | |
| CC-5 | P06 | 5.10 | 31 | 1.85 | 1.42 | | | | | | | |
| CC-5 | P06 | 5.60 | 27 | 1.86 | 1.47 | | | | | | | |
| CC-5 | P07 | 6.10 | 30 | 1.87 | 1.43 | | | | | | | |
| CC-5 | P07 | 6.60 | 28 | 1.82 | 1.43 | | | | | | | |
| CC-5 | P08 | 7.10 | 30 | 2.04 | 1.57 | | | | | | | |
| CC-5 | P08 | 7.50 | 30 | 1.80 | 1.38 | | | | | | | |
| CC-5 | P09 | 8.10 | 31 | 1.68 | 1.28 | | | | | | | |
| CC-5 | P09 | 8.55 | 25 | | | | | | | | | |
| CC-5 | P10 | 9.80 | 30 | | | | | | | | | |
| CC-5 | P11 | 10.10 | 29 | 1.83 | 1.42 | | | | | | | |
| CC-5 | P11 | 10.50 | 29 | 1.71 | 1.33 | | | | | | | |
| CC-5 | P12 | 11.10 | 32 | 2.05 | 1.55 | | | | | | | |
| CC-5 | P12 | 11.50 | 33 | 1.82 | 1.37 | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-5 | P12 | 11.80 | 31 | 1.78 | 1.35 | | | | | | | |
| CC-5 | P13 | 12.00 | 30 | 1.94 | 1.49 | | | | | | | |
| CC-5 | P13 | 12.25 | 32 | 1.96 | 1.48 | | | | | | | |
| CC-5 | P13 | 12.60 | 55 | 2.05 | 1.32 | | | | | | | |
| CC-5 | P14 | 13.10 | 52 | 2.00 | 1.32 | | | | | | | |
| CC-5 | P14 | 13.40 | 53 | 2.09 | 1.37 | | | | | | | |
| CC-5 | P15 | 14.20 | 59 | 1.98 | 1.25 | | | | | | | |
| CC-5 | P16 | 14.60 | 26 | | | | | | | | | |
| CC-5 | P17 | 15.10 | 17 | | | | | | | | | |
| CC-5 | PU18 | 15.55 | 7 | | | | | | | | | |
| CC-5 | CR19 | 15.70 | 25 | | | | | | | | | |
| CC-5 | PU20 | 16.55 | 3 | | | | | | | | | |
| CC-5 | CR21C | 17.20 | 6 | | | | | | | | | |
| CC-5 | PU23 | 18.60 | 8 | | | | | | | | | |
| CC-5 | PU24 | 19.10 | 8 | | | | | | | | | |
| CC-5 | CR28 | 20.70 | 17 | | | | | | | | | |
| CC-5 | CR29 | 21.15 | 8 | | | | | | | | | |
| CC-5 | CR31 | 22.05 | | 2.59 | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|
| <p>Client: TECHNITAL S.p.A and Modimar S.r.l</p> <p>Project Name: Genoa Port (PFTE)</p> <p>Project Number: GMOP20-G-013</p> | <p>Location: Genoa Port</p> |  |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-6 | P01 | 0.80 | 29 | | | | | | | | | |
| CC-6 | P02 | 1.80 | 33 | | | | | | | | | |
| CC-6 | P03 | 8.20 | 30 | 1.91 | 1.47 | | | | | | | |
| CC-6 | P03 | 8.40 | 29 | 2.00 | 1.55 | | | | | | | |
| CC-6 | P03 | 8.80 | 35 | | | | | | | | | |
| CC-6 | P04 | 9.20 | 35 | 1.90 | 1.41 | | | | | | | |
| CC-6 | P04 | 9.40 | 32 | | | | | | | | | |
| CC-6 | P04 | 9.60 | 32 | 1.91 | 1.44 | | | | | | | |
| CC-6 | P05 | 16.15 | 33 | 1.90 | 1.43 | | | | | | | |
| CC-6 | P05 | 16.30 | 30 | | | | | | | | | |
| CC-6 | P05 | 16.45 | 30 | 1.90 | 1.47 | | | | | | | |
| CC-6 | P06 | 17.25 | 33 | 1.84 | 1.38 | | | | | | | |
| CC-6 | P06 | 17.45 | 33 | | | | | | | | | |
| CC-6 | P06 | 17.60 | 31 | 1.93 | 1.47 | | | | | | | |
| CC-6 | P07A | 24.05 | 19 | | | | | | | | | |
| CC-6 | P07A | 24.20 | 18 | | | | | | | | | |
| CC-6 | P08 | 24.60 | 30 | | | | | | | | | |
| CC-6 | P08 | 24.70 | 30 | 2.01 | 1.55 | 212 | 275 | | | | | |
| CC-6 | P08 | 24.90 | | | | | 250 | | | | | |
| CC-6 | P09 | 25.85 | 31 | | | 162 | 200 | | | | | |
| CC-6 | P10 | 32.00 | 37 | 1.89 | 1.38 | | | | | | | |
| CC-6 | P10 | 32.25 | | | | 212 | 250 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-6 | P10 | 32.45 | 34 | 2.00 | 1.49 | | | | | | | |
| CC-6 | P10 | 32.70 | | | | | 375 | | | | | |
| CC-6 | P10 | 32.90 | | | | | 250 | | | | | |
| CC-6 | P11 | 33.10 | | | | 200 | 250 | | | | | |
| CC-6 | P11 | 33.35 | 37 | 1.98 | 1.45 | | | | | | | |
| CC-6 | P11 | 33.55 | | | | 250 | 200 | | | | | |
| CC-6 | P12 | 39.50 | 36 | 1.94 | 1.43 | 187 | 250 | | | | | |
| CC-6 | P12 | 39.90 | | | | 200 | 275 | | | | | |
| CC-6 | P12 | 40.00 | 35 | 1.95 | 1.44 | | | | | | | |
| CC-6 | P12 | 40.20 | | | | 200 | 300 | | | | | |
| CC-6 | P13 | 40.50 | 41 | 2.01 | 1.43 | | 375 | | | | | |
| CC-6 | P13 | 41.00 | 32 | 1.95 | 1.48 | | 450 | | | | | |
| CC-6 | P13 | 41.40 | | | | | 450 | | | | | |
| CC-6 | P14 | 47.50 | | 2.08 | | | 325 | | | | | |
| CC-6 | P14 | 47.70 | | 2.11 | | | 350 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-7 | P01 | 0.15 | 51 | | | 1 | | | | | | |
| CC-7 | P01 | 0.55 | 48 | 1.71 | 1.16 | 1 | | | | | | |
| CC-7 | P02 | 1.20 | 41 | 1.81 | 1.28 | 6 | | | | | | |
| CC-7 | P02 | 1.60 | | | | 7 | | 7 | 3 | | | |
| CC-7 | P03 | 2.20 | 43 | 1.78 | 1.24 | 2 | | | | | | |
| CC-7 | P03 | 2.60 | 77 | 1.72 | 0.97 | 7 | | | | | | |
| CC-7 | P04 | 3.20 | 40 | 1.79 | 1.28 | | | | | | | |
| CC-7 | P04 | 3.40 | | | | 10 | | | | | | |
| CC-7 | P04 | 3.85 | | | | 9 | | 6 | 2 | | | |
| CC-7 | P04 | 3.60 | 41 | 1.82 | 1.29 | | | | | | | |
| CC-7 | P05 | 4.25 | 54 | 1.92 | 1.25 | 40 | 75 | | | | | |
| CC-7 | P05 | 4.65 | 36 | 2.01 | 1.48 | | | | | | | |
| CC-7 | P06 | 5.05 | 33 | | | | | | | | | |
| CC-7 | P06 | 5.30 | 32 | 1.88 | 1.42 | | | | | | | |
| CC-7 | P06 | 5.70 | 31 | 1.92 | 1.47 | | | | | | | |
| CC-7 | P07 | 6.20 | 31 | 2.18 | 1.66 | | | | | | | |
| CC-7 | P07 | 6.60 | 33 | 2.10 | 1.58 | | | | | | | |
| CC-7 | PU08B | 7.10 | 22 | 1.87 | 1.53 | | | | | | | |
| CC-7 | PU11 | 8.50 | 21 | | | | | | | | | |
| CC-7 | PU11 | 8.60 | 11 | | | | | | | | | |
| CC-7 | PU12 | 9.00 | 47 | 1.74 | 1.18 | 40 | | | | | | |
| CC-7 | PU12 | 9.05 | | | | | 63 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|
| <p>Client: TECHNITAL S.p.A and Modimar S.r.l</p> <p>Project Name: Genoa Port (PFTE)</p> <p>Project Number: GMOP20-G-013</p> | <p>Location: Genoa Port</p> |  |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-7 | PU12 | 9.20 | 43 | 1.85 | 1.29 | | 50 | | | | | |
| CC-7 | PU12 | 9.25 | | | | 45 | | | | | | |
| CC-7 | PU13 | 3.75 | | | | | 188 | | | | | |
| CC-7 | PU13 | 9.60 | 37 | 1.68 | 1.23 | 100 | | | | | | |
| CC-7 | PU13 | 1.75 | | | | | 175 | | | | | |
| CC-7 | PU13 | 9.90 | | | | 87 | | | | | | |
| CC-7 | P14 | 10.20 | | | | 100 | 88 | | | | | |
| CC-7 | P14 | 10.40 | 39 | 1.91 | 1.37 | | | | | | | |
| CC-7 | P14 | 10.55 | | | | 100 | 150 | | | | | |
| CC-7 | P15 | 10.80 | | | | | 125 | | | | | |
| CC-7 | P15 | 11.80 | 33 | | | 162 | | | | | | |
| CC-7 | P16 | 12.20 | 33 | 1.95 | 1.47 | 85 | 163 | | | | | |
| CC-7 | P16 | 12.40 | 32 | 1.93 | 1.46 | | | | | | | |
| CC-7 | P16 | 12.55 | | | | 70 | 250 | | | | | |
| CC-7 | P17 | 13.25 | | | | 88 | 200 | | | | | |
| CC-7 | P17 | 13.70 | 32 | 1.90 | 1.44 | | | | | | | |
| CC-7 | P17 | 13.95 | | | | 87 | 150 | 86 | 45 | | | |
| CC-7 | P18 | 14.00 | 35 | 1.99 | 1.47 | 100 | 213 | | | | | |
| CC-7 | P18 | 14.25 | | | | 112 | 225 | | | | | |
| CC-7 | P19 | 15.25 | 32 | 1.97 | 1.49 | 150 | 163 | | | | | |
| CC-7 | P19 | 15.65 | 31 | 1.99 | 1.52 | 162 | | | | | | |
| CC-7 | P19 | 15.75 | | | | | 188 | | | | | |


PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-7 | P19 | 15.90 | | | | | 200 | | | | | |
| CC-7 | P19 | 15.95 | | | | 188 | | | | | | |
| CC-7 | P20 | 16.25 | 34 | 2.03 | 1.51 | 187 | 200 | | | | | |
| CC-7 | P20 | 16.70 | | | | 200 | 225 | | | | | |
| CC-7 | P21 | 17.10 | | | | 162 | 175 | | | | | |
| CC-7 | P21 | 17.20 | 30 | 1.99 | 1.53 | | | | | | | |
| CC-7 | P21 | 17.60 | 30 | 1.93 | 1.48 | 175 | 188 | | | | | |
| CC-7 | P21 | 17.85 | | | | | | 83 | 58 | | | |
| CC-7 | P21 | 17.90 | | | | 175 | 175 | | | | | |
| CC-7 | P22 | 18.30 | 29 | 1.96 | 1.52 | 150 | 138 | | | | | |
| CC-7 | P22 | 18.70 | 30 | 1.95 | 1.50 | 112 | 125 | | | | | |
| CC-7 | P23 | 19.10 | 30 | 2.04 | 1.57 | 150 | 225 | | | | | |
| CC-7 | P23 | 19.11 | | | | | 250 | | | | | |
| CC-7 | P23 | 19.55 | | 1.97 | 1.88 | | | | | | | |
| CC-7 | P23 | 19.95 | | | | 125 | 175 | 93 | 61 | | | |
| CC-7 | P23 | 19.96 | | | | | 200 | | | | | |
| CC-7 | P23 | 20.00 | 31 | | | | | | | | | |
| CC-7 | P24 | 20.20 | 50 | 2.02 | 1.35 | 150 | 250 | | | | | |
| CC-7 | P24 | 20.60 | 34 | 1.99 | 1.49 | | | | | | | |
| CC-7 | P24 | 20.90 | | | | 162 | 250 | | | | | |
| CC-7 | P25 | 21.10 | 33 | 1.99 | 1.50 | 125 | 150 | | | | | |
| CC-7 | P25 | 21.70 | 33 | 2.01 | 1.51 | 137 | 175 | | | | | |


PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

¹ Local Geodetic Datum: Gauss-Boaga Fuso W, Actual Coordinates

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-7 | P25 | 21.90 | | | | 125 | | | | | | |
| CC-7 | P26 | 22.20 | 33 | 2.05 | 1.54 | 175 | 250 | | | | | |
| CC-7 | P26 | 22.60 | | | | 187 | 225 | | | | | |
| CC-7 | P27 | 23.05 | 37 | 2.16 | 1.58 | 175 | 220 | | | | | |
| CC-7 | P27 | 23.55 | 33 | 1.95 | 1.47 | 187 | 225 | | | | | |
| CC-7 | P28 | 24.10 | 35 | 1.99 | 1.47 | 225 | 250 | | | | | |
| CC-7 | P28 | 21.85 | | | | | | 100 | 63 | | | |
| CC-7 | P28 | 24.70 | 36 | 1.93 | 1.42 | 212 | 225 | | | | | |
| CC-7 | P29 | 25.05 | 39 | 1.88 | 1.35 | 162 | 200 | | | | | |
| CC-7 | P29 | 25.40 | | 1.90 | | 175 | 225 | | | | | |
| CC-7 | P29 | 26.00 | | | | 175 | | | | | | |
| CC-7 | P30 | 26.20 | 36 | 1.90 | 1.40 | 150 | 220 | | | | | |
| CC-7 | P30 | 26.60 | 36 | 1.97 | 1.45 | 175 | 225 | | | | | |
| CC-7 | P31 | 27.05 | | 1.96 | | | | | | | | |
| CC-7 | P31 | 27.20 | | | | 175 | 200 | | | | | |
| CC-7 | P31 | 27.80 | 36 | 1.99 | 1.46 | 200 | 225 | | | | | |
| CC-7 | P31 | 27.95 | | | | 200 | | | | | | |
| CC-7 | P32 | 28.20 | 31 | 2.04 | 1.56 | 187 | 225 | | | | | |
| CC-7 | P32 | 28.60 | | | | 200 | 225 | | | | | |
| CC-7 | P33 | 29.00 | 31 | 1.96 | 1.50 | | | | | | | |
| CC-7 | P33 | 29.20 | | | | 212 | 275 | | | | | |
| CC-7 | P33 | 29.40 | | 2.00 | | | 275 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-7 | P33 | 29.60 | | | | 225 | 330 | | | | | |
| CC-7 | P33 | 29.75 | 31 | | | | | | | | | |
| CC-7 | P34 | 30.00 | 29 | 2.00 | 1.55 | | 425 | | | | | |
| CC-7 | P34 | 30.60 | 30 | | | | | | | | | |
| CC-7 | P35 | 31.20 | 29 | 2.01 | 1.56 | | 500 | | | | | |
| CC-7 | P35 | 31.80 | | 2.04 | | | 400 | | | | | |
| CC-7 | P36 | 32.20 | 48 | 2.01 | 1.36 | | 350 | | | | | |
| CC-7 | P36 | 32.60 | 47 | 1.97 | 1.34 | | 350 | | | | | |
| CC-7 | P37 | 33.00 | 35 | 1.98 | 1.47 | | | | | | | |
| CC-7 | P37 | 33.40 | 34 | 1.94 | 1.45 | | 325 | | | | | |
| CC-7 | P37 | 33.80 | | | | | 300 | | | | | |
| CC-7 | P38 | 34.20 | 35 | 1.95 | 1.44 | | 275 | | | | | |
| CC-7 | P38 | 34.60 | 36 | 1.97 | 1.45 | | 300 | | | | | |
| CC-7 | P39 | 35.00 | 35 | 1.93 | 1.43 | | 275 | | | | | |
| CC-7 | P39 | 35.40 | 33 | 2.03 | 1.53 | | 300 | | | | | |
| CC-7 | P40 | 36.00 | 33 | 2.00 | 1.50 | | | | | | | |
| CC-7 | P40 | 36.20 | | | | | 300 | | | | | |
| CC-7 | P40 | 36.40 | 32 | 1.96 | 1.48 | | | | | | | |
| CC-7 | P40 | 36.80 | | | | | 325 | | | | | |
| CC-7 | P41 | 37.10 | 31 | 2.05 | 1.56 | | 350 | | | | | |
| CC-7 | P41 | 37.20 | 32 | 2.02 | 1.53 | | | | | | | |
| CC-7 | P41 | 37.50 | 30 | 2.06 | 1.58 | | 350 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| CC-7 | P43 | 38.39 | | | | | 88 | | | | | |
| CC-7 | P43 | 38.40 | 34 | 1.89 | 1.41 | | 100 | | | | | |
| CC-7 | P43 | 38.50 | | | | 65 | | | | | | |
| CC-7 | P44 | 39.35 | 33 | 1.83 | 1.38 | 55 | 50 | | | | | |
| CC-7 | P44 | 39.55 | | | | 55 | 63 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| PCPT-5 | H01 | 36.65 | 28 | | | | | | | | | |
| PCPT-5 | H01 | 36.80 | 26 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| PCPT-6 | PU02 | 39.70 | 31 | 1.98 | 1.51 | | | | | | | |
| PCPT-6 | PU03 | 46.60 | 35 | | | | | | | | | |
| PCPT-6 | PU03 | 46.90 | 36 | | | | | | | | | |
| PCPT-6 | PU03 | 47.20 | 38 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| PCPT-6A | P01 | 45.10 | 31 | 1.99 | 1.52 | | 375 | | | | | |
| PCPT-6A | P01 | 45.50 | 30 | 2.01 | 1.55 | | 375 | | | | | |
| PCPT-6A | P02 | 55.20 | 31 | 1.98 | 1.51 | | 350 | | | | | |
| PCPT-6A | P02 | 55.60 | 32 | 2.02 | 1.53 | | 350 | | | | | |
| PCPT-6A | P02 | 55.85 | | | | | 300 | | | | | |
| PCPT-6A | P03 | 65.20 | 33 | 2.01 | 1.51 | | 350 | | | | | |
| PCPT-6A | P03 | 65.40 | | | | | 375 | | | | | |
| PCPT-6A | P03 | 65.60 | 32 | 1.97 | 1.49 | | 350 | | | | | |
| PCPT-6A | P04 | 75.20 | 32 | 1.99 | 1.51 | | 400 | | | | | |
| PCPT-6A | P04 | 75.40 | 30 | 1.99 | 1.53 | | 450 | | | | | |
| PCPT-6A | P04 | 75.60 | | | | | 450 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| PCPT-7 | CR08B | 9.55 | 10 | | | | | | | | | |
| PCPT-7 | CR09 | 10.60 | 1 | 2.52 | 2.50 | | | | | | | |
| PCPT-7 | CR09 | 10.80 | 6 | | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| PCPT-8 | P01 | 0.05 | 63 | | | | | | | | | |
| PCPT-8 | P01 | 0.20 | 58 | 1.66 | 1.05 | 6 | | | | | | |
| PCPT-8 | P01 | 0.50 | | | | 9 | | | | | | |
| PCPT-8 | P01 | 0.70 | 56 | 1.81 | 1.16 | | | | | | | |
| PCPT-8 | P01 | 0.90 | | | | 10 | | | | | | |
| PCPT-8 | P02 | 1.10 | | | | 9 | | | | | | |
| PCPT-8 | P02 | 1.50 | 45 | 1.60 | 1.10 | 12 | | | | | | |
| PCPT-8 | P02 | 1.90 | | | | 10 | | 12 | 3 | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|-------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l | Location: Genoa Port |  |
| Project Name: Genoa Port (PFTE) | | |
| Project Number: GMOP20-G-013 | | |

| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| PCPT-8A | P01 | 0.30 | 63 | | | 2 | | | | | | |
| PCPT-8A | P01 | 0.60 | 58 | | | 6 | | | | | | |
| PCPT-8A | P01 | 0.80 | | | | 7 | | | | | | |
| PCPT-8A | P02 | 1.15 | 50 | 1.91 | 1.27 | 7 | | | | | | |
| PCPT-8A | P02 | 1.35 | | | | 8 | | | | | | |
| PCPT-8A | P02 | 1.55 | 56 | | | 7 | | | | | | |
| PCPT-8A | P02 | 1.85 | | | | | | 4 | 0 | | | |
| PCPT-8A | P03 | 2.20 | 46 | | | | | | | | | |
| PCPT-8A | P03 | 2.30 | | | | 14 | | | | | | |
| PCPT-8A | P03 | 2.40 | 47 | | | | | | | | | |
| PCPT-8A | P03 | 2.70 | 46 | 1.84 | 1.26 | 12 | | | | | | |
| PCPT-8A | P04 | 7.60 | 34 | 1.87 | 1.40 | | | | | | | |
| PCPT-8A | P04 | 8.20 | 30 | 1.99 | 1.53 | | | | | | | |
| PCPT-8A | P05 | 8.60 | 30 | 1.91 | 1.47 | | | | | | | |
| PCPT-8A | P05 | 9.20 | 33 | 1.86 | 1.39 | | | | | | | |
| PCPT-8A | P06 | 15.70 | 20 | 2.13 | 1.78 | 100 | 113 | | | | | |
| PCPT-8A | P06 | 16.30 | 29 | 2.07 | 1.60 | 137 | 150 | | | | | |
| PCPT-8A | P07 | 16.60 | 27 | 2.04 | 1.61 | 112 | 138 | | | | | |
| PCPT-8A | P07 | 17.20 | 24 | 2.06 | 1.66 | 100 | 138 | | | | | |
| PCPT-8A | P07 | 17.40 | | | | 150 | 113 | 132 | 47 | | | |
| PCPT-8A | P08 | 23.70 | 27 | 2.11 | 1.66 | 112 | 138 | | | | | |
| PCPT-8A | P08 | 24.20 | 24 | 2.11 | 1.70 | 162 | 163 | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

| | | |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|
| Client: TECHNITAL S.p.A and Modimar S.r.l Project Name: Genoa Port (PFTE) Project Number: GMOP20-G-013 | Location: Genoa Port |  |
|--------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------|


| Borehole / Location | Sample No. | Test Depth (m) | Moisture Content (%) | Bulk Density (Mg/m ³) | Dry Density (Mg/m ³) | Torvane Su (kPa) | PP Su (kPa) | Lab Vane Peak Su (kPa) | Lab Vane Residual Su (kPa) | UU Su _{UU} (kPa) | UU ϵ_{50} (%) | Thermal Conductivity (w/mK) |
|---------------------|------------|----------------|----------------------|-----------------------------------|----------------------------------|------------------|-------------|------------------------|----------------------------|---------------------------|------------------------|-----------------------------|
| PCPT-8A | P08 | 24.40 | | | | 100 | 113 | | | | | |
| PCPT-8A | P09 | 24.50 | 23 | 2.05 | 1.67 | | | | | | | |
| PCPT-8A | P09 | 24.75 | | | | 187 | 175 | | | | | |
| PCPT-8A | P09 | 25.00 | 22 | 2.18 | 1.79 | | | | | | | |
| PCPT-8A | P09 | 25.25 | | | | 175 | 163 | | | | | |
| PCPT-8A | P09 | 25.45 | | | | 162 | 138 | 144 | 44 | | | |
| PCPT-8A | PU10A | 31.60 | 11 | 2.11 | 1.89 | | | | | | | |
| PCPT-8A | PU15 | 40.55 | | 1.72 | | | | | | | | |

PP - Pocket Penetrometer UU - Undrained Unconsolidated Triaxial ϵ_{50} - Strain at half max. deviator stress

Appendix B.2 Strength Tests

Client: TECHNITAL S.p.A
 Project Name: Genoa Port (PFTE)
 Project Number: GMOP20-G-013

Location: Genoa Port
 Borehole No.: CC-2



Before Test Photo

After Test Photo



| | | | | |
|-------------------|------------------------|-------------------------------------|------------------------|-----------------------|
| Sample Ref.: P06 | Cell Pressure: 365kPa | Bulk Density: 1.82Mg/m ³ | Water Content: 21% | Strain at Failure: 4% |
| Test Depth: 5.30m | Rate of Strain: 1%/min | Dry Density: 1.50Mg/m ³ | Test Type: Undisturbed | Shear Strength: 8kPa |

UNCONSOLIDATED UNDRAINED TRIAXIAL TEST

Ref.: GMOP20-G-013-FLD-01

Client: TECHNITAL S.p.A
 Project Name: Genoa Port (PFTE)
 Project Number: GMOP20-G-013

Location: Genoa Port
 Borehole No.: CC-3



Before Test Photo

After Test Photo

| | | | | |
|-------------------|------------------------|-------------------------------------|------------------------|------------------------|
| Sample Ref.: P09 | Cell Pressure: 580kPa | Bulk Density: 1.76Mg/m ³ | Water Content: 42% | Strain at Failure: 20% |
| Test Depth: 8.40m | Rate of Strain: 1%/min | Dry Density: 1.24Mg/m ³ | Test Type: Undisturbed | Shear Strength: 11kPa |

UNCONSOLIDATED UNDRAINED TRIAXIAL TEST

Ref.: GMOP20-G-013-FLD-01

APPENDIX C METHODOLOGIES AND PROCEDURES

C.1 Soil Classification and Description Methodologies

Overview

Soil classifications and descriptions are based on the requirements as outlined by ISO 19901-8. This is further detailed below.

Classification and Description

Soil descriptions and classification are completed as per contractual requirements utilising the following standards:

- For primary fractions:
 - BS EN ISO 14688-1:2018 Geotechnical investigation and testing – Identification and classification of soil – Part 1: Identification and description
 - BS EN ISO 14688-2:2018 Geotechnical investigation and testing – Identification and classification of soil – Part 2: Principles for a classification
- For secondary/tertiary fractions:
 - BS 5930:2015 Code of practice for ground investigation

Strength Descriptions

Undrained Shear Strength descriptors are summarised in the following table (after ISO 14688-2):

| Term | Undrained shear strength s_u, kPa |
|----------------|-----------------------------------------------------------|
| Extremely low | <10 |
| Very low | 10 to 20 |
| Low | 20 to 40 |
| Medium | 40 to 75 |
| High | 75 to 150 |
| Very high | 150 to 300 |
| Extremely high | >300 |

Where undrained shear strengths of cohesive materials cannot be measured, a consistency based on hand manipulation can be applied (after ISO 14688-1):

| Term | Field Assessment |
|-------------|--------------------------------------------------|
| Very soft | Exudes between the fingers when squeezed in hand |
| Soft | Soil can be moulded by light finger pressure |
| Firm | Thumb makes an impression easily |
| Stiff | Soil can be indented slightly by thumb |
| Very Stiff | Soil can be indented by thumb nail |

Relative Density Descriptions are based on the following table (after Lunne and Christoffersen, 1983):

| Term | Relative Density (%) |
|--------------|----------------------|
| Very loose | 0 to 15 |
| Loose | 15 to 35 |
| Medium dense | 35 to 65 |
| Dense | 65 to 85 |
| Very dense | 85 to 100 |

Secondary fraction

The following descriptions for secondary fraction are used which is partially based on BS5930:

| Principal material | Term of secondary material | Proportion of Secondary ^{A)} |
|-----------------------|---------------------------------------|---------------------------------------|
| Coarse (0.063 – 63mm) | slightly (sandy) ^{B)} | <5% |
| | (sandy) ^{B)} | 5-20% ^{C)} |
| | very (sandy) ^{B)} | >20 ^{C)} |
| | SAND and GRAVEL | About 50% |
| Fine (<0.063mm) | slightly (sandy) ^{D)} | <35% |
| | (sandy) ^{D)} | 35-65% ^{E)} |
| | very (sandy) ^{F)} | >65% ^{E)} |
| | Silty CLAY/ Clayey SILT ^{G)} | - |

- A. Percentage coarse or fine soil type assessed excluding cobbles and boulders
- B. Gravelly or sandy and/or silty or clayey
- C. Can be described as fine soil depending on mass behaviour
- D. Gravelly and/or sandy
- E. Can be described as coarse soil depending on mass behaviour
- F. Gravelly or sandy
- G. Terms used to reflect secondary fine constituents where this is important

Tertiary fraction

The following descriptions for tertiary fraction are used (after BS5930) that do not affect the engineering behaviour of the material. Proportions are defined on a site or material specific basis, or subjectively.

The following descriptions for tertiary fraction are used:

| Term | Percentage |
|----------------------------|------------|
| Rare | <10 |
| Occasional | 10-25 |
| Frequent/Abundant/Numerous | >25 |

Bedding Thicknesses

Bedding thicknesses are described on the following (after ISO 14688-1):

| Term | Thickness of bedding (mm) |
|---------------------|----------------------------------|
| Thinly laminated | <6 |
| Thickly laminated | 6 to 20 |
| Very thinly bedded | 20 to 60 |
| Thinly bedded | 60 to 200 |
| Medium bedded | 200 to 600 |
| Thickly bedded | 600 to 2000 |
| Very thickly bedded | >2000 |

Particle Size Distribution – Fractions

The description of particle sizes is based on the results of sieve and hydrometer results (after ISO 14688-1) as follows:

| Soil Group | Particle Size Fractions | Range of Particle Sizes (mm) |
|-------------------|--------------------------------|-------------------------------------|
| Coarse Soil | Coarse Gravel | 20 to 63 |
| | Medium Gravel | 6.3 to 20 |
| | Fine Gravel | 2.0 to 6.3 |
| | Coarse Sand | 0.63 to 2.0 |
| | Medium Sand | 0.2 to 0.63 |
| | Fine Sand | 0.063 to 0.2 |
| Fine Soil | Coarse Silt | 0.02 to 0.063 |
| | Medium Silt | 0.0063 to 0.02 |
| | Fine Silt | 0.002 to 0.0063 |
| | Clay | <0.002 |

Spacing of discontinuities

Bedding thicknesses are described in the following fashion (after BS5930:2015 Table 7):

| Term | Thickness of bedding (mm) |
|-------------------|----------------------------------|
| Extremely closely | <20 |
| Very closely | 20 to 60 |
| Closely | 60 to 200 |
| Medium | 200-600 |
| Widely | 600-2000 |
| Very widely | >2000 |

C.2 Rock Core Handling and Rock Core Logging Methodologies

Overview

Soil classifications and descriptions are based on the requirements as outlined by the relevant BSI Standards. This is further detailed below.

Classification and Description

Rock descriptions and classification are completed as per contractual requirements utilising BS5930:2015 Code of practise for ground investigations

Descriptive Terms

| Strength | Extremely Weak | Very Weak | Weak | Medium Strong | Strong | Very Strong | Extremely Strong |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|----------------------------------------------------------|------------------------------------------------------------|------------------------------------|---------------------------------------------------------------|
| Range | 0.6 – 1.0MPa | 1 – 5MPa | 5 - 25MPa | 25 - 50 MPa | 50 – 100 MPa | 100 - 250 MPa | >250MPa |
| Strength | Gravel size lumps can be crushed between finger and thumb | Gravel size lumps can be broken in half by heavy hand pressure | Only thin slabs, corners or edges can be broken off with heavy hand pressure | When held in the hand rock can be broken by hammer blows | When resting on surface rock can be broken by hammer blows | Rock chipped by heavy hammer blows | Rock rings on hammer blows, only chipped by geological hammer |
| Structure | Sedimentary | Thinly – thickly laminated, very thinly – thickly bedded, Cross bedded, Graded bedding, Slumped Bedding Styolitic, (this list is not exhaustive, see BS5930) The term banded is not sedimentary and is not to be used | | | | | |
| | Metamorphic | Foliated, Schistose, Crenulated, Gneissose, Banded, Flow banded (this list is not exhaustive, see BS5930) | | | | | |
| | Igneous | Massive Graphic, Orbicular, Flow banded, Flow aligned, Amygdaloidal, Vesicular, (this list is not exhaustive, see BS5930) | | | | | |
| Colour | If available a Munsell Colour Chart should be used to ascribe a Munsell number to the colour. Include laminated colour and mottling | | | | | | |
| Texture | Sedimentary | Relates to the relationship of individual rock mass grains and may include, Fine, medium, coarse, grained, locally conglomeratic, locally brecciated, pelloidial, oolitic (this list is not exhaustive, see BS5930) | | | | | |
| | Metamorphic | Granulose, Augen, Flow aligned, Microcrystalline, Glassy, Cryptocrystalline (this list is not exhaustive, see BS5930) | | | | | |
| | Igneous | Porphyritic, Megacrystic, Microcrystalline, Glassy, Cryptocrystalline (this list is not exhaustive, see BS5930) | | | | | |
| Grain Size | Fine, medium, coarse grained (sandstone, carbonate rocks, crystalline nature: igneous, metamorphic rocks), see BS5930 Table 14 for more detail. | | | | | | |
| Rock Name | As appropriate for the overall description, (see BS5930, Table 14 for more detail) | | | | | | |

Grain Size

Grain Size is particularly important for the description and classification of Sedimentary and Metamorphic rocks. Grain size refers to the average dimension of the primary constituent. Separate measurements of the grain and matrix may be necessary. (after BS EN ISO 14688-2):

| Term | Grain Size |
|--------------------------|-------------------|
| Coarse Grained | > 2 mm |
| Medium to Coarse Grained | 0.63 to 2 mm |
| Medium Grained | 0.2 to 0.63 mm |
| Medium to Fine Grained | 0.063 to 0.2 mm |
| Fine Grained | 0.002 to 0.063 mm |
| Amorphous | < 0.002 mm |

Minor Constituents

The following minor constituents descriptors are summarised in the following table (after BS EN ISO 14688-2):

| Term |
|-------------|
| Rare |
| Occasional |
| Frequent |
| Vugs |
| Shells |
| Pyrite |
| Crystals |
| Organics |
| Colours |
| Odours |

Weathering

Weathering is described based on Figure 19 from BS5930.

| | | | |
|----------------------------------------------------------------------------------|-----|----------------------|----------------------------------------------------------------------------------------------------------------|
| Weathering grade / weathering, (moderately strong or stronger when fresh) | I | Fresh | Unchanged from original state |
| | II | Slightly Weathered | Slight discolouration, slight weakening |
| | III | Moderately Weathered | Considerably weakened, penetrative discolouration. Large pieces cannot be broken by hand |
| | IV | Highly Weathered | Large pieces cannot be broken by hand. Does not readily disaggregate (slake) when dry sample immersed in water |
| | V | Completely Weathered | Considerably weakened Slakes Original texture apparent |
| | VI | Residual Soil | Soil derived by in situ weathering but retaining none of the original texture or fabric |

Spacing

Spacing refers to the mean or modal spacing of a set of discontinuities and is the perpendicular distance between adjacent discontinuities. The table below indicates the terms used (BS EN ISO 14688-2):

| Measurement | Bedding Term | Discontinuities Term |
|-------------|-------------------|----------------------|
| > 2000 mm | Very Thickly | Very Widely |
| > 600 mm | Thick | Widely |
| > 200 mm | Medium | Medium |
| > 60 mm | Thin | Closely |
| > 20 mm | Very Thin | Very Closely |
| > 6 mm | Thickly Laminated | Extremely Closely |
| < 6 mm | Thinly Laminated | |

Orientation

Dip orientation is an averaged recorded value of discontinuities within the core sample (after BS EN ISO 14688-2):

| |
|------------------------------|
| Dip Direction and Dip |
| e.g. 245/70 |
| Dip amount only in cores. |

Infilling

Width, continuity and relevant characteristics of infill are recorded (after BS EN ISO 14688-2):

| Term | Typical Characteristics |
|-------------------------------------------------------------------|------------------------------------|
| Clean | |
| Surface Staining | Colouring |
| Soil Infilling | |
| Mineral Coatings | E.g. Calcite, Chlorite, Gypsum etc |
| Other | |
| Record width, continuity, and relevant characteristics of infill. | |

C.3 Offshore Laboratory Testing Methodologies

Overview

The following excerpts are from GEOQUIP procedure GM-MSP-OI-5-3-3 Offshore Sample Handling, Soil Description & Laboratory Testing. These cover the tests completed offshore.

Water Content

Moisture content tests were carried soon after recovery on samples recovered in the field.

The water content is the ratio between mass of water and mass of solids of soil.

$$w = \frac{M_w}{M_s}$$

where:

w = Water content

M_w = Mass of water

M_s = Mass of solids

The water content tests were performed according with ISO 17892-1. This test consists of a measurement of the weight of the sample before and after drying in an oven. The sample is placed in an oven at a temperature of 105 ° C (± 5 ° C) for at least 16 hours. The measurements of weight should consider the weight of the tares.

Density

Bulk (or wet) and dry density test are determined on appropriate extruded samples in the field. Densities are calculated in accordance with ISO 17892-2.

The bulk (or wet) density is the ratio between the total mass and the total volume.

$$\rho_m = \frac{M_t}{V}$$

where:

ρ_m = Bulk density of soil

M_t = Total mass of soil sample (wet)

V = Mass volumen of soil sample

The dry density was then calculated, drying the sample following the procedure of Section 4.11 or it was calculated following the next equation based on the total density and the water content.

$$\rho_d = \frac{\rho_m}{(1+w/100)}$$

where:

ρ_d = Dry density of soil

Pocket Penetrometer

This test is most accurately performed on cohesive soils from 50 to 760kPa. The results of shear strength measurements taken with a pocket penetrometer should only be used as a guide to the soil's shear strength. This test is inaccurate in the shear strength range 0 to 50kPa and greater than 760kPa, at which point the soil can essentially be considered to have become rock. The test can be susceptible to inaccuracies in cohesive soils with pockets of sand or shells. It is recommended to carry out a number of pocket penetrometer tests in one undisturbed sample.

The following outlines the method for yielding undrained shear strength results from pocket penetrometers:

- Select an area of the undisturbed sample and cut a flat face parallel to the core specimen ends
-

- Select penetrometer head size based on soil characteristics. Small head for high strength soil and normal head for lower strength soil types
- Ensuring the penetrometer scale reads zero, push the instrument at a constant rate into the specimen until the head penetrates the soil up to marker on the style. Do not push to the end of the penetrating rod
- Observe reading on penetrometer scale and record. Note that the reading is taken from the underside of the indicator
- Record results on Soil Sample Data Sheets
- The shear strength of specimen is determined from conversion tables corresponding to penetrometer size and scale reading

Unconsolidated Undrained Triaxial Tests

Undrained unconsolidated triaxial (UU) tests were conducted on cohesive soil samples to determine the undrained shear strength. These were performed both offshore and onshore on undisturbed samples in accordance with ASTM D2850. The selected specimens were trimmed so that the height to diameter ratio between 2 and then inserted into a latex membrane with a thickness of 0.38 mm. The samples were then placed into a triaxial cell and pressured with water back to near in situ conditions. An axial load is then applied to produce an axial strain rate of 1.0% per min for plastic soils and 0.3% per min for brittle soils. The tests were run until the soil has failed and dropped by 20% maximum deviator stress or 15% axial strain.

C.4 Sampling

Soil samples were obtained using conventional push tube sampling methodologies, based on GEOQUIP procedure GM-MSP-OI-5-2-9 Wireline Sampling & In Situ Testing and ISO 22475-1. Push sampling with or without using an internal piston arrangement was conducted in cohesive and non-cohesive formations.

The wireline push sampler is lowered into the drill string where it latches into the BHA. The attached sample tube was hydraulically pushed into the ground ahead of the drill bit to sample the soil. Before the push commences, the piston is located at the bottom of the sample tube preventing any ingress of drill cuttings and travels up the tube as it penetrates the ground minimising sample disturbance and maximising recovery. When the piston is not fitted the push sampler head has a hole which allows water to escape whilst penetrating the ground. After the test has completed the hole is then covered by a ball and held in place using a spring this is to prevent losing the sample when recovering the tool.

C.5 Cone Penetration Testing

Overview

In situ PCPT were performed in accordance with ISO 19901-8 (2014) using a WISON-APB wireline downhole tool with 1.5m and 3.0m stroke length tool configurations. This tool has a hydraulically controlled thrusting mechanism which pushes an instrumented cone on a rod into the soil. A data cable connects the cone to a surface acquisition computer. The pore water pressure is measured behind the tip (u_2).

To carry out a PCPT test, the hole is first drilled out to the required test depth, ensuring that all cuttings are flushed out of the hole by the drilling mud. The drill string is advanced to the required testing depth and clamped by the seabed frame to provide on bottom weight reaction for the test. At this point the first baseline reading is taken from the cone sensors at deck level. The WISON-APB tool is then lowered into the drill string on its combined hydraulic/data/lift cable until it latches into the BHA of the drill string. When the tool is correctly latched, the cone is just behind the drill bit at the bottom of the borehole.

At this point the second baseline reading is taken from the cone sensors, these are also known as the zero offsets before testing as the system zero's all the cone channels; cone resistance (q_c), sleeve friction (f_s) and pore water pressure (u_2). The test is then started by activating the hydraulic flow from the topside power pack which pushes the cone into the soil at a constant (flow controlled) rate of 2cm/s. Data is continuously recorded and displayed in real time on the surface acquisition and control computer for all cone channels. At the end of the test the drill string is lifted to pull the cone rod free from the ground and so that the cone is at the same depth as the beginning of the test when the third baseline reading is taken. The tool is then recovered from the drill string and returned to the drill deck using the umbilical winch. Once safely back on deck the final baseline reading is taken. The baseline readings were checked after each test to ensure that the cone was stable and fell within the minimum allowable accuracies set in ISO 19901-8 (2014) for the testing soil type which is summarised in the following table.

| Application Class | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|--------------------------------------|
| 1 | Intended for very soft to soft soil deposits. Class 1 penetration tests are normally not achievable for mixed bedded soil profiles with weak to strong layers (although predrilling through these layers can overcome the problem). Tests can only be performed as PCPT | | |
| 2 | Intended for precise evaluation for mixed bedded soil profiles with weak to strong layers, in terms of profiling and material identification. Interpretation in terms of soil parameters is also possible, with restriction to indicative use for the soft to weak layers. The test type should be PCPT | | |
| 3 | Intended for evaluation of mixed bedded soil profiles with soft to stiff clays and loose to dense sands, in terms of profiling and material identification. Interpretation in terms of soil parameters is appropriate for very stiff to hard clay and for dense to very dense sand layers. For stiff clays or silts and loose sands, only an indicative qualitative interpretation can be undertaken using data acquired under this application class. The test type should be PCPT but in some cases CPT may be acceptable | | |
| Application Class | Test Type | Measured parameter | Allowable min. accuracy ^a |
| 1 | PCPT | Cone resistance | 35 kPa or 5% |
| | | Sleeve friction | 5 kPa or 10% |
| | | Pore pressure | 25 kPa or 5% |
| 2 | CPT or PCPT | Cone resistance | 100 kPa or 5% |
| | | Sleeve friction | 15 kPa or 15% |
| | | Pore pressure ^b | 50 kPa or 5% |
| 3 | CPT or PCPT | Cone resistance | 200 kPa or 5% |
| | | Sleeve friction | 25 kPa or 15% |
| | | Pore pressure ^b | 100 kPa or 5% |
| ^a Larger value of the two quoted. Percentage values apply to measured value and not measured range ^b Pore pressure can only be measured if PCPT is used | | | |

Derived Results – Net Cone Resistance

The net cone resistance (q_{net}) is computed by correcting measured cone resistance (q_c) for pore water pressure effects on the net areas of the cone face and behind the shoulder of the cone (Lunne et al., 1997). Effects of overburden pressure are also removed to standardise the cone resistance as a function of depth.

The process for calculating q_{net} from a test zeroed at the bottom of a borehole is:

$$q_t = q_c + (h \cdot \alpha \cdot \gamma_w) + (1 - \alpha) \cdot (u_2 + h \cdot \gamma_w)$$

which can be simplified to:

$$q_t = q_c + (1 - \alpha) \cdot u_2 + h \cdot \gamma_w$$

where:

q_t = corrected cone resistance (for pore water pressure effects)

q_c = measured cone resistance

α = net area ratio of cone

u_2 = measured pore pressure behind the cone tip

h = depth (below seabed) at start of test

γ_w = unit weight of water

then:

$$q_{net} = q_t - \sigma_{v0}$$

where:

q_{net} = net cone resistance

σ_{v0} = in situ vertical total stress (referenced to seabed)

Derived Results – Friction Ratio

The friction ratio (R_f) is the ratio of the sleeve friction divided by corrected cone resistance.

Therefore:

$$R_f = \frac{f_s}{q_t}$$

The ratio can be used for soil classification (Schmertmann, 1978). Sand typically gives a friction ratio of less than 2 percent, while the friction ratio of clays is normally between 2 to 5 percent, depending on cone resistance. Clays with a high silt content show a lower friction ratio.

Derived Results – Pore Pressure Ratio

The pore pressure ratio (B_q) is the ratio of the excess pore water pressure (i.e. the water pressure in excess of theoretical hydrostatic pressure) to the net cone resistance (Senneset et al., 1982).

The process for calculating B_q is:

$$\Delta u = u_2 - z \cdot \gamma_w$$

then:

$$B_q = \frac{\Delta u}{q_{net}}$$

where:

γ_w = unit weight of water

Δu = excess pore pressure

u_2 = measured pore pressure

z = test depth below bottom of the borehole

q_{net} = net cone resistance

The pore pressure ratio is a good indicator for the soil type in layered soils. Clays show a positive pore pressure ratio (except stiff overconsolidated clays which may give small or negative values if dilatant during shear) and sands (except very loose or very silty sands) a negative pore pressure ratio. Sharp changes normally observed at layer changes accurately define the layer boundaries. The ratio can also be used to provide an indication of the overconsolidation ratio of clays (Lunne et al., 1985; Rad et al., 1985).

Undrained Shear Strength Profile

In addition to the direct measurements of undrained shear strength performed by laboratory testing, the undrained shear strength has also been derived from PCPT data in cohesive soil layers.

Undrained shear strength can be estimated from PCPT data using the following relationship (Lunne et al., 1997).

$$s_u = \frac{q_{net}}{N_{kt}}$$

where:

q_{net} = net cone resistance

N_{kt} = cone factor

Typically, a range $15 < N_{kt} < 20$ was used.

Relative Density Plot

In situ relative density can be determined from the results of PCPTs based on the cone resistance as follows (Jamiolkowski et al., 2003):

$$D_r(dry) = \frac{1}{0.0296} \cdot \ln \left[q_c / \left[2.494 \cdot \left[\frac{\sigma'_{v0} \cdot \left[\frac{1 + 2 \cdot K_0}{3} \right]^{0.467}}{100} \right] \right] \right]$$
$$D_r(saturated) = \left[\frac{-1.87 + 2.32 \cdot \ln \frac{1000 \cdot q_c}{(100 \cdot \sigma'_{v0})^{0.5}}}{100} + 1 \right] \cdot D_r(dry)$$

where:

$D_r(dry)$ = Estimated dry relative density (%)

$D_r(saturated)$ = Estimated saturated relative density (%)

q_c = Measured cone resistance (MPa)

σ'_{v0} = Vertical effective overburden stress (kPa)

K_0 = Coefficient of lateral earth pressure (1.0)

C.6 Dissipation Testing

The dissipation test measures the decay of pore water pressure over a specified amount of time.

A PDDPT was undertaken during a PCPT at a selected depth as directed by the onboard client representative. To start the test the penetration during the selected PCPT was stopped and the initial pore pressure was recorded. The pore water pressure (u_2) was then continuously measured against time in seconds. When the required dissipation value has been met, in this case it was at least 60% dissipation, the dissipation test is deemed complete and the PCPT penetration resumes to complete the PCVPT as required.

Dissipation results are presented in Appendix A.

C.7 References

ASTM, 2009, "ASTM D2488 – 09a Standard Practice for Description and Identification of Soils (Visual-Manual Procedure)", ASTM International, Houston, ASTM.

ASTM D2850, Standard Test Method for Unconsolidated-Undrained Triaxial Compression Test on Cohesive Soils, ASTM International, West Conshohocken, PA, 2015, www.astm.org

International Standards Organisation (ISO), 2017, "Geotechnical investigation testing – Identification and classification of soil – Part 1: Identification and description, International Standard ISO 14688-1:2017", Geneva, ISO.

International Standards Organisation (ISO), 2017, "Geotechnical investigation testing – Identification and classification of soil – Part 2: Principles for a classification, International Standard ISO 14688-2:2017", Geneva, ISO.

International Standards Organisation (ISO), 2006, "Geotechnical investigation and testing - Sampling methods and groundwater measurements – Part 1: Technical principles for execution, International Standard ISO 22475-1:2006", Geneva, ISO

International Standards Organisation (ISO), 2014, "Geotechnical investigation testing – Laboratory testing of soil - Part 1: Determination of water content, International Standard ISO 17892-1:2014", Geneva, ISO.

International Standards Organisation (ISO), 2014, "Geotechnical investigation testing – Laboratory testing of soil - Part 2: Determination of bulk density, International Standard ISO 17892-2:2014", Geneva, ISO.

International Standards Organisation (ISO), 2014, "Petroleum and Natural Gas Industries – Specific Requirements for Offshore Structures – Part 8: Marine Soil Investigations, International Standard ISO 19901-8:2014", Geneva, ISO

Lunne, T. and Christoffersen, H.P., (1983), "Interpretation of Cone Penetrometer Data for Offshore Sands.", Proceedings of 15th Offshore Technology Conference, Houston, Paper No. OTC 4464, pp. 181-192.

Lunne, T., Robertson, P.K. and Powell, J.J.M., (1997), "Cone Penetration Testing", Blackie Academic & Professional, pp. 64-67.

Rad, N.S., Eidsmoen, T., and Lunne, T., (1985), "In-situ Site Investigation Techniques and Interpretation for Offshore Practice.", Progress Report 40019-23, NGL.

Schmertmann, J.H., (1978), "Guidelines for Cone Penetration Test Performance and Design.", US Federal Highway Administration, Washington DC, Report FHWA-TS-78- 209, 145.

Senneset, K., Janbu, N. and Svano, G., (1982) "Strength and Deformation Parameters from Cone Penetration Tests.", Proceedings of 2nd European Symposium on Penetration Testing, ESOPT-II, Amsterdam, Vol.2, pp. 863-870.p
