

# Input Report

## Workspace: 72232-1-Elaborati di calcolo

### Sergnano

Study

72232-1-Elaborati di calcolo

Tab	Group	Field	Value	Units
Context of calculations	Selection of context	Weathers to use for this study	Weather folder	
		Parameters to use for this study	Parameter set	
		Obstructions to use for this study	Multi-Energy obstruction set	
Bund, building and terrain	Terrain and bund definition	Type of terrain for dispersion	Default terrain	
		Type of pool substrate and bunds	No bund	
Toxic parameters	Indoor toxic calculations	Specify the downwind building type	Unselected	
		Building type (downwind building type)	Buildings\Building type	
Dispersion	Distances of interest	Distances of interest		m

### Trattamento

Pressure vessel

72232-1-Elaborati di calcolo\Sergnano

Tab	Group	Field	Value	Units
Material	Material	Material	GAS NATURALE STOGIT	
		Specify volume inventory?	No	
		Mass inventory	100000	kg
		Volume inventory	1797,83	m <sup>3</sup>
		Material to track	GAS NATURALE STOGIT	
	Phase	Specified condition	Pressure/temperature	
		Temperature	25	degC
		Pressure (gauge)	70	bar
		Fluid state	Vapour	
		Liquid mole fraction	0	fractio n



Audit Number: 45642

Date: 24/03/2022 Time: 15:48

Page 1 of 10

Scenario	Pipe dimensions	Pipe length		m
	Release location	Elevation	1	m
		Tank head	0	m
	Direction	Outdoor release direction	Horizontal	
		Outdoor release angle	0	deg
Discharge parameters	Model settings	Atmospheric expansion method	DNV GL recommended	
		Phase change upstream of orifice?	Disallow liquid phase change only (metastable liquid)	
	Droplet break-up mechanism	Droplet break-up mechanism - instantaneous	Use flashing correlation	
		Droplet break-up mechanism - continuous	Do not force correlation	
Short pipe	Pipe characteristics	Pipe roughness	0,045	mm
	Frequencies	Frequency of bends in pipe	0	/m
		Frequency of couplings in pipe	0	/m
		Frequency of junctions in pipe	0	/m
	Frequencies of valves	Frequency of excess flow valves	0	/m
		Frequency of non-return valves	0	/m
		Frequency of shut-off valves	0	/m
	Velocity head losses	Excess flow valve velocity head losses	0	
		Non-return valve velocity head losses	0	
		Shut-off valve velocity head losses	0	
Time varying releases	Modelling of time-varying leaks and line ruptures	Vacuum relief valve	Operating	
		Vacuum relief valve set point	0	bar
	Inventory data for time-varying releases	Tank volume	1797,83	m <sup>3</sup>
		Tank vapour volume	1797,83	m <sup>3</sup>
		Tank liquid volume	0	m <sup>3</sup>
		Tank liquid level	0	m
		Maximum vapour release height		m
		Minimum mass inventory	0,1	kg
		Maximum mass inventory	1E+09	kg
	Safety system modelling for time-varying releases	Safety system modelling (isolation and blowdown)	No	

Dispersion	Dispersion scope	Concentration of interest		ppm
		Averaging time for concentration of interest		
		Specify user-defined averaging time	No	
		User defined averaging time		s
	Distances of interest	Distances of interest		m
	Averaging time for reports	ERPG [1 hr]	No	
		IDLH [30 mins]	No	
		STEL [15 mins]	No	
Bund, building and terrain	Terrain and bund definition	Type of terrain for dispersion	Default terrain	
		Type of pool substrate and bunds	No bund	
	Building definition	Release building		
		In-building release?	Outdoor	
		Building wake effect	None	
		Wind or release angle from North	0 deg	
		Handling of droplets	Trapped	
		Indoor mass modification factor	3	
Explosion parameters	Explosion method (Consequence calculations only)	Explosion method	Multi-Energy: Uniform confined	
	Ignition	Supply late ignition location	No ignition location	
		Location of late ignition		m
	Vapour liquid method	Use explosion mass modification factor	Yes	
		Explosion mass modification factor	3	
Fireball	Result types to calculate	Calculate probit	No	
		Calculate dose	No	
		Calculate lethality	No	
	Radiation levels	Number of input radiation levels	3	
		Intensity levels	4; 12,5; 37,5	kW/m <sup>2</sup>
		Probit levels	2,73; 3,72; 7,5	
		Dose levels	1,27E+06; 5,8E+06; 2,51E+07	
		Lethality levels	0,01; 0,1; 0,99	fraction
	Parameters	Mass modification factor	3	

		Fireball maximum exposure duration	20	s
	Calculation method	Fireball model	Martinsen time varying	
		TNO model flame temperature	1726,85	degC
Jet fire	Jet fire method	Jet fire method	Cone model	
	Result types to calculate	Calculate probit	No	
		Calculate dose	No	
		Calculate lethality	No	
	Radiation levels	Number of input radiation levels	5	
		Intensity levels	3; 5; 7; 12,5; 37,5	kW/m <sup>2</sup>
		Probit levels	2,73; 3,72; 7,5	
		Dose levels	1,27E+06; 5,8E+06; 2,51E+07	
		Lethality levels	0,01; 0,1; 0,99	fraction
	Parameters	Rate modification factor	3	
		Jet fire maximum exposure duration	20	s
	Cone model data	Crosswind angle	0	deg
		Horizontal options	Use standard method	
		Correlation	Recommended	
		Flame-shape adjustment if grounded	Yes	
	Surface emissive power	Calculation method for surface emissive power	Calculate SEP	
		Flame emissive power		kW/m <sup>2</sup>
		Emissivity fraction		fraction
Pool fire	Result types to calculate	Calculate probit	No	
		Calculate dose	No	
		Calculate lethality	No	
	Radiation levels	Number of input radiation levels	5	
		Intensity levels	3; 5; 7; 12,5; 37,5	kW/m <sup>2</sup>
		Probit levels	2,73; 3,72; 7,5	
		Dose levels	1,27E+06; 5,8E+06; 2,51E+07	
		Lethality levels	0,01; 0,1; 0,99	fraction

Parameters	Radiative fraction for general fires	0,4	fraction
	Pool fire maximum exposure duration	20	s
Geometry	Geometry	East	0 m
		North	0 m

## 50 mm

Leak

72232-1-Elaborati di calcolo\Sergnano\Trattamento

Tab	Group	Field	Value	Units
Scenario	Hole	Orifice diameter	50	mm
		Use specified discharge coefficient?	Yes	
		Discharge coefficient	0,62	fraction
	Release location	Elevation	1	m
		Tank head	0	m
	Direction	Outdoor release direction	Horizontal	
		Outdoor release angle	0	deg
Material	Material	Material characteristics	Flammable only	
		Material to track	GAS NATURALE STOGIT	
		Type of risk effects to model	Flammable only	
	Phase	Phase to be released	Vapour	
Discharge parameters	Model settings	Atmospheric expansion method	DNV GL recommended	
		Phase change upstream of orifice?	Disallow liquid phase change only (metastable liquid)	
	Droplet break-up mechanism	Droplet break-up mechanism - continuous	Do not force correlation	
Dispersion	Dispersion scope	Concentration of interest		ppm
		Averaging time for concentration of interest		
		Specify user-defined averaging time	No	
		User defined averaging time		s
	Distances of interest	Distances of interest		m
	Averaging time for reports	ERPG [1 hr]	No	
		IDLH [30 mins]	No	



Bund, building and terrain	Terrain and bund definition	STEL [15 mins]	No
	Type of terrain for dispersion	Default terrain	
Explosion parameters	Explosion method	Type of pool substrate and bunds	No bund
	Explosion method	Multi-Energy: Uniform confined	
	Ignition	Supply late ignition location	No ignition location
		Location of late ignition	m
	Vapour liquid method	Use explosion mass modification factor	Yes
		Explosion mass modification factor	3
Fireball	Result types to calculate	Calculate probit	No
		Calculate dose	No
		Calculate lethality	No
	Radiation levels	Number of input radiation levels	3
		Intensity levels	4; 12,5; 37,5
			kW/ m2
		Probit levels	2,73; 3,72; 7,5
		Dose levels	1,27E+06; 5,8E+06; 2,51E+07
		Lethality levels	0,01; 0,1; 0,99
			fractio n
	Parameters	Mass modification factor	3
		Fireball maximum exposure duration	20 s
	Calculation method	Fireball model	Martinsen time varying
		TNO model flame temperature	1726,85 degC
Jet fire	Jet fire method	Jet fire method	Cone model
	Result types to calculate	Calculate probit	No
		Calculate dose	No
		Calculate lethality	No
	Radiation levels	Number of input radiation levels	5
		Intensity levels	3; 5; 7; 12,5; 37,5
			kW/ m2
		Probit levels	2,73; 3,72; 7,5
		Dose levels	1,27E+06; 5,8E+06; 2,51E+07
		Lethality levels	0,01; 0,1; 0,99
			fractio n

	Parameters	Rate modification factor	3
		Jet fire maximum exposure duration	20 s
	Cone model data	Correlation	Recommended
		Horizontal options	Use standard method
		Flame-shape adjustment if grounded	Yes
	Surface emissive power	Calculation method for surface emissive power	Calculate SEP
		Flame emissive power	kW/m <sup>2</sup>
		Emissivity fraction	fraction
Pool fire	Result types to calculate	Calculate probit	No
		Calculate dose	No
		Calculate lethality	No
	Radiation levels	Number of input radiation levels	5
		Intensity levels	3; 5; 7; 12,5; 37,5 kW/m <sup>2</sup>
		Probit levels	2,73; 3,72; 7,5
		Dose levels	1,27E+06; 5,8E+06; 2,51E+07
		Lethality levels	0,01; 0,1; 0,99 fraction
	Parameters	Radiative fraction for general fires	0,4 fraction
		Pool fire maximum exposure duration	20 s

## FB 203 mm

Leak

72232-1-Elaborati di calcolo\Sergnano\Trattamento

Tab	Group	Field	Value	Units
Scenario	Hole	Orifice diameter	203	mm
		Use specified discharge coefficient?	Yes	
		Discharge coefficient	1	fraction
	Release location	Elevation	1	m
		Tank head	0	m
	Direction	Outdoor release direction	Horizontal	



		Outdoor release angle	0 deg
Material	Material	Material characteristics	Flammable only
		Material to track	GAS NATURALE STOGIT
		Type of risk effects to model	Flammable only
	Phase	Phase to be released	Vapour
Discharge parameters	Model settings	Atmospheric expansion method	DNV GL recommended
		Phase change upstream of orifice?	Disallow liquid phase change only (metastable liquid)
	Droplet break-up mechanism	Droplet break-up mechanism - continuous	Do not force correlation
Dispersion	Dispersion scope	Concentration of interest	ppm
		Averaging time for concentration of interest	
		Specify user-defined averaging time	No
		User defined averaging time	s
	Distances of interest	Distances of interest	m
	Averaging time for reports	ERPG [1 hr]	No
		IDLH [30 mins]	No
		STEL [15 mins]	No
Bund, building and terrain	Terrain and bund definition	Type of terrain for dispersion	Default terrain
		Type of pool substrate and bunds	No bund
Explosion parameters	Explosion method	Explosion method	Multi-Energy: Uniform confined
	Ignition	Supply late ignition location	No ignition location
		Location of late ignition	m
	Vapour liquid method	Use explosion mass modification factor	Yes
		Explosion mass modification factor	3
Fireball	Result types to calculate	Calculate probit	No
		Calculate dose	No
		Calculate lethality	No
	Radiation levels	Number of input radiation levels	3
		Intensity levels	4; 12,5; 37,5 kW/m <sup>2</sup>
		Probit levels	2,73; 3,72; 7,5

		Dose levels	1,27E+06; 5,8E+06; 2,51E+07	
		Lethality levels	0,01; 0,1; 0,99	fraction
	Parameters	Mass modification factor	3	
		Fireball maximum exposure duration	20	s
	Calculation method	Fireball model	Martinsen time varying	
		TNO model flame temperature	1726,85	degC
Jet fire	Jet fire method	Jet fire method	Cone model	
	Result types to calculate	Calculate probit	No	
		Calculate dose	No	
		Calculate lethality	No	
	Radiation levels	Number of input radiation levels	5	
		Intensity levels	3; 5; 7; 12,5; 37,5	kW/ m <sup>2</sup>
		Probit levels	2,73; 3,72; 7,5	
		Dose levels	1,27E+06; 5,8E+06; 2,51E+07	
		Lethality levels	0,01; 0,1; 0,99	fraction
	Parameters	Rate modification factor	3	
		Jet fire maximum exposure duration	20	s
	Cone model data	Correlation	Recommended	
		Horizontal options	Use standard method	
		Flame-shape adjustment if grounded	Yes	
	Surface emissive power	Calculation method for surface emissive power	Calculate SEP	
		Flame emissive power		kW/ m <sup>2</sup>
		Emissivity fraction		fraction
Pool fire	Result types to calculate	Calculate probit	No	
		Calculate dose	No	
		Calculate lethality	No	
	Radiation levels	Number of input radiation levels	5	
		Intensity levels	3; 5; 7; 12,5; 37,5	kW/ m <sup>2</sup>
		Probit levels	2,73; 3,72; 7,5	

	Dose levels	1,27E+06; 5,8E+06; 2,51E+07	
	Lethality levels	0,01; 0,1; 0,99	fraction
Parameters	Radiative fraction for general fires	0,4	fraction
	Pool fire maximum exposure duration	20	s