

PROPONENTE: **AME ENERGY S.r.l.**

Via Pietro Cossa, 5 20122 Milano (MI) - ameenergysrl@legalmail.it - PIVA 12779110969

REGIONE CAMPANIA
PROVINCIA DI SALERNO
COMUNE DI CAGGIANO

Titolo del Progetto:

REALIZZAZIONE DI UN IMPIANTO EOLICO UBICATO NEL COMUNE DI CAGGIANO (SA) IN LOCALITA' "TEMPA DEL VENTO", CON POTENZA NOMINALE PARI A 46.2 MW

Documento:

PROGETTO DEFINITIVO

N° Documento:

CAGEO-T008

ID PROGETTO:

105

DISCIPLINA:

PD

TIPOLOGIA:

R

FORMATO:

A4

Elaborato:

**PRELIMINARY WIND RESOURCE ASSESSMENT
RELAZIONE ANEMOLOGICA**

FOGLIO:

18

SCALA:

-

Nome file:

CAGEO-T008.pdf

Progettazione:

IPROJECT S.R.L.



**Consulenza, Progettazione e Sviluppo Impianti
ad Energia Rinnovabile**

Sede Legale: Via Del Vecchio Politecnico, 9 - 20121 Milano (MI)

P.IVA 11092870960-PEC: i-project@legalmail.it

Sede Operativa: Via Bisceglie n° 17 - 84044 Albanella (SA)

-mail: a.manco@iprojectsrl.com

Cell: 3384117245

Progettista:

Arch. Antonio Manco



Rev:	Data Revisione	Descrizione Revisione	Redatto	Controllato	Approvato
0	15/07/2023	Prima emissione	Vector Renewables Italia srl	Vector Renewables Italia srl	Arch. Antonio Manco



PRELIMINARY WIND
RESOURCE ASSESSMENT
Caggiano

June 2023

Details

A.1.1 Prepared for:

Client: i-Project S.r.l.

Contact: Antonio Manco

Reference: VRIT230241

A.1.2 Prepared by:

Vector Renewables Italia S.r.l.

Via Alberto Falck, 4/16, Sesto San Giovanni, Milano • +39 02 87 36 68 56

Contact details

Contact Name	Position	Email
Marco Guarneroli	Country Manager - Italy	mguarneroli@vectorenrenewables.com
Chiara Pavani	Head of Technical Advisory - Italy	cpavani@vectorenrenewables.com
Nell Franchi	Technical Advisory - Italy	nfranchi@vectorenrenewables.com
Gianmarco Palma	Technical Advisory - Italy	gpalma@vectorenrenewables.com

Version control

Version	Description	Date	Drafted	Reviewed	Approved
V00	Initial version	15/05/2023	NF	GP	CP
V01	Energy Assessment	30/06/2023	NF	GP	CP

Disclaimer

The contents of this document have been prepared by Vector Renewables Italia S.r.l. (hereinafter, "Vector Renewables") based on its knowledge, the present project information, as well as the current legislation and the wind and photovoltaic market according to its experience in the renewable energy sector and, particularly, in the auditing and consultancy of wind and photovoltaic facilities. Therefore, the results, analysis and comments included in this document shall be solely interpreted under such considerations.

Estimates, conclusions, and recommendations included in this document are based on information which has been considered correct, provided by reliable and verified databases as well as the best practice standards and estimates by Vector Renewables. Notwithstanding the above, it is not possible to guarantee the integrity and accuracy of such information, especially in relation to forecasts or future projections as long as the whole information needed or required for its production has not been received or its accuracy not verified. In this sense, Vector Renewables, its partners, affiliates, directors, or employees are not responsible for the accuracy, completeness or veracity of the information contained herein or conclusions or decisions made, based on false, incomplete or inaccurate information.

The content of this document is strictly limited to the matters that are addressed herein. In this sense, in no case should be understood that the content can be applied by analogy to other issues that it does not make explicit reference. The content of this document does not necessarily cover every matter of the topics dealt herein.

Vector Renewables, its partners, affiliates, directors or employees accept no responsibility for the results that any interested third party may produce, either for direct damages or for any damages which, directly or indirectly, could be derived from decisions or considerations based on this document, or any use that the recipient may make of this document.

With regards to the liability Vector Renewables may be made responsible for as an independent Technical Advisor, this will not exceed, under any circumstance, the fees agreed to carry out the services for which Vector Renewables has been hired, and in any case, will exclude indirect or consequential damages, lost profits, damages or opportunity costs. Vector Renewables will respond solely and exclusively to the recipient or the petitioner of the service excluding any liability towards any third party involved directly or indirectly in the project.

This document has an informative and confidential nature and does not represent a report for qualified expert opinion purposes to be used in a court or at a trial, nor is it a legal or a fiscal report. It is therefore, intended solely and exclusively for such purposes to the recipient or borrower, with its exhibition, distribution, or reproduction without the prior written consent of Vector Renewables being prohibited. The use of this document for others than those uses agreed will need prior written consent by Vector Renewables.

In case of using this document for other purposes not agreed or without prior written consent by Vector Renewables will lead to Vector Renewables to be entitled to claim an additional 20% to the fees received for the elaboration of this document, all without prejudice to legal action under the applicable law that may correspond for any damages that were caused.

The reception of this document by its recipient implies the full acceptance of this "Disclaimer".

Contents

1. Foreword	4
2. Wind resource assessment	5
3. Layout	9
4. Wind Turbine Models	11
5. Preliminary expected energy yield assessment	13
6. Conclusions	16

1. FOREWORD

I-Project S.r.l. (the "**Client**") engaged Vector Renewables Italia S.r.l. as "**Technical Advisor**" (or "**TA**") to perform a preliminary analysis for the definition of the wind resource of the Caggiano wind site (the "**Project**") in development in Italy.

The activity consisted in the preliminary estimation of the expected wind statistics at the site extrapolated from a Virtual Met Mast downscaled to a location deemed as representative of the wind farm, according to the **Technical Advisor's** analysis on the long-term wind regime representative of the area.

The whole study was carried out with professional approach and instruments, as prescribed by the international methodologies for a trustworthy assessment of expected wind farm production.

Being the assessment based on re-analysis data characterized by a higher level of uncertainty compared to a measurement on site, the presented wind resource shall be considered as preliminary, and the analysis should be updated when a full year measurement campaign onsite is available.

2. WIND RESOURCE ASSESSMENT

The supplied material useful for this preliminary assessment of the wind resource includes:

1. Area of the wind site

As requested by the Client, the wind assessment has been performed by adopting the WASP 12 model propagation as embedded in WindPRO 3.6. The height contours and roughness maps to be included in the wind flow model were not provided and therefore they were downloaded from online sources covering an area of about 20 km x 20 km. In particular, the elevation map was retrieved from the TINITALY Model with a 10 m vertical spacing for the wind farm area while the roughness map was downloaded from the Corine Land Cover 2018 database and its values adjusted to the site based on satellite images.

The proposed area extends on a mountain, with turbine elevation ranging from 600 m to 1260 m. The orography of the site can be classified as very complex with medium to low terrain roughness.

No information has been provided regarding other neighbouring turbines in operation or even in development phase and no site inspection has been carried out at this stage in order to verify this or presence of any other obstacle that might affect the **Project**. From public database and aerial pictures publicly available online it is observed that there aren't operating turbines in the area within a radius of approximately 6 km distance from the **Project**.

The location of the proposed site area is shown in Figure 1.

Considering that a measurement campaign recorded onsite is not yet available, the preliminary estimation of the wind resource of the Project is extrapolated from a Virtual Met Mast downscaled to a representative location of the Caggiano site at 100 m height. The Virtual Met Mast statistics are usually obtained by using the sources available in the area deemed as representative, such as land-based wind data and mesoscale data. For the Project, 10-year Vortex Series ERA-5 hourly time series has been acquired.

The long-term wind regime expected onsite has been assessed using the Virtual Met Mast characterized by a long-term wind speed at 100 m of 5.44 m/s, whose Weibull distribution, energy and wind roses split into five wind speed classes and 12 sectors are reported below. It is observed the prevailing winds are from the northern and southern sectors.




Fig. 2 - Wind conditions at the Virtual Met Mast at 100 m

The following figure shows the estimated wind resource on the site area.




Fig. 3 - Wind resource map

3. LAYOUT

Based on the wind map provided in SECTION 2, the Client has designed and supplied a layout for the Project consisting in n. 7 wind turbines. The coordinates of the proposed layout are reported in the table below:

UTM WGS84 ZONE 33			
Turbine ID	Longitude [m]	Latitude [m]	Elevation [m a.s.l.]
T1	543476	4489729	1130
T2	544127	4489708	1108
T3	544708	4489550	976
T4	543994	4488272	1008
T5	544490	4488031	1087
T6	545296	4487523	1170
T7	545239	4486470	1166

Tab. 1 – Caggiano wind farm coordinates

The location of the proposed turbines in red is shown in Fig. 4.



Fig. 4 - Proposed wind turbines

Technical Advisor's standard requirements for distances between turbines are five rotor diameters in the prevailing wind direction, and three rotor diameters in directions perpendicular to the prevailing. The next table shows the distances separating the wind turbines in diameters of 170 m rotor.

RD=170m\Meter	T1	T2	T3	T4	T5	T6	T7
T1	-	651	1245	1546	1978	2860	3705
T2	3.8	-	602	1442	1716	2478	3424
T3	7.3	3.5	-	1464	1535	2111	3125
T4	9.1	8.5	8.6	-	551	1502	2190
T5	11.6	10.1	9.0	3.2	-	953	1731
T6	16.8	14.6	12.4	8.8	5.6	-	1055
T7	21.8	20.1	18.4	12.9	10.2	6.2	-


Tab. 2 - Spacings in rotor diameter and meters of Caggiano wind farm

All turbines are spaced by at least three rotor diameters. Considering the most energetic sector from NNE, all turbines fully meet the above requirements.

Anyway, it is recommended to obtain the turbine manufacturer's Mechanical Load assessment and site suitability Analysis (MLA), in order to ensure that the desired wind turbine model and the proposed layout will be suitable for the site according to IEC 61400-1 Standard Ed.3 and that the fatigue loads, resulting from the wind conditions onsite and acting on the turbine main components, are within the design load envelope.


4. WIND TURBINE MODELS

The expected energy production of the wind farm is estimated considering the following two wind turbine models requested by the Client, whose power and thrust curves have been derived from the WindPRO database and adjusted at the site air density of 1.09 kg/m³ according to the IEC 61400-12 method correction.

Turbine type		SG 6.6-170	Diameter [m]	170.0
Rated power [MW]		6.6	Hub height [m]	115.0
Rated wind speed [m/s]		15.5	IEC class	S
Cut-in/Cut-out wind speed [m/s]		3.0/23.0	Air density [kg/m ³]	1.225
Bin wind speed [m/s]	Power [kW]	Thrust coefficient [-]		
0	0	0		
1	0	0		
2	0	0		
3	89	0.953		
4	328	0.847		
5	758	0.824		
6	1376	0.833		
7	2230	0.837		
8	3346	0.825		
9	4600	0.766		
10	5660	0.648		
11	6272	0.506		
12	6510	0.383		
13	6579	0.294		
14	6596	0.231		
15	6599	0.186		
16	6600	0.155		
17	6600	0.132		
18	6600	0.115		
19	6336	0.087		
20	6072	0.072		
21	5808	0.060		
22	5544	0.050		
23	5280	0.042		

Tab. 3 – SGRE SG 6.6-170, power and C_t curves

Turbine type		V162-6.2	Diameter [m]	162.0
Rated power [MW]		6.2	Hub height [m]	119.0
Rated wind speed [m/s]		12.5	IEC class	S
Cut-in/Cut-out wind speed [m/s]		3.0/24.0	Air density [kg/m³]	1.225
Bin wind speed [m/s]	Power [kW]	Thrust coefficient [-]		
0	0	0		
1	0	0		
2	0	0		
3	34	0.908		
4	292	0.853		
5	676	0.819		
6	1229	0.812		
7	2000	0.807		
8	3017	0.799		
9	4284	0.775		
10	5483	0.657		
11	6114	0.504		
12	6197	0.370		
13	6200	0.283		
14	6200	0.223		
15	6200	0.180		
16	6200	0.148		
17	6186	0.124		
18	5853	0.100		
19	5348	0.078		
20	4825	0.062		
21	4251	0.048		
22	3664	0.037		
23	3064	0.029		
24	2451	0.022		



Tab. 4 – Vestas V162-6.2, power and C_t curves

5. PRELIMINARY EXPECTED ENERGY YIELD ASSESSMENT

The expected energy production of the Caggiano wind farm has been estimated with the wind turbine configuration requested, using the long-term wind statistics of the Virtual Met Mast and adopting the WAsP 12 model propagation as embedded in WindPRO 3.6. The wake model implemented in the analysis is the N.O. Jensen (RISO/EMD) Park2 2018 wake model with DTU default onshore wake decay constant of 0.090.

The energy production accounts for the losses due to wake effects and to the site air density.

The tables hereunder contain the following information for each wind turbine:

Site ID: ID number of the wind turbine in the table

X [m]: longitude in **UTM WGS84 ZONE 33** coordinates

Y [m]: latitude in **UTM WGS84 ZONE 33** coordinates

Elev. [m]: elevation above sea level (ASL)

HH [m]: hub height

V [m/s]: average wind speed estimated by the model at hub height

Gross Production [GWh]: expected gross output, gross and net of wake losses

Loss [%]: percent of production lost due to wake losses

Equivalent Hours [h]: equivalent annual hours of gross production, net of wake losses

ID	X [m]	Y [m]	Elev. [m]	HH [m]	V [m/s]	Gross Production [GWh]		Loss [%]	Net Hours [h]
						Gross of wakes	Net of wakes		
T1	543476	4489729	1130	115.0	6.79	19.60	19.35	1.27	2932
T2	544127	4489708	1108	115.0	6.72	19.17	18.34	4.32	2779
T3	544708	4489550	976	115.0	6.00	16.00	14.97	6.47	2268
T4	543994	4488272	1008	115.0	5.38	12.79	12.30	3.81	1864
T5	544490	4488031	1087	115.0	5.75	14.65	13.92	4.99	2109
T6	545296	4487523	1170	115.0	5.90	15.27	14.53	4.88	2201
T7	545239	4486470	1166	115.0	5.93	15.42	15.19	1.45	2302
Average					6.07	16.13	15.51	3.88	2351
Total						112.90	108.60		

Tab. 5 – Caggiano energy production – SGRE SG 6.6-170

ID	X [m]	Y [m]	Elev. [m]	HH [m]	V [m/s]	Gross Production [GWh]		Loss [%]	Net Hours [h]
						Gross of wakes	Net of wakes		
T1	543476	4489729	1130	115.0	6.80	18.25	18.03	1.18	2909
T2	544127	4489708	1108	115.0	6.73	17.84	17.13	4.01	2762
T3	544708	4489550	976	115.0	6.02	14.91	14.02	5.97	2261
T4	543994	4488272	1008	115.0	5.41	11.92	11.50	3.50	1855
T5	544490	4488031	1087	115.0	5.78	13.66	13.04	4.53	2103
T6	545296	4487523	1170	115.0	5.92	14.23	13.59	4.47	2192
T7	545239	4486470	1166	115.0	5.96	14.39	14.20	1.33	2290
Average					6.09	15.03	14.50	3.57	2339
Total						105.19	101.51		

Tab. 6 – Caggiano energy production – Vestas V162-6.2

It should be noted that the energy production presented above accounts only for the losses due to wake effects and air density and no other losses are included.

Overall the wake losses are deemed as acceptable with a maximum wake loss of 6.5% with the SG 6.6-170 and of 6.0% with 162-6.2 found at turbine T3.

The next step in the analysis is to assess the energy losses to determine the energy that will be available for input into the power grid. At this preliminary phase a reasonable assumption of additional loss of the plant for a period of 10 years is equal to **10%**, including losses relating to the availability of the plant (wind turbines, B.O.P. and grid), the performance of wind turbines, electrical and environmental losses and excluding potential limitations. A more detailed assessment can be made at a more advanced design stage and once all supply and O&M contracts for the project have been signed or under discussion.

The following table summarizes the results obtained for the Project:

Configuration	Wind farm capacity [MW]	Gross production (net of wakes)		Net production (deliverable to grid)	
		[GWh/year]	[h/year]	[GWh/year]	[h/year]
SGRE SG 6.6-170	46.20	108.60	2351	97.74	2116
Vestas V162-6.2MW	43.40	101.51	2339	91.36	2105

Tab. 7 – Gross and Net energy production

The expected net production estimates (deliverable to grid) shown in the table above, represent the so-called $P_{50\%}$, i.e. the production calculated with the average wind conditions, also called central estimate.

Without measurements on site, it is not possible to provide an accurate evaluation of the uncertainty of the wind and energy assessment.

In any case, an exercise has been undertaken evaluating the main uncertainty sources according as far as possible to IEC WG15 outcoming standards in order to provide an indicative average uncertainty value for a 10-year period.

In this context, the uncertainty of a parameter is defined as the estimate of the standard deviation of the corresponding statistical distribution. A sensitivity factor of 1.9 has been estimated to convert the uncertainty related to the wind speed into energy uncertainty.

Under these assumptions, and considering such sensitivity factor, the assessment of an indicative uncertainty for the 10-year period provides a value of about **25.5%**.

6. CONCLUSIONS

The activity of the current assessment consisted in the preliminary wind resource assessment of the Caggiano wind site. The study was based on the analysis of the long-term wind regime representative of the area at the desired hub height, according to the expected wind statistics at the site extrapolated from a Virtual Met Mast downscaled to a location deemed as representative of the wind farm. The following conclusions are made concerning the preliminary wind regime and energy production assessment:

1. It is necessary to emphasize that the Virtual Met Mast does not replace a traditional on-site measurement mast and therefore any assessment of the wind resource will have a high uncertainty. Therefore, the results shall be intended as a **preliminary estimation only**.
2. **In order to reduce the uncertainties and to achieve a bankable project, at least one met mast shall be installed onsite and update the analysis accordingly.** The location of the mast should be selected to be well exposed with respect to the prevailing wind direction and well representative of the turbine locations. The structure of such mast should be sufficiently high to reduce uncertainty related to the vertical extrapolation: a height of at least 2/3 of the proposed hub height is recommended. After the measurement period, a detailed wind and energy assessment, comprehensive of a site suitability analysis of the planned wind turbine model and layout, should be undertaken.
3. No site visit has been undertaken at this stage to verify information regarding the territory (orography, roughness, obstacles etc.) assumed in the assessment or other issues.
4. At this preliminary stage, a reasonable assumption of the additional losses related to turbine, B.O.P. and grid availability, electrical plant, environment, turbine performance and excluding any potential curtailment consists of about 10%. A more detailed evaluation could be performed when supply or O&M agreement are in place or even at a discussion phase.
5. It is recommended to obtain the turbine manufacturer's Mechanical Load assessment and site suitability Analysis (MLA), in order to ensure that the desired wind turbine model and the proposed layout will be suitable for the site according to IEC 61400-1 Standard Ed.3 and that the fatigue loads, resulting from the wind conditions onsite and acting on the turbine main components, are within the design load envelope.

Vector Renewables



Expertise and insights gained as Asset Manager of more than **3.5 GW**



70 GW of experience including solar PV and wind power services



Experience in more than 40 countries worldwide



Multidisciplinary team composed of over 200 employees



Offices in **10 countries**



15 years in the renewable energy industry

